

C. L. BEST GAS TRACTION CO.

INCORPORATED

TRACKLAYER


· C · L · B ·

ALL STEEL 75 AND 90 H-P
TRACKLAYER



PRICE LIST OF EXTRAS

NUMBER TWO



W. G. Noack, ex-Best & Cut Engineers
collection. Gift of his son 11-12-58

C. L. BEST GAS TRACTION CO.

INCORPORATED

SAN LEANDRO, CALIFORNIA, U. S. A.

MANUFACTURERS OF

• C • L • B •

ALL STEEL

• 75 AND 90 H • P •

TRACKLAYER

TRACKLAYER

PRICE LIST OF EXTRAS

PRICES SUBJECT TO CHANGE WITHOUT NOTICE

1916

MAIN OFFICE AND WORKS

SAN LEANDRO, CALIFORNIA

PHONE: SAN LEANDRO

NIGHT NUMBERS:

SAN LEANDRO 164 AND ELMHURST 1043

SAN LEANDRO 383 J

BRANCH OFFICES

SAN FRANCISCO : LOS ANGELES : WALLA WALLA, WASH.

INDEX

	PAGE
Alphabetical—Parts List	54—81
Numerical—Parts List	82—98
Miscellaneous—Parts List	98—106
Units Complete	106—114
Carburetors	42—47
Care and Operation 75 H. P. Track Layer	5
Care of Transmission, Track, Trucks and Main Drive Sprocket.....	6
Care of Differential and Main Clutch	7
Impulse Starters for K. W. Magneto	40—41
Magneto—Bosch Z R 4.....	30—48—49—50—51
Magneto—Splitdorf, Model W	31—52—53—54
Magneto—K. W. K. H. Model	32—39
Photograph—Differential and Main Sprocket, 1913 Model 75 H. P.....	8
“ Differential and Transmission, 1913 Model 75 H. P.....	9
“ Differential and Transmission, 1916 Model 75 H. P.....	10
“ Complete 75 H. P.—1913 Model	18
“ Complete 75 H. P.—1916 Model	19
“ Motor Parts	15—16—17
“ Motors Vale Cage Model	11—12
“ Motors Removable Cylinder-head Model	13—14
“ Power steer parts—New style	27
“ Side Friction Drive, 90 H. P.....	28
“ Swing Frame and Track, 90 H. P.	29
“ Tractor Parts	20—26
General Information	3—4
Instruction for Ordering Parts	3
Instruction for Returning Goods	4

GENERAL INFORMATION

In listing parts in this book, the purpose has been to simplify as much as possible the finding of any desired parts.

To accomplish this, we have listed parts in four different ways.

In the first or Alphabetical List you will find the same parts, listed under a different heading, name and description always following the part number. For example: Bushing for clutch spider, which is listed as such, will also be found at Clutch spider bushing. Cam shaft bearings will also be found under Bearings for Cam shaft. This applies to nearly every part listed in the Alphabetical List. The parts listed on this book with few exceptions are shown in the photographs.

The Numerical List contains the same items that are given in the Alphabetical List, arranged in numerical order according to the part number.

The Unit List contains only complete units; the separate parts of these units are shown in both of the above lists.

The Miscellaneous List contains parts which are not numbered and are not shown in any of the other lists.

INSTRUCTION FOR ORDERING PARTS

1. In order to avoid delay, mistakes and unnecessary correspondence, please observe the following:
2. Observe carefully the part number and the letter on the part for which you want a duplicate, compare with the photo shown of this part and be sure to state that part number and letter in your order with the description following it in the list of repairs.
3. Remember that you cannot be too particular in your specification. Be sure to designate any peculiarity of the part or piece required, such as right or left, etc.
4. State plainly your post office address (also freight station), County and State to which the goods are to be sent. State whether by Parcel Post or Express (if Express, by which Company) or Freight by what route.
5. There are several sizes of many parts and it is necessary to show on your order the full dimensions and to give a full description, also the number of your Tractor.
6. In ordering extras, be careful to use the same number and names that are used in these lists.
7. Prepay freight and express charges on sample castings or parts sent us and put your name on the back of the shipping tag.

C. L. BEST GAS TRACTION CO.

8. Always make out your orders for extras on a separate sheet and not in the body of your letter, for if put in a general letter the order may be overlooked.

TERMS

To all customers in good standing 2% discount 15 days; 30 days net.

ALL PRICES SUBJECT TO CHANGE WITHOUT NOTICE.

INSTRUCTIONS FOR RETURNING GOODS

1. Advise us in separate letter that you are returning goods to us, and why. This must be done regardless of any former correspondence. Give us the number and date of our invoice wherein we charged you with the goods.

2. Advise us the name of the carrier over which you are returning the goods to us.

3. Always prepay shipments and put your name on the back of the shipping tag. Send shipping receipt covering goods returned with your letter.

Claims for shortage or error in order must be made upon receipt of goods or same will not be considered.

The prices in this list are net and no discount will be allowed excepting the usual Cash Discount.

All shipments leave our Factory in perfect condition; should they reach you otherwise, you should make claim on the Carrier.

Broken goods should be refused or a full description of damage made by the Carrier Agent or expense bill. If this is insisted upon full damage can always be collected from the Transportation Co.

We assume no responsibility for delay or damage to merchandise while in transit. Our responsibility ceases upon delivery of same to the Transportation Companies, from whom we receive a receipt showing that shipment is in good condition when delivered to them; therefore, your claim, if any, should be made with the Transportation Company and not the C. L. Best Gas Traction Co.

We reserve the right to make changes in prices of any of the parts herein listed without advance notice.

We also reserve the right to change the construction or material of any part where it seems desirable to do so without incurring the obligation of installing such change on tractors already delivered.

The number of the Motor is stamped on a brass plate which is screwed to the cylinder next to the fly wheel. The Tractor number is painted on the front end of tractor, also on brass plate on differential gear case.

CARE AND OPERATION OF C. L. B. TRACK LAYER

Upon receiving the engine, uncrate the motor, being careful not to injure the magneto or force feed oiler. Remove the inspection door and see if there is plenty of oil in crank pits. The oil should never be lower than the pet-cock on the right hand side of motor. It can be two inches higher. Remove the spark plugs and inject at least two table-spoons full of cylinder oil in each cylinder. If the water has been drained from the motor, put a half oil-can of oil in water pump. Turn the motor over several times and the oil will work in the piston rings and through the water pump. Do this, also, if the motor has stood idle for any length of time. Fill all the grease cups on motor, also cups on the clutch shifter and the one on the clutch spider inside of the wheel. Do not fail to fill the oil cup on vertical shaft between first and second cylinder. Fill the radiator with clean water and the motor will be ready to start. Open the valve from the gasoline tank to the carburetor. Be sure the valve to the distillate tank is closed. The needle valve on carburetor should be open about $1\frac{1}{2}$ turns. The air valve adjusting screw should be tightened about half way.

Prime the cylinders through the top priming-cocks, giving each about two squirts from the gasoline can. Retard spark lever as far forward as possible. The governor lever should be set in the middle of the quadrant. Open the relief-cocks. Put the switch on battery and crank motor over with bar. When the resistance of the compression is felt, give the motor a quick turn and it will start. Then close the pet-cocks and advance the spark lever as soon as possible.

In cold weather the motor will start better if the needle valve on carburetor is opened about three-quarters of a turn more than the regular position. It should be closed back as soon as the motor exhaust starts to smoke.

IF THE MOTOR DOESN'T START

TEST THE BATTERIES. They may have run down. They should test over eight amperes.

You may have a loose wire.

Your spark plugs may be fouled.

You may be priming with distillate.

Eighty-six degrees gasoline is the best to prime with.

Always use the best cylinder oil in motor. It pays. Keep the fan belt tight. A loose belt wears out quickly. Keep the radiator full of clean water. If the motor heats, examine the water strainer. It may be fouled. It is placed there to protect the pump. See if hose between radiator and pump is collapsed or plugged.

Change the oil in crank case every ten days and wash out the crank case with coal oil. The old oil may be used on the track, but not in gear cases.

STOPPING THE MOTOR

In stopping the motor at noon or any time during the day after it has been working hard, do not stop it immediately. Close the throttle and lower the spark one-half and let the motor run idle for at least five minutes.

On a hot day if the engine has been working several hours, by shutting it down quickly, the heat in the walls of the cylinders heats the

C. L. BEST GAS TRACTION CO.

dead water, which is not circulating around the cylinders, until it is quite hot. This will melt the oil around the pistons and cylinders and it will all trickle out. Then when you start, the usual method is to prime it, which will wash the balance of the oil out of the cylinders and the result is that you have no compression. This is the most common fault of engines in starting and is caused by shutting them down suddenly when they are hot.

CARE OF TRANSMISSION

A heavy transmission oil should be used in the transmission and differential cases, as important bearings are thus lubricated. Never use heavy grease.

All grease cups should be filled daily.

While the machine is new, an excessive amount of grease and oil should be used.

The grease cups on the trucks, wheels and sprockets should be screwed down every forty or fifty minutes, so that the grease will work out at the end of the hubs. This will work out the dirt that tends to get in the bearings.

CARE OF TRACK AND TRUCKS

When the truck wheels get end play, they should be washered up with hardened washers that are sent with each machine.

If the oscillating trucks get loose sideways between the guides, the slide box, which is bolted to the channel frame, should be shimmed out, as the case may be, so as to keep the truck frame parallel. The front idler must also be kept in line and parallel, for if care is not taken in regard to these two, one track may be pulling off a few degrees to the left and the other track a few degrees to the right and the steer wheel pointing straight ahead; or both tracks may be pointing to the left and the steer wheel to the right and vice versa. For the fact that the tracks are laying themselves, it is obvious that they should be parallel. For instance, in a railroad track if the rails were continually getting narrower or continually getting wider the result would be that the flanges on the wheels would be badly worn as the rails were getting narrower, and if the rails were getting wider there would be a tremendous strain upon the side boxes trying to keep them in line.

CARE OF TRACK LINKS

If the pins in the link show any looseness, they should be tightened immediately by pounding the lip of the link down against the flat part of the pin. This is preferably done with a blacksmith's punch with a handle in it, so that it can be struck with a heavy hammer.

MAIN DRIVE SPROCKET

The main drive sprocket, which has an internal gear cast integral with it, runs loose on a hardened axle. This gear is bronze bushed and gets lubrication through the center of the axle. The pinion should be examined inside to see if it is well in mesh, and if it is not, the axle can be loosened and a shim put under it and the gear put in mesh. In order to make gears wear well and last long, they must be kept in mesh.

CARE OF THE DIFFERENTIAL

At the left-hand differential and transmission end of the differential shaft is a thrust bearing. It is under the collar that secures the bull pinion. Its purpose is to keep the side bevel gears in mesh with the pinions in the large differential gear. These gears must be kept snug in mesh. Any play can be taken up by the addition of washers to the set located between the collar and the bull pinion in the left side of the machine.


The large differential gear should be kept snug in mesh with the main drive pinion. For this purpose an annular ball bearing is used as a roller and holds the main gear in mesh with the drive pinion. For the purpose of adjustment the roller is mounted on an eccentric pin. **KEEP YOUR GEARS IN MESH.**

Use plenty of oil in the bearing on the left side of differential. This oil lubricates the sleeve bearing and the shaft inside of the sleeve. Never use grease here.


CLUTCH

Use plenty of grease in cup on clutch spider. This grease lubricates the shaft extension when the motor is running and the clutch standing.


The tension on clutch springs is set by the $\frac{3}{4}$ -inch nut next to shoe. To adjust for wear engage clutch and remove cotter pin from small nut inside of clevice. Unscrew not so as to lengthen eye bolt. When clutch is engaged, this nut should stand $\frac{3}{32}$ of an inch from clevice. If too far away, clutch will be hard to engage; if too close, clutch will not hold.



TRACK PIN AND SPOOL—1913 MODEL
1916 MODEL HAS SQUARE HEAD PIN




DIFFERENTIAL AND MAIN DRIVE SPROCKETS—1913 MODEL




TRANSMISSION AND DIFFERENTIAL—1913 MODEL


C. L. BEST GAS TRACTION CO.




TRANSMISSION AND DIFFERENTIAL—1916 MODEL





C.L.B. 75H.P. MOTOR
Valve Cage Type






C. L. B. 75 H. P. REMOVABLE CYLINDER HEAD MOTOR






MOTOR PARTS FOR VALVE CAGE AND REMOVABLE CYLINDER HEAD MOTOR




MOTOR PARTS FOR VALVE CAGE AND REMOVABLE CYLINDER HEAD MOTOR




MOTOR PARTS FOR VALVE CAGE MOTORS

C. L. BEST GAS TRACTION CO.



C. L. BEST 75 H. P. ALL STEEL TRACK LAYER—1913 MODEL



C. L. BEST 75 H. P. ALL STEEL TRACK LAYER—1916 MODEL


This diagram illustrates the exploded view of a mechanical assembly, likely a pump or engine component. The parts are labeled with numbers and letters, indicating their specific functions and assembly order. The main components include:

- Large Curved Gear (401C-1):** The central, largest component, featuring a curved gear profile with multiple teeth and mounting holes.
- Shaft (517C):** A central shaft passing through the gear assembly, supported by bearings (337, 338, 339).
- Wheels (362C, 208C):** Two circular wheels with spokes, mounted on the shaft. The 208C wheel has a dimension of 98 indicated.
- Mounting Brackets (129C-1, 372C-1, 371C-1):** Various brackets and supports for the assembly, including a large bracket (372C-1) and a smaller one (371C-1).
- Gears (413, 246-1, 246-2, 212, 507C, 214):** Several smaller gears of different sizes, including a large gear (413) and a small gear (214).
- Other Components:** Various smaller parts like bolts (524C, 566C), washers (525C, 527C), and a handle (471C) are also shown.

The diagram uses arrows to indicate the assembly sequence and direction of movement for certain parts, such as the large curved gear (401C-1) and the shaft (517C).


20

C. L. BEST GAS TRACTION CO.




TRACTOR PARTS—1913 AND 1916 MODELS

C. L. BEST GAS TRACTION CO.



MOTOR AND TRACTOR PARTS

C. L. BEST GAS TRACTION CO.



TRACTOR PARTS

520 C

78

521 C

281

350 C

409

309

537 C

556 C

366 C

385 C

197 C

192 C

136 C-1

136 C-2

137 C

205 C

197 C

384 C

238

522 C

523 C

559 C

558 C

560 C

299

298

205


278

514 C


65

310


24




MISCELLANEOUS TRACTOR PARTS




MISCELLANEOUS TRACTOR AND RADIATOR PARTS



POWER STEER PARTS—1916 MODEL




SIDE FRICTION 90 H. P.—1916 MODEL




BOSCH MAGNETO Z-R-4

Wiring Diagrams.


*Magneto running clockwise
Firing Sequence
I, III, IV, II*




*Magneto running clockwise
Firing Sequence
I, II, IV, III*






*Magneto running anti-
clockwise
Firing Sequence
I, III, IV, II*



*Magneto running anti-
clockwise
Firing Sequence
I, II, IV, III*





K-W IGNITION SYSTEM

CROSS-SECTION TYPE H AND HK MAGNETOS

(See Impulse Starter on page 37)

Diagram "A" shows a longitudinal sectional elevation of type "H" and "HK" Magnetos. By referring to the numbers in the following instructions some idea can be obtained of the function of the various parts. This diagram will also assist in ordering repair parts as the numbers correspond with those in repair part list.

THE K-W
CIRCUIT BREAKER

The entire Circuit Breaker is removable. Release spring No. 189 by pushing it aside with knob on end. Pull out complete Breaker Box and remove cover nut No. 79. This allows removal of circuit breaker cap and gives access to breaker parts. Same type of circuit breaker is used on all K-W High Tension Magnetos and is shown by Diagram "D." It is arranged to have 30 degrees of advance or retard.




DIAGRAM "D"

The firing point of the magneto is just when the points are beginning to open or break circuit, not when they touch.

TO OPEN THE DISTRIBUTOR

Remove the High Tension Lead "100" by turning it to right, unfastening it at bottom. Unscrew nut "55" and remove the bridge or spider "I," thus releasing cap on distributor block and giving view of distributor and brush "B," No. "119."




DIAGRAM "A"

When the points "P," Diagram B, fail to separate or when the distance is too far apart, adjust Part 194 with small screw driver inserted through hole for that purpose in housing. The proper distance apart is 1/64 of an inch. A gauge is sent with every Magneto.

While there is no guarantee on the Platinum Iridium Points, they should, with proper care, last about 5,000 miles or more on auto engines and give equal service on large stationary or tractor engines.

Don't fill the circuit breaker box with oil or grease. Once a month oil the wick in roller "68" on upper contact arm. See that no oil gets on contact points as oil destroys the contact and makes hard starting. See full directions under "A Few Dont's" and "Care of Magneto."

K-W IGNITION SYSTEM

THE DIRECTION OF ROTATION

Be sure the Magneto when installed is running in direction as stamped by arrow on the dust cap around the driving end of shaft. This is "Clock-wise" or Right-hand, or "Anti-clockwise" or Left-hand. Magnetos will not operate in opposite direction to that for which they are intended.

TO CHANGE DIRECTION OF ROTATION

Take off cam 67 and turn it round end for end. Take off Hard Rubber Distributor Block exposing moulding (part 94 plate No. 1), fastened by three screws to large distributor gear (No. 2 plate 1). Shift to other set of holes for the screws and put back together.

DO NOT ATTEMPT THIS UNLESS YOU ARE BOTH AN EXPERT MECHANIC AND ELECTRICIAN, as we can not be responsible for error or damage resulting from improper handling.

If an error is made in ordering and you get the wrong direction, it is best to telegraph us at once to send the right one and Express Co. can arrange the exchange.

MOUNT THE MAGNETO

on an iron bracket, if desired, as it is not necessary to use a brass or aluminum bracket for the Models H and HT K-W Magnetos, because they have a brass base with magnets some distance from the bottom. If strap is desired to go over the magnets to hold magneto down, this must be of brass, as any part touching the magnets must be brass. Can mount at an angle, if desired, in order to avoid obstructions, as it is not necessary to have magneto upright.

Be sure bolts for attaching magneto to bracket are not too long so as to break through the magneto base and strike the rotor. $\frac{3}{8}$ " is all they should go in magneto.

TO TIME MAGNETO

See Diagrams "B" and "C" on next pages following.

FIRST—Have piston in cylinder No. 1 at highest point of compression stroke, which is firing position. Have rocker arm "A" horizontal as shown

SECOND—Shift Magneto around until Distributor Brush "B" touches segment "S," thus connecting with cylinder No. 1.

THIRD—Shift Magneto slowly by hand, in the proper direction of rotation, until the contacts "P" are just beginning to separate; this is the firing point of the magneto and must occur when the piston is at highest point of firing stroke. At this point secure Magneto shaft to gear or coupling with set screws.

K-W IGNITION SYSTEM WIRING DIAGRAM.




DIAGRAM "B"
This Sketch Shows Firing
Order 1, 2, 4, 3


FOURTH—When one cylinder is all right, proceed to connect the others as follows: Ascertain the firing order of the motor, then crank engine slowly and connect plug cable from next cylinder that fires to distributor segment No. 2 and so on until all the plug cables are connected. The Secondary connections on the Hard Rubber Distributor Block are numbered in consecutive order—1, 2, 3, 4, etc. These numbers do not refer to the engine cylinders, and it is necessary to determine the order in which the cylinders fire and connect secondary cables accordingly.

FIFTH—Replace parts on the magneto and start the engine to test the setting. See that all nuts and connections are tight, especially nuts Nos. 55 and 56. Also see that retainer spring No. 189 has been replaced. There should be a tendency for the engine to kick back slightly when starting, and if it does not, advance Magneto until it does kick slightly.

To advance, shift coupling against direction of rotation. To retard, shift coupling with direction of rotation. Shift slightly each time until correct position is obtained.

SIXTH—Pin Magneto shaft to gear or coupling with taper pin, do not depend on a set screw, as it will surely work loose in time.

K-W IGNITION SYSTEM



TO WIRE TO SWITCH

Remove nut "56" and fasten wire, which runs to switch. Connect other side of switch to any convenient place on engine frame for ground.

When the switch makes connection it short-circuits the magneto and stops it. When the connection is made or the circuit closed it stops the engine. When the connection is open the magneto is ready for operation. The switch is, therefore, not essential for running, but only for stopping.

TO CONNECT SPARK ADVANCE

When the magneto is timed, connect "A" to spark advance lever on the wheel with it half way between advance and retard, and with "A" horizontal.

K-W IGNITION SYSTEM

A FEW DON'TS.

Don't take off the magnets. When dis-assembling a magneto, a keeper must be placed across the magnets before removal from the magneto. Remagnetizing K-W Magnetos is not necessary unless a battery current has accidentally been shunted through them. If for any reason it should be necessary to remagnetize or repair a magneto, would advise having the instrument returned to us unless the service of a competent magneto man can be procured.

Don't fill the breaker box with grease, vaseline or oil. See oiling directions under the heading, "Care of Magneto," and follow them carefully.

Don't solder new contacts to the old parts as solder spoils the contacts. In replacing contacts get entire parts (No 190, \$3.50, and No. 194, \$2.50) direct from us.

Don't get busy to adjust the breaker box as soon as trouble develops. The trouble is very rarely found in the adjustment of the circuit breaker of the K-W Magneto and if you take the time to check up the system complete, in nine cases out of ten the difficulty will be located elsewhere.

Don't tinker with the circuit breaker adjustment unless the points either fail to separate or the gap is too great. The proper distance of the points is about 1/64 of an inch.

When sending magneto in to us for repairs don't fail to prepay express and mark your name on box as well as write a letter giving serial number of the magneto returned to us.

CARE OF MAGNETO

Once a month clean out the distributor with a soft cloth, removing any carbon dust that may have worn off the carbon brush.

Once a month remove the circuit breaker (Diagram D) and clean out any surplus oil, then oil the wick in the roller on the upper contact arm with two or three drops of good oil. Make sure that the contact points are clean and that no oil has lodged on them. Oil on the breaker points is an insulation and will cause hard starting and probable missing at low speed. Replace the circuit breaker box. Be sure that the contact spring, No. 189, has been properly replaced, and nut No. 79 is tight.

Once a month place a few drops of oil in each of the three bearings. One bearing is located on each side of the rotor shaft and one bearing on the distributor shaft.

K-W IGNITION SYSTEM IN CASE OF TROUBLE

See that all nuts, particularly No. 55, No. 56 and No. 79 are tight; that the high tension lead, No. 100, is in place; that the retainer spring, No. 189, is making good contact, and all wires leading to the spark plugs are connected or making good connections.

See that the magneto is revolving in the direction of rotation as stamped by the arrow on the driving end.

Check up the timing to see that the magneto is timed correctly. It may be possible the set screw has been used in connecting the coupling or gear to the shaft. After the magneto has been properly timed and temporarily set with a set screw, a taper pin should be inserted to prevent slipping.

Look at the distributor and see that it is free from carbon dust.

Open up the circuit breaker and see that it is not flooded with oil and no oil is on the contact points. The proper adjustment for these points is 1/64 of an inch apart when they break.

If the magneto fails to start, examine the switch and see that it breaks the ground connection when the switch is in the operating position.

Remove the spark plugs, examine them carefully to see that they are not cracked, short circuited and that the spark plug points are not too far apart. The proper adjustment of spark plug points for the K-W Magneto is 1/64 of an inch apart.

See that the spark plug points reach down into the cylinder deep enough to get to the good mixture. It sometimes happens that spark plugs are used with too short a barrel, firing in a chamber that pockets some of the exhaust gas.

To test the magneto, pull off one secondary wire from the plug, hold it about $\frac{1}{8}$ of an inch away from magnets and turn engine to give magneto one quick turn at the proper cylinder. A good spark should be thrown. On the type HTK Magnetos the magnets will give a hot spark regardless of how slowly engine is cranked.

IMPORTANT

When ordering repair parts always give Magneto Model and Number.

K-W MAGNETO PARTS




PLATE No. 1




PLATE No. 2

C. L. BEST GAS TRACTION CO.

PRICE LIST K-W HIGH TENSION MAGNETO PARTS

PLATE NO. 1


1—Bridge or spider.....	\$1.00	127—Bearing, circuit breaker end....	\$ 2.50
2—Distributor gear.....	2.00	128—Bearing, driving end.....	3.00
3—End piece for circuit breaker..	2.50	129—Bearing for distributor shaft..	2.00
7—Housing for distributor gear.....	6.00	132—Pole piece complete.....	5.00
9—Housing for end bearing.....	2.00	139—Winding assembled.....	7.50
10—Base.....	5.00	113—H. T. secondary winding only	5.00
14—Low tension bus bar.....	.40	180—Rotor shaft complete.....	15.00
26—Magnet clamp.....	1.00	181—Circuit breaker complete.....	10.00
64—Driving pinion.....	2.00	182—Distributor bearing housing.....	5.00
70—Shaft for distributor gear.....	1.00	183—Holder and distributor brush	1.50
73—Magnets, each.....	3.00	184—Cap for distributor block.....	.75
77—Terminal for Safety spark gap	.50	185—Condenser housing.....	.50
94—Molding for distributor gear..	2.00	186—High tension bus bar.....	.50
96—Distributor block.....	7.00	187—Screw driver.....	.10
100—High tension lead.....	1.00	188—Wrench.....	.15
118—Cap for safety spark gap.....	.25	195—High tension plug.....	1.50
126—Condenser complete.....	6.00		

PLATE NO. 2

13—Washer for spacing bearings.\$.05	78—Low tension stud.....	.25
21—Plate for circuit breaker cap..	.25	79—Primary circuit plunger.....	.10
24—Dust cover.....	.25	80—Nut for primary circuit plunger	.05
32—Screw for condenser case.....	.05	95—Circuit breaker cap.....	.25
32—Screw for distributor gear		104—Washer for primary stud	
bearing housing.....	.05	(upper).....	.05
33—Screw for end bearing.....	.05	106—Washer for primary stud	
34—Screw for condenser case		(lower).....	.05
(end).....	.10	109—Primary circuit plunger spring	.05
34—Ground screw.....	.10	110—Circuit breaker arm spring.....	.10
34—Screw for distributor gear		111—Distributor gear bearing re-	
bearing housing.....	.10	tainer ring.....	.05
35—Magnet clamp screw.....	.05	119—Distributor Brush.....	.10
36—Magnet clamp screw.....	.05	120—Secondary contact plunger.....	.10
37—Stud for clamping bridge.....	.05	123—Dust washer.....	.05
39—Screw for end piece for circuit		141—Retainer ring, breaker roller	
breaker housing (flat head)	.05	shaft.....	.05
40—Screw for end piece for circuit		143—High tension plug plunger	
breaker housing (filister	.05	spring.....	.05
head).....	.05	144—Distributor cap plunger spring	.05
42—Stop pin for circuit breaker		145—Distributor brush spring.....	.05
housing.....	.05	146—High tension plug plunger.....	.05
43—Screw for distributor gear.....	.05	147—Primary bus bar stud.....	.10
44—Screw for distributor block.....	.05	165—Key for Oldham coupling.....	.10
45—Screw for distributor block.....	.05	167—Oldham coupling, magneto end	.50
47—Screw for dust cover.....	.05	168—Oldham coupling, driving shaft	
47—Screw for breaker arm spring	.05	end. State diameter of driv-	
49—Bridge stud.....	.05	ing shaft when ordering.....	.50
51—Screw for distributor gear		170—Cam key.....	.05
molding.....	.05	189—Circuit breaker housing cap	
52—Nut for bridge studs.....	.05	plate retainer spring com-	
53—Nut for primary stud.....	.05	plete.....	.25
54—Nut for rotor shaft.....	.05	190—Circuit breaker arm (upper)	
55—Lock nut for bridge.....	.05	complete with contact.....	3.50
56—Lock nut for switch binding		192—Bridge stud washer.....	.05
post.....	.05	193—Primary stud washer.....	.05
57—Nut for primary stud (lower)	.05	194—Lower contact screw com-	
58—Nut for primary stud.....	.05	plete with contact.....	2.50
59—Nut for stud for breaker arms..	.05	Plug cables, 3 ft. with terminals...	1.00
61—Nut for retainer spring.....	.05	For each additional foot add.....	.20
66—Circuit breaker arm spring		Cable terminals, magneto end, ver-	
rivet.....	.05	tical type, each.....	.50
67—Cam.....	.50	Cable terminals, magneto end, hori-	
68—Cam roller.....	.10	zontal type, each.....	.50
69—Circuit breaker roller shaft...	.15	Cable terminals, spark plug end.....	.20

39
Platinum joint 2.50

K-W IMPULSE STARTER PARTS




C. L. BEST GAS TRACTION CO.

K-W IMPULSE STARTER PARTS

When ordering parts for K-W Impulse Starter, be sure to specify number of magneto, cylinder and cycle, and direction of rotation of Magneto when viewing same from driving end. We will be able to fill orders without the delay of writing for information if these specifications are given.

ST- 1 Bracket	\$ 1.25	ST-29 Dog Stud.....	.15
ST- 2 Case R. H. Gear Drive-1, 2 and 3 Cylinder.....	2.50	ST-30 Ratchet Catch Roller.....	.10
ST- 3 Case L. H. Gear Drive-1, 2 and 3 Cylinder.....	2.50	ST-31 Ratchet Catch Lock Screw.....	.05
ST- 4 Case R. H. Gear Drive-4 and 6 Cylinder.....	2.50	ST-32 Ratchet Catch Stud Nut....	.05
ST- 5 Case L. H. Gear Drive-4 and 6 Cylinder.....	2.50	ST-33 Ratchet Catch Stud Washer.....	.05
ST- 6 Ratchet R. H.-1, 2 and 3 Cylinder	1.50	ST-34 Rotor Shaft Washer.....	.05
ST- 7 Ratchet L. H.-1, 2 and 3 Cylinder	1.50	ST-35 Cam Screw.....	.05
ST- 8 Ratchet R. H.-4 and 6 Cylinder	1.50	ST-36 Ratchet Catch Stud Pin.....	.05
ST- 9 Ratchet L. H.-4 and 6 Cylinder	1.50	ST-37 Ratchet Taper Pin.....	.05
ST-10 Rotor Shaft Only.....	6.00	ST-38 Rotor Shaft Nut.....	.05
ST-11 Cam40	ST-39 Dog Stud Nut.....	.05
ST-12 Dog40	ST-40 Case Nut.....	.10
ST-13 Ratchet Catch.....	.50	ST-41 Rotor Shaft Nut Cotter Pin..	.05
ST-14 Ratchet Catch Lock.....	.20	ST-42 Catch Spring Support Pin ..	.05
ST-15 Ratchet Insert R. H.....	.15	ST-43 Ratchet Insert Pin.....	.05
ST-16 Ratchet Insert L. H.....	.15	ST-49 Case Oiler.....	.10
ST-17 Spring50	ST-50 Case R. H. Coupling Drive- 1, 2 and 3 Cylinder.....	2.50
ST-18 Cushion Spring.....	.10	ST-51 Case L. H. Coupling Drive- 1, 2 and 3 Cylinder.....	2.50
ST-19 Cushion Spring Sleeve, Inner15	ST-52 Case R. H. Coupling Drive- 4 and 6 Cylinder.....	2.50
ST-20 Cushion Spring Sleeve, Outer15	ST-53 Case L. H. Coupling Drive- 4 and 6 Cylinder.....	2.50
ST-21 Cushion Spring Plunger, Upper10	ST-54 Case R. H. Flange Drive- 1, 2 and 3 Cylinder.....	2.50
ST-22 Cushion Spring Plunger, Lower10	ST-55 Case L. H. Flange Drive..... 1, 2 and 3 Cylinder.....	2.50
ST-23 Cushion Spring Stud.....	.25	ST-56 Case R. H. Flange Drive- 4 and 6 Cylinder.....	2.50
ST-24 Case Bushing.....	.35	ST-57 Case L. H. Flange Drive..... 4 and 6 Cylinder.....	2.50
ST-25 Ratchet Catch Spring Sup- port, R. H.....	.20	ST-58 Ratchet Catch Spring Rivet ..	.05
ST-26 Ratchet Catch Spring Sup- port, L. H.....	.20	ST-59 Ratchet Catch Lock Spring R. H.05
ST-27 Ratchet Catch Spring R. H.	.05	ST-60 Ratchet Catch Lock Spring L. H.05
ST-28 Ratchet Catch Stud.....	.15	ST-61 Ratchet Catch Spring L. H.	.05
		ST-65 Ratchet Catch Spring Sup- port (new, in place of ST 26 and 27). Specify Right or Left Hand.....	.50



SCHEBLER CARBURETOR, MODEL "L"


C. L. BEST GAS TRACTION CO.

PRICE LIST OF REGULAR MODEL "L" PARTS.

2 inch Regular Model "L".....	\$37.00
2½ inch Regular Model "L".....	60.00

Symbol	Name	2"	2½"
	Body, complete.....	\$37.00	\$60.00
	Bowl, complete.....	7.50	15.00
A	Leather air valve disk.....	1.00	1.00
B	Bowl casting.....	6.00	10.00
C	Body casting.....	35.00	45.00
D	Spray nozzle.....	.20	.20
E	Needle valve.....	.20	.20
F	Cork float.....	.50	1.00
G	Gasoline union.....	.30	.30
H	Float valve.....	.20	.20
I	Needle valve adjusting knurl.....	.20	.20
J	Float lever.....	.20	.20
K	Throttle Disk.....	.10	.10
L	Air valve cap.....	2.00	2.00
M	Air valve adjusting screw.....	.20	.20
N	Cork gasket for bowl.....	.10	.10
O	Air valve spring.....	.10	.10
P	Needle valve lift lever.....	.40	.40
Q	Throttle lever.....	.40	.40
R	Female flange.....	4.00	5.00
S	Throttle stop screw.....	.10	.10
U	Bowl cap.....	.30	.30
V	Flusher.....	.50	.50
W	Needle valve lift lever pin.....	.10	.10
X	Needle valve guide.....	.30	.30
Y	Needle valve lift lever spring.....	.10	.10
Z	Cam, complete.....	1.00	1.00
1	Throttle stop lock screw.....	.10	.10
2	Air bend.....	2.00	2.00
3	Air valve seat.....	3.00	3.00
4	Float washer and screw.....	.20	.20
5	Flange cap screw.....	.20	.20
6	Float valve retainer nut.....	.10	.10
7	Float lever screw.....	.10	.10
8	Throttle shaft.....	.30	.30
9	Bowl lock nut casting for air bend.....	1.00	1.00
10	Air bend lock nut.....	.10	.10
11	Throttle lever lock screw.....	.10	.10
12	Water jacket plug.....	.10	.10

In ordering carburetor parts, be sure to specify
size and model of carburetor.




SCHEBLER CARBURETOR, MODEL "D"

C. L. BEST GAS TRACTION CO.

PRICE LIST OF MODEL "D" PARTS.

1½ inch Model "D".....		\$16.50	
2 inch Model "D".....		33.00	
Symbol	Name	1½"	2"
	Air valve, complete.....	\$5.00	\$8.00
	Bowl, complete.....	12.00	22.00
	Throttle, complete.....	6.00	9.00
	Leather air valve disk.....	.20	.50
A	Bowl casting.....	9.00	17.00
B	Butterfly shutter, complete.....	.50	.50
C	Spray nozzle.....	.20	.20
D	Needle valve.....	.20	.20
E	Cork float.....	.50	2.00
F	Gasoline union.....	.30	.30
G	Float valve.....	.20	.20
H	Float lever.....	.20	.20
J	Throttle disk.....	.10	.10
K	Lid	3.00	4.00
L	Air valve adjusting screw.....	.20	.30
M	Cork gasket for lid.....	.10	.10
N	Air valve spring.....	.10	.10
O	Throttle back.....	2.00	3.00
P	Throttle lever.....	.40	.40
Q	Throttle front with pipe thread.....	3.50	5.50
R	Throttle stop screw.....	.10	.10
S	Drain cock.....	.40	.40
T	Bowl cap.....	.30	.30
U	Flusher (see Part V, Model L).....	.50	.50
V	Lock nut for adjusting screw.....	.10	.10
W	Needle valve connection.....	.20	.20
X	Lock spring for adjusting screw.....	.10	---
Y	Throttle stop lock screw.....	.10	.10
1	Air valve cap screw.....	.10	.20
2	Air valve casting.....	4.00	7.00
3	Float washer and screw.....	.20	.20
4	Throttle cap screw.....	.10	.20
5	Float valve retainer nut.....	.10	.10
6	Float lever screw.....	.10	.10

In ordering carburetor parts, be sure to specify
size and model of carburetor.



SCHEBLER CARBURETOR, MODEL "E"


C. L. BEST GAS TRACTION CO.

PRICE LIST OF MODEL "E" PARTS.

1½ inch Model "E".....	\$22.50
2 inch Model "E".....	37.50

Symbol	Name	1½"	2"
	Air valve, complete.....	\$ 5.00	\$ 8.00
	Bowl, complete.....	16.00	26.00
	Throttle, complete.....	6.00	9.00
A	Leather air valve disk.....	.20	.50
B	Bowl casing.....	13.00	21.00
C	Butterfly shutter for air bend.....	.50	.50
D	Spray nozzle.....	.20	.20
E	Needle valve.....	.20	.20
F	Cork float.....	.50	2.00
G	Gasoline union.....	.30	.30
H	Float valve.....	.20	.20
I	Air bend.....	2.00	2.00
J	Float lever.....	.20	.20
K	Throttle disk.....	.10	.10
L	Lid	3.00	4.00
M	Air valve adjusting screw.....	.20	.30
N	Cork gasket for lid.....	.10	.10
O	Air valve spring.....	.10	.10
P	Throttle back.....	2.00	3.00
Q	Throttle lever.....	.40	.40
R	Throttle front with pipe thread.....	3.50	5.50
S	Throttle stop screw.....	.10	.10
T	Drain cock.....	.40	.40
U	Bowl cap.....	.30	.30
V	Flusher (see Part V, Model L Parts).....	.50	.50
W	Lock nut for adjusting screw.....	.10	.10
X	Needle valve connection.....	.20	.20
Y	Lock spring for adjusting screw.....	.10	---
1	Throttle stop lock screw.....	.10	.10
2	Air valve cap screw.....	.10	.20
3	Air valve casting.....	4.00	7.00
4	Float washer and screw.....	.20	.20
5	Throttle cap screw.....	.10	.20
6	Float valve retainer nut.....	.10	.10
7	Float lever screw.....	.10	.10

In ordering carburetor parts, be sure to specify
size and model of carburetor.



BOSCH MAGNETO, MODEL "Z-R-4"


C. L. BEST GAS TRACTION CO.

SPARE PARTS, FOR TYPES "Z R 4" WITH ADVANCE.

Plate I—Magneto Interrupter and Magneto Interrupter Housing.

"Z R 4"	List Price
219B Interrupter housing, complete.....	\$4.20
226 Interrupter housing, without segments.....	1.56
232 Segment with oil wick in interrupter housing, 219b.....	.24
233 Segment without oil wick in interrupter housing, 219b.....	.24
244 Lock nut for fastening interrupter housing, 219b.....	1.20
245 Timing lever on interrupter housing, 219b.....	.96
246 Timing lever without fastening screw, 249.....	
249 Fastening screw for timing lever, 245.....	.03
288 Terminal nut for fastening short circuit cable on fibre cover, 817.....	.12
345 Hexagon nut for front armature spindle.....	.03
347 Washer for hexagon nut, 345.....	.03
401 Anti-clockwise magneto interrupter, complete.....	5.16
402 Clockwise magneto interrupter, complete.....	5.16
405 Magneto interrupter disk with spring 417, for anti- clockwise magneto.....	.78
406 Magneto interrupter disk with spring 417, for clockwise magneto78
417 Holding spring for interrupter levers, 451 and 452.....	.03
418 Washer for spring 417.....	.03
433 Contact block for magneto interrupter, 401.....	.18
434 Contact block for magneto interrupter, 402.....	.18
435 Long platinum screw for contact blocks, 433 and 434.....	1.14
438 Lock nut for platinum screw 435.....	.03
447 Fastening screw for contact blocks, 433 and 434.....	.03
451 Interrupter lever for magneto interrupter, 401.....	1.05
452 Interrupter lever for magneto interrupter, 402.....	1.05
455 Short platinum screw for interrupter levers, 451 and 452.....	1.14
457 Fibre block in interrupter levers, 451 and 452.....	.03
460 Flat spring for magneto interrupter levers, 451 and 452.....	.03
461 Auxiliary spring on magneto interrupter levers, 451 and 452	.03
462 Auxiliary spring on boss of magneto interrupters, 401 and 40203
463 Fastening screw for flat spring, 460.....	.03
464 Carbon brush with spring for grounding magneto interrupt- ers, 401 and 402.....	.09
465 Carbon brush for grounding magneto interrupter.....	
466 Spring for carbon brush, 465.....	
467 Fastening screw for magneto interrupters, 401 and 402.....	.06
817 Fibre cover on interrupter housing, 219b, with short circuit- ing terminal.....	.66
819 Fibre cover on interrupter housing, 219b, without short circuiting terminal.....	.33

When ordering, please state, besides indicating the number and designation of the desired parts, that they are for type "Z R 4."



BOSCH MAGNETO, MODEL "Z-R-4"

C. L. BEST GAS TRACTION CO.


"Z R 4"

PLATE II.

List Price.

63	Lower fastening screw for shaft end plate.....	\$.03
64	Upper fastening screw for shaft end plate.....	.03
82	Brush holder, complete.....	1.74
*88	Hard rubber brush holder.....	.90
94	Collar on brush holder 88 (89), with electrode 97.....	
97	Electrode for safety spark gap.....	.06
103	Wire ring for brush holder 88 (89), in collar 94 (95).....	.03
104	Felt ring in collar 94 (95).....	.03
107	Connecting piece without carbon brush 109 on brush holder 82 (83).....	.06
108	Carbon brush 109 with spring 110 for brush holder.....	.09
109	Carbon brush in connecting piece 107.....	
110	Spring for carbon brush 109.....	
111	Carbon brush 112 with spring 113 for brush holder.....	.09
112	Carbon brush.....	
113	Spring for carbon brush 112.....	
117	Fastening screw for collar 94 (95).....	.03
118	Bonnet with felt packing and oil hole cover 125 or 126, respectively.....	1.50
125	Oil hole cover for anti-clockwise magneto on bonnet 118....	.24
126	Oil hole cover for clockwise magneto on bonnet 118.....	.24
131	Fastening screw for oil hole covers 125 and 126.....	.03
132	Spring for oil hole covers 125 and 126.....	.03
139	Fastening screw for bonnet 118.....	.03
140	Washer for fastening screw 139.....	.03
165	Screw with grounding carbon brush 167 and spring 168....	.24
166	Screw with grounding.....	.12
167	Grounding carbon brush.....	
167A	Grounding carbon brush 167 with spring 168.....	.12
168	Spring for grounding carbon brush 167.....	
169	Oil hole cover on interrupter end plate.....	
174	Fastening pin for oil hole cover 169.....	.03
175	Spring for oil hole cover 169.....	.03
176	Holding spring for distributor plate 537 (539).....	.06
179	Fastening pin for holding spring 176.....	.03
182	Screw 166, with oil wick 184, for distributing gear shaft....	.24
183	Oil wick in screw 182, with spring 186.....	.06
184	Oil wick in screw 182.....	
186	Spring for oil wick 184.....	
*510	Rotating distributor brush holder, complete, with carbon brush 533 for anti-clockwise magnetos.....	
511	Rotating distributor brush holder, complete, with carbon brush 533 for clockwise magnetos.....	
526	Rotating distributor brush holder.....	.25
532	Carbon brush 533 for rotating distributor brush holder, with spring 534.....	
533	Carbon brush for rotating distributor brush holder.....	
534	Spring for carbon brush 533.....	
537	Distributor plate, complete.....	
543	Distributor plate, without terminal nuts.....	
554	Mica plate for window in distributor plate 537 (539).....	
562	Terminal nut for fastening cables on terminal studs of distributor plate.....	.05

The numbers marked * are not illustrated.



SPLITDORF MAGNETO, MODEL "W"

C. L. BEST GAS TRACTION CO.

SPLITDORF MAGNETO PARTS—MODEL "W."

Part No.	Cradle	List Price.
22	Cradle	\$7.50
276	Armature cover screws, each.....	.05
388	Magnet screws, short, each.....	.05
389	Magnet screws, long, each.....	.05
415	Magnets, per pair.....	7.50
2435	Armature cover.....	.75
Front Plate		
226A	Plate screws with lock washers, short, each.....	.05
227A	Plate screws with lock washers, long, each.....	.05
363A	Standard annular bearings, 15 m/m, for armature shaft.....	4.00
364	Standard annular bearings, $\frac{3}{8}$ inch, for distributor shaft.....	3.50
646A	Oil cup, complete.....	.10
832A	Front plate with ground stud, oiler and 3 bearings.....	15.00
832B	Front plate with ground stud and oiler.....	4.50
1671	Gear cover.....	.10
Distributor Gear		
182	Distributor gear, only.....	4.00
182A	Distributor gear, complete, with 2 bearings.....	11.00
186	Distributor shaft washer.....	.10
187	Distributor shaft nut.....	.10
213	Dust cap.....	.25
364	Standard annular bearings, $\frac{3}{8}$ inch, for distributor shaft.....	3.50
640	Distributor disc screws, each.....	.05
1725	Distributor disc with segment.....	1.25
Distributor Block		
390A	Carbon brush, short, with spring, each.....	.10
436	Distributor block hex. nut.....	.05
826	Terminal plug insulation.....	.35
826A	Terminal plug, complete.....	.45
828	Distributor block, only.....	4.00
829	Distributor block with terminal plugs and brushes.....	6.00
1764A	Distributor block screws with lock washers, each.....	.05
1772	Terminal plug.....	.10
Breaker Box		
287A	Breaker bar roller, screw and lock nut.....	.25
297A	Gauze brush, short, with spring.....	.10
436	Hex. nut.....	.05
791	Breaker box less cover, breaker bar and platinum contact screw.....	7.00
802	Breaker bar, complete, with platinum.....	2.50
805	Breaker bar finger spring.....	.05
1061A	Breaker box cover, complete.....	.75
1085	Connection stud nut.....	.05
1105	Breaker bar main spring.....	.15
1359	Breaker bar finger screw.....	.05
1539	Breaker box pillar.....	.25
2077A	Breaker box cover spring.....	.25
2598A	Platinum contact screw, with platinum and 2 lock nuts.....	2.00

C. L. BEST GAS TRACTION CO.

SPLITDORF MAGNETO PARTS—MODEL "W."

Armature

55	Cam	1.00
64	Armature gear.....	1.00
71	Cam nut.....	.15
72	Cam key.....	.10
73	Key, drive end.....	.10
74	Nut, drive end.....	.10
363A	Standard annular bearings, 15 m/m, for armature shaft.....	4.00
1709	Collector spool.....	.50
1711	Collector spool washer.....	.20
1785	Armature, drive end, less bearing and spool.....	2.50
2368	Armature, with gear.....	17.50
2368A	Armature, complete, with gear and bearings.....	24.50

Back Plate.

226A	Plate screws, short, with lock washers, each.....	.05
363A	Standard annular bearings, 15 m/m, for armature shaft.....	4.00
646A	Oil cup, complete.....	.10
1601A	Back plate with oiler and bearing.....	6.00
1601B	Back plate with oiler.....	2.00
1601C	Back plate, complete, with oiler, bearing and brush.....	7.50
	holder35
1726A	Collector brush with spring.....	1.15
2407A	Collector brush holder.....	1.75
2626A	Condenser box and lead.....	

When ordering parts, please specify Magneto Model.

ALPHABETICAL CASTING LIST

A

\$ 2.00	418 C	Air Intake Screen Casting used on 75 H. P. Harvester Motor	Brass
.80	560 C	Angle for Scraper, front wheel.....	75 & 90 H. P.—W. I.
.80	529 C	Arrow	75 & 90 H. P.—Sheet Steel
2.74	594 C	Arrest for Spark Complete.....	75 & 90 H. P.
.96	528 C	Arrow Stand.....	75 & 90 H. P.—W. I.
1.14	372 C	Axle Hanger Straps for Main Drive Sprocket outside	75 & 90 H. P.—M. S.
1.14	372 C-1	Axle Hanger Straps for Main Drive Sprocket inside	75 & 90 H. P.—M. S.
22.68	371 C	Axle Back 4-in., 22 & 24 in. Track.....	75 H. P.—C. R. S.
26.04	371 C-1	Axle Back 4-in., 30-in. Track.....	75 & 90 H. P.—C. R. S.

B

86.00	2 C	Base, Lower O. S.....	75 H. P.—C. I.
75.00	1 C	Base, Upper O. S.....	75 H. P.—C. I.
86.34	224 C	Base, Lower N. S.....	75 & 90 H. P.—C. I.
85.44	234 C	Base, Upper N. S.....	75 & 90 H. P.—C. I.
10.00	230 C	Ball Bearing Drum for Track Roller.....	75 H. P.—C. I.
6.00	239 C	Ball Bearing Drum for Track Roller.....	75 H. P.—C. I.
8.62	229 C	Band Brake Toggle.....	75 H. P.—Chrome
2.14	159 C	Band Brake Support.....	75 H. P.—C. S.
.60	160 C	Band Brake Clamp.....	75 H. P.—C. S.

C. L. BEST GAS TRACTION CO.

.70	160	C-1	Band Brake Clamp.....	75 H. P.—C. S.
6.84	537	C	Band Brake Complete.....	75 H. P.
1.00	34	C	Balls Governor (Brass) O. S.....	75 H. P.—Brass
.30	247	C	Balls, Governor, N. S.....	75 H. P.—C. I.
.15	375	C	Balls, 2¼-in. diam., for Front Wheel Circle.....	75 & 90 H. P.—C. I.
.25	374	C	Ball Socket Joint for Governor Lever.....	75 & 90 H. P.
1.05	378	C	Base or Bracket for Head Lights.....	75 H. P.—C. I.
50.72	351	C	Bars, Main Side 10-in. Channel.....	75 H. P.—S. S.
	351	C-1	Bars, Main Side 10-in. Channel.....	90 H. P.—S. S.
.85	494	C	Bar, Starting.....	75 & 90 H. P.—C. R. S.
13.30	506	C	Bar, Draw.....	75 & 90 H. P.—W. I.
	465	C	Band for Clutch.....	90 H. P.—C. I.
2.00	314	C	Ball Bearing End Truss Collar for Fan.....	75 H. P.
4.00	64	C	Belt Tightener Bracket, Valve Cage Motor.....	75 H. P.—C. S.
3.00	308	C	Belt Tightener Pulley, Valve Cage Motor.....	75 H. P.—C. I.
14.30	347	C	Belt for Fan, 4½" x 6' 2½", Wire Stitched.....	75 & 90 H. P.
13.60	347	C-1	Belt for Fan, 4 " x 6' 2½", Wire Stitched.....	75 H. P.
2.50	232	C	Bell Crank for Brake Rods.....	75 H. P.—C. S.
15.04	143	C	Bevel Gear Coupling Main Drive.....	75 & 90 H. P.—C. S.
2.06	259	C	Bearing for Oil Pump Drive.....	75 H. P.—C. I.
2.50	271	C	Bearing for Magneto Drive Shaft.....	75 H. P.—C. I.
2.40	47	C	Bearing, Oiler Shaft.....	75 H. P.—C. I.
2.20	48	C	Bearing, Cam Shaft, Valve Cage Motor.....	75 H. P.—C. I.
2.00	49	C	Bearing, Cam Shaft, Valve Cage Motor.....	75 H. P.—C. I.
1.60	282	C	Bearing, Cam Shaft, Cyl. Head Motor.....	75 H. P.—C. I.
1.60	270	C	Bearing, Cam Shaft (Fly Wheel End), Cyl. Head Motor.....	75 H. P.—C. I.
1.60	269	C	Bearing, Cam Shaft (Center), Cyl. Head Motor.....	75 H. P.—C. I.
20.12	102	C	Bearing or Box for Differential, RH.....	75 H. P.—C. S.
12.52	103	C	Bearing or Box Cap for 102 C.....	75 H. P.—C. S.
15.20	104	C	Bearing or Box for Differential, LH.....	75 H. P.—C. S.
10.44	105	C	Bearing or Box Cap for 104 C.....	75 H. P.—C. S.
22.00	102	C-1	Bearing or Box for Differential, RH, Special for 30" Track only, used before 265 C Sprocket was used.....	75 H. P.—C. S.
17.00	104	C-1	Bearing or Box for Differential, LH, Special for 30" Track only, used before 265 C Sprocket was used.....	75 H. P.—C. S.
14.00	103	C-1	Bearing or Box Cap for 102 C-1.....	75 H. P.—C. S.
12.00	105	C-1	Bearing or Box Cap for 104 C-1.....	75 H. P.—C. S.
5.00	127	C	Bearing or Box for Front Track Idler Shaft, R & L Hand, use on Eng. 201 to 207 inc.....	75 H. P.—C. S.
3.00	128	C	Bearing or Box Cap for 127 C.....	75 H. P.—C. S.
9.06	129	C	Bearing or Box Solid for Main Drive Sprocket on Main Frame.....	75 H. P.—C. S.
9.06	129	C-1	Bearing or Box Solid for Main Drive Sprocket on Main Frame.....	75 & 90 H. P.—C. S.
.90	184	C	Bearing, Oil Pipe end, Valve Cage Motor.....	75 H. P.—C. I.
.90	185	C	Bearing, Oil Pipe end, Valve Cage Motor.....	75 H. P.—C. I.
4.50	222	C	Bearing or Bracket for Diff. Roller Pin Bolts to Cross Tie.....	75 H. P.—C. S.

C. L. BEST GAS TRACTION CO.

2.50	97 C	Bearing for Connecting Rod (Special Metal each Half)	75 H. P.
5.45	65	Bearing or Box for Lead Wheel Shaft	75 & 90 H. P.—C. I.
3.35	193 C	Bearing or Box for Front Track Idler, RH	75 H. P.—C. S.
3.35	198 C	Bearing or Box for Front Track Idler, LH	75 H. P.—C. S.
		(two above takes place of 127 C and 128 C)	
3.25	296 C	Bearing or Box for Front Track Idler (Takes place of 193 C), RH	75 & 90 H. P.—C. S.
3.25	295 C	Bearing or Box for Front Track Idler (Takes place of 198 C)	75 & 90 H. P.—C. S.
1.00	180 C	Block for Friction Clutch Spring	75 H. P.—C. S.
.25	390 C	Block for Universal Joint Oiler Drive OS	75 H. P.—C. R. S.
.30	393	Block for Steering Knuckle No. 84	75 & 90 H. P.—C. I.
.15	510 C	Block for Governor Shifter	75 H. P.—C. R. S.
1.00	581 C	Blade for Fan	75 & 90 H. P.—Saw Steel
1.25	354 C	Bolts or Rod for Track Tightening, used with 127 C Bracket	75 H. P.
2.50	354 C-1	Bolts or Rod for Track Tightening, used with 193 C Bracket (and 198 C)	75 H. P.
.83	354 C-2	Bolts or Rod without nuts for Track Tightening, used with 295 C and 296 C Bracket	75 & 90 H. P.
1.30	354 C-2	Bolts or Rod with nuts for Track Tightening used with 295 C and 296 C Bracket	75 & 90 H. P.
.11	571 C	Bolt for Track Link, $\frac{5}{8}$ " x $8\frac{3}{4}$ "	75 & 90 H. P.—M. S.
.12	572 C	Bolt for Track Shoe, $\frac{7}{8}$ " x $2\frac{1}{4}$ ", O. S.	75 H. P.—M. S.
.15	573 C	Bolt for Track Shoe, $\frac{7}{8}$ " x $2\frac{1}{4}$ ", Sq. Shank, N. S.	75 & 90 H. P.—M. S.
.09	575 C	Bolt for Flexible Coupling, $\frac{3}{4}$ " x $3\frac{3}{4}$ "	75 & 90 H. P.—M. S.
.46	548 C	Bolt Eye for Clutch	75 & 90 H. P.—M. S.
.30	561 C	Bolt Eye for Brake	75 H. P.—M. S.
.40	524 C	Bolt Eye or Guide, Power Steer Safety Rod	75 H. P.—M. S.
	463 C	Bolt Eye for Side Clutch	90 H. P.—M. S.
12.50	299	Bottom for Radiator	75 & 90 H. P.—C. I.
1.50	592 C	Boot or Cover for Gear Shifter	75 & 90 H. P.—Leather
.75	265	Bowl for Spark Arrestor	75 & 90 H. P.—C. I.
3.00	192 C	Bracket or Female Slide Block for 119 C and 201 C, O. S.	75 H. P.—C. S. S.
3.00	384 C	Bracket or Female Slide Block for 386 C and 387 C	75 & 90 H. P.—C. S.
4.78	191 C	Bracket Sliding Male to Hold Swing Frame in Place, O. S.	75 H. P.—C. S.
4.78	201 C	Bracket Sliding Male to Hold Swing Frame in Place, O. S.	75 H. P.—C. S.
4.90	385 C	Bracket Sliding Male to Hold Swing Frame in Place, N. S., Inside	75 & 90 H. P.—C. S.
4.90	386 C	Bracket Sliding Male to Hold Swing Frame in Place, N. S., Outside	75 & 90 H. P.—C. S.
2.50	389 C	Bracket for Main Sprocket Axle Riveted to Main Frame	75 & 90 H. P.—C. S.

C. L. BEST GAS TRACTION CO.

5.52	125 C	Bracket for Swing Frame Roller.....	75 & 90 H. P.—C. S.
6.00	126 C	Bracket for Swing Frame Roller.....	75 & 90 H. P.—C. S.
6.00	172 C	Bracket for Swing Frame Roller.....	75 & 90 H. P.—C. S.
7.50	231 C	Bracket for Drum 230 C for Track Roller, RH	75 H. P.—C. S.
7.00	235 C	Bracket for Drum 230C for Track Roller LH	75 H. P.—C. S.
7.00	238 C	Bracket for Drum 239 C for Track Roller.....	75 H. P.—C. S.
6.84	196 C	Bracket for Top Chain Carrier Idler Shaft, Front	75 & 90 H. P.—C. S.
5.58	279 C	Bracket for Top Chain Carrier Idler Shaft, Rear	75 & 90 H. P.—C. S.
2.50	24 C	Bracket for Rocker Arm, O. S.....	75 H. P.—C. S.
2.50	267 C	Bracket for Rocker Arm, N. S.....	75 H. P.—C. I.
15.00	76 C	Bracket for Fan, O. S.....	75 H. P.—C. S.
12.00	276 C	Bracket for Fan, N. S.....	75 H. P.—C. S.
1.80	92 C	Bracket for Splitdorf Magneto.....	75 H. P.—C. S.
1.80	261 C	Bracket for Bosch & K. W. Magneto.....	75 H. P.—C. I.
12.16	208 C	Bracket for Power Steer, O. S.....	75 H. P.—C. S.
1.50	139 C	Bracket for Track Tightener Bolt or Rod, O. S.	75 H. P.—C. S.
4.16	304 C	Bracket for Track Tightener Bolt or Rod, N. S. (used in place of 139 C).....	75 & 90 H. P.—C. S.
.86	469 C	Bracket Plate or Guide for Power Steer Shifting Lever.....	75 & 90 H. P.—W. I.
6.10	153 C	Bracket for Throttle Control Lever Hand Steer	75 H. P.—C. I.
6.10	298 C	Bracket for Throttle Control Lever Power Steer	75 H. P.—C. I.
	157 C	Bracket for Brake Drum.....	75 H. P.—C. S.
2.00	209 C	Bracket for Oiler or Lubricator.....	75 H. P.—C. S.
1.28	171 C	Bracket for Oiler or Lubricator.....	75 H. P.—W. I.
.94	416 C	Bracket for Magneto Control Wire on Throttle	75 & 90 H. P.—C. S.
1.58	428 C	Bracket for Power Steer Gear Case.....	75 & 90 H. P.—M. S.
5.52	174 C	Bracket Box or Bearing for Stationary Drive Shaft	75 H. P.—C. S.
2.00	309	Bracket for Front Circle Braces, Inside, RH	75 & 90 H. P.—C. I.
2.00	310	Bracket for Front Circle Braces, Inside, LH	75 & 90 H. P.—C. I.
1.50	337	Bracket for Steering Worm, Hand and Power Steer.....	75 & 90 H. P.—C. I.
.50	338	Bracket or Toe Piece for 337 Worm Bracket, Front	75 & 90 H. P.—C. I.
.50	339	Bracket or Toe Piece for 337 Worm Bracket, Rear	75 & 90 H. P.—C. I.
1.14	372 C	Bracket or Hanger for Main Sprocket Shaft, Outside	75 & 90 H. P.—M. S.
1.14	372 C-1	Bracket or Hanger for Main Sprocket Shaft, Inside	75 & 90 H. P.—M. S.
1.00	176 C	Brake Lever (Cast Steel Part Only).....	75 H. P.—C. S.
1.81	176 C-1	Brake Lever (Cast Steel with Wrought Part Welded)	75 H. P.
2.21	176 C-2	Brake Lever (Cast Steel with Wrought Part Welded)	75 H. P.

C. L. BEST GAS TRACTION CO.

1.64	538 C	Brake Foot	75 H. P.—W. I.
.15	539 C	Bracket Dust Guard.....	75 & 90 H. P.—W. I.
.83	530 C	Bracket Steer Segment.....	75 H. P.—W. I.
.32	522 C	Brace, Circular, for Radiator.....	75 & 90 H. P.—W. I.
.12	523 C	Brace, Straight, for Radiator.....	75 & 90 H. P.—W. I.
.48	558 C	Brace, for Scraper (Long).....	75 & 90 H. P.—W. I.
.36	559 C	Brace for Scraper (Short).....	75 & 90 H. P.—W. I.
	577 C	Bracket for Clutch Shifter, LH.....	90 H. P.—C. S.
	579 C	Bracket for Clutch Shifter, RH.....	90 H. P.—C. S.
.92	534 C	Brake Rod, LH.....	75 H. P.—W. I.
.76	535 C	Brake Rod, RH.....	75 H. P.—W. I.
1.03	536 C	Brake Shaft.....	75 H. P.—W. I.
	601 C	Bracket Steering Segment.....	90 H. P.—W. I.
	602 C	Bracket Brake Shaft.....	90 H. P.—W. I.
1.60	221 C	Bushing, 2 pieces Cast Iron for Manganese Track Roller, 199 C and 195 C.....	75 H. P.—C. I.
.90	19 C	Bushing, Bronze, for Water Pump.....	75 H. P.—Bronze
1.00	61 C	Bushing, Bronze, for Oil Pump.....	75 H. P.—Bronze
1.00	62 C	Bushing, Bronze, for Oil Pump Idler Gear	75 H. P.—Bronze
1.75	73 C	Bushing, Bronze, for Pump End Drive Gear O. S. Valve Cage Motor.....	75 H. P.—Bronze
1.88	75 C	Bushing, Bronze, for Piston Pin.....	75 H. P.—Bronze
1.00	81 C	Bushing, Bronze, for Truss Roller 158 C	75 H. P.—Bronze
4.37	87 C	Bushing, Bronze, for Clutch Spider.....	75 & 90 H. P.—Bronze
2.25	95 C	Bushing, Bronze, for End Gear Case Cover	75 H. P.—Bronze
1.00	146 C	Bushing, Bronze, for Bevel Pinion in Diff. gear	75 H. P.—Bronze
7.56	147 C	Bushing, Bronze, for Differential Sleeve, 6" long	75 & 90 H. P.—Bronze
5.25	148 C	Bushing, Bronze, for Differential Sleeve, 4" long	75 & 90 H. P.—Bronze
8.64	149 C	Bushing, Bronze, for Differential Bevel Gear No. 118 C.....	75 H. P.—Bronze
7.02	150 C	Bushing, Bronze, for Transmission Gear 110 C and 301 C.....	75 & 90 H. P.—Bronze
9.24	151 C	Bushing, Bronze, for Bull Pinion No. 111 C	75 & 90 H. P.—Bronze
8.56	166 C	Bushing, Bronze, for Large Sprocket, N. S. with Shoulder.....	75 & 90 H. P.—Bronze
8.40	166 C-1	Bushing, Bronze, for Large Sprocket, O. S. without Shoulder.....	75 H. P.—Bronze
2.66	179 C	Bushing, Bronze, for Reverse Idler Gear No. 167 C.....	75 & 90 H. P.—Bronze
.60	181 C	Bushing, Bronze, for Rocker Arm, Short	75 H. P.—Bronze
3.00	223 C	Bushing, Bronze, for Cam Shaft Idler Gear	75 H. P.—Bronze
.65	233 C	Bushing, Bronze, for Rocker Arm, Long	75 H. P.—Bronze
1.25	84 C	Bushing for Valve Cage.....	75 H. P.—C. I.
1.25	277 C	Bushing for Valve Stem, Cyl. Head Motors	75 H. P.—C. I.

C. L. BEST GAS TRACTION CO.

.90	383 C	Bushing for Oil Pump Drive End Bearing No. 259 C.....	.75 H. P.—Bronze
2.92	190 C	Bushing, 2 pieces, for Flanged Track Roller 186 C and 187 C.....	.75 & 90 H. P.—C. I.
4.98	212 C	Bushing, 2 pieces, for Front Track Idler No. 217 C and 493 C.....	.75 & 90 H. P.—C. I.
1.66	414	Bushing, Bronze, for 212 and 415 O. S. Power Steer.....	.75 H. P.—Bronze
3.11	412 C	Bushing for Power Steer Case, N. S.75 & 90 H. P.—Bronze
.72	413 C	Bushing for Power Steer Bevel Gear, N. S.75 & 90 H. P.—Bronze
24.42	111 C	Bull Pinion, 12 Teeth, Bronze Bushed, LH75 H. P.—Chrome
19.15	112 C	Bull Pinion, 12 Teeth, RH.....	.75 H. P.—Chrome
18.90	393 C	Bull Pinion, 12 Teeth, takes place of 111C, LH.....	.75 H. P.—Chrome
22.06	414 C	Bull Pinion, 12 Teeth, takes place of 111C and 393 C, LH.....	.75 & 90 H. P.—Chrome
19.42	415 C	Bull Pinion, 12 Teeth, takes place of 112C75 H. P.—Chrome
C			
11.00	12 C	Casing, Gear Casing for Water Pump, O. S.75 H. P.—C. I.
4.50	13 C	Casing, Gear Casing Cover for Water Pump75 H. P.—C. I.
4.60	17 C	Case, Oilier Gear.....	.75 H. P.—C. I.
3.50	28 C	Casing, Governor, Brass, O. S.....	.75 H. P.—Brass
2.00	29 C	Casing, Governor End, O. S.....	.75 H. P.—Brass
2.50	30 C	Casing, Governor End, O. S.....	.75 H. P.—Brass
5.00	39 C	Casing Cover for Oil Pump.....	.75 H. P.—C. I.
3.50	40 C	Casing Cover for Oil Pump.....	.75 H. P.—C. I.
1.60	23 C	Cam Rod Guide.....	.75 H. P.—C. I.
2.50	41 C	Cam Shaft Idler Stud, Valve Cage Motor.....	.75 H. P.—C. S.
2.20	48 C	Cam Shaft Bearing, Valve Cage Motor.....	.75 H. P.—C. I.
1.60	269 C	Cam Shaft Bearing, Center.....	.75 H. P.—C. I.
2.00	49 C	Cam Shaft Bearing, Valve Cage Motor.....	.75 H. P.—C. I.
1.60	270 C	Cam Shaft Bearing, Fly Wheel End.....	.75 H. P.—C. I.
8.00	50 C	Cam Shaft Gear, Valve Cage Motor.....	.75 H. P.—C. S.
9.00	51 C	Cam Idler Gear, Valve Cage Motor.....	.75 H. P.—C. S.
16.20	225 C	Cam Shaft Gear.....	.75 H. P.—Chrome
1.60	282 C	Cam Shaft Bearing.....	.75 H. P.—C. I.
1.40	244 C	Cam Intake.....	.75 H. P.—Chilled Iron
1.40	243 C	Cam Exhaust.....	.75 H. P.—Chilled Iron
.50	58 C	Cap for Oil Box Plate.....	.75 H. P.—C. I.
7.00	36 C	Cap for Fly Wheel End, Valve Cage Motor75 H. P.—C. I.
7.00	257 C	Cap for Fly Wheel End.....	.75 H. P.—C. I.
7.00	37 C	Cap for Front End, Valve Cage Motor.....	.75 H. P.—C. I.
5.20	256 C	Cap for Front End.....	.75 H. P.—C. I.
5.70	38 C	Cap for Center Bearing, Valve Cage Motor75 H. P.—C. I.
5.20	255 C	Cap for Center Bearing.....	.75 H. P.—C. I.
	74 C	Cap for Connecting Rod.....	.75 H. P.—C. S.
.30	68 C	Cap for Oil Bearings.....	.75 H. P.—C. I.
2.00	77 C	Cap for Fan Bracket (Long).....	.75 H. P.—C. I.

C. L. BEST GAS TRACTION CO.

2.00	78	C	Cap for Fan Bracket (Short).....	75 H. P.—C. I.
80.28	341	C	Canopy Top complete, Galv. Corrugated.....	75 & 90 H. P.
.12	340	C	Canopy Top Brace for Posts.....	75 & 90 H. P.—M. S.
1.32	342	C	Canopy Top Uprights or Posts (Front).....	75 & 90 H. P.—M. S.
.90	342	C-1	Canopy Top Uprights or Posts (Rear).....	75 & 90 H. P.—M. S.
.50	302	C	Cap or Cover for Oil Pocket, Diff. Bearing No. 114 C.....	75 & 90 H. P.—C. I.
.50	303	C	Cap or Cover for Oil Pocket, Diff. Bearing No. 103 C and 105 C.....	75 & 90 H. P.—C. I.
1.00	98		Cap for O. S. Power Steer Bracket No. 208C.....	75 H. P.—C. I.
7.60	333	C	Cam Shaft (Only).....	75 H. P.—C. R. S.
	482	C	Cap for Bevel Pinion Bearing.....	90 H. P.—C. S.
70.00	479	C-1	Case for Transmission.....	90 H. P.—C. S.
69.41	113	C	Case for Transmission, O. S.....	75 H. P.—C. S.
69.41	479	C	Case for Transmission, N. S.....	75 H. P.—C. S.
21.00	140	C	Case Cover for Transmission, No. 113C, 479 C and 479 C-1.....	75 & 90 H. P.—C. I.
13.09	504	C	Case, Differential Top.....	75 H. P.—Sheet Steel
13.09	505	C	Case, Differential (Lower).....	75 H. P.—Sheet Steel
	45	C	Cap for Drop Forged Connecting Rod.....	75 H. P.—Drop Forged
.35	78		Cap for End of Lead Wheel Shaft.....	75 & 90 H. P.—C. I.
5.82	408	C	Case for Power Steer Gears Only (Upper).....	75 & 90 H. P.—C. I.
6.12	409	C	Case for Power Steer Gears Only (Lower).....	75 & 90 H. P.—C. I.
	603	C	Case Clutch (Upper).....	90 H. P.—Sheet Steel
	604	C	Case Clutch (Lower).....	90 H. P.—Sheet Steel
1.50	139	C	Chain Tightener Bolt Bracket on top of I Beam, O. S.....	75 H. P.—C. S.
4.16	304	C	Chain Tightener Bolt Bracket on end of I Beams, N. S.....	75 & 90 H. P.—C. S.
	583	C	Clutch Shifter Lever.....	90 H. P.—C. S.
	584	C	Clutch Shifter Lever Handle.....	90 H. P.—W. I.
2.50	27	C	Clevis Valve Rod for Rocker Arm Stand.....	75 H. P.—Drop Forged
23.67	69	C	Clutch Spider, Bronze Bushed.....	75 H. P.—C. S.
7.00	70	C	Clutch Shoe without Lagging.....	75 H. P.—C. S.
10.50	70	C	Clutch Shoe with Lagging.....	75 H. P.—C. S.
6.78	292	C	Clutch Shoe without Lagging, takes place of 70 C.....	75 H. P.—C. S.
10.28	292	C	Clutch Shoe with Lagging, takes place of 70 C.....	75 H. P.—C. S.
7.00	283	C	Clutch Shifter, O. S.....	75 H. P.—C. S.
7.60	71	C	Clutch Sleeve.....	75 H. P.—C. S.
7.20	326	C	Clutch Shifter, takes place of 283 C.....	75 & 90 H. P.—C. S.
.50	21	C	Clamp for Exhaust and Intake Manifold.....	75 H. P.—C. S.
.55	22	C	Clamp Cam Rod Guide.....	75 H. P.—C. S.
1.00	180	C	Clutch Spring Block Motor Clutch.....	75 H. P.—C. S.
3.38	360	C	Clutch Lever.....	75 & 90 H. P.—M. S.
3.36	211		Clutch for O. S. Power Steer.....	75 H. P.—C. S.
2.52	420	C	Clutch for N. S. Power Steer.....	75 & 90 H. P.—C. R. S.

C. L. BEST GAS TRACTION CO.

2.00	431 C	Clutch for C. I. Bevel Gear used on N. S. Power Steer, same is riveted to gears No. 432 C and 433 C.....	75 H. P.—C. R. S.
7.68	133 C	Clutch for Differential Sleeve, O. S.....	75 H. P.—C. S.
10.32	404 C	Clutch for Differential Sleeve, takes place of 133 C.....	75 H. P.—C. S.
.70	160 C-1	Clamp for Band Brake.....	75 H. P.—C. S.
.50	164	Clamp or Guide for Lever Grip Rod (Upper).....	75 & 90 H. P.—Brass
.60	232	Clamp or Guide for Lever Grip Rod (Lower).....	75 & 90 H. P.—Brass
	465 C	Clutch Band.....	90 H. P.—C. I.
	458 C	Clutch Drum.....	90 H. P.—C. S.
	459 C	Clutch Spider, 2 Arm, Side Clutch.....	90 H. P.—C. I.
	464 C	Clutch Toggle, Side Clutch.....	90 H. P.—C. S.
	462 C	Clutch Wedge, Side Clutch.....	90 H. P.—M. S.
	488 C	Clutch Lever Connector, Side Clutch.....	90 H. P.—C. S.
17.90	142 C	Coupling, Flexible, 2 parts.....	75 & 90 H. P.—C. S.
1.50	260 C	Coupling for Pump Magneto and Governor Shaft.....	75 H. P.—C. I.
1.88	75 C	Connecting Rod Bushing Wrist Pin.....	75 H. P.—Bronze
20.08	44 C-1	Connecting Rod.....	75 H. P.—Drop Forged
6.64	258 C	Cover for Timing Gear Case.....	75 H. P.—C. I.
2.60	266 C	Cover for Crank Case, Fly Wheel End.....	75 H. P.—C. I.
5.60	10 C	Cover for Water Pump Casing.....	75 H. P.—C. I.
5.00	39 C	Cover, Oil Pump Casing.....	75 H. P.—C. I.
3.50	40 C	Cover, Oil Pump Casing.....	75 H. P.—C. I.
4.70	56 C	Cover, Oil Well Plate.....	75 H. P.—C. I.
3.50	57 C	Cover for Oil Well Inlet Plate.....	75 H. P.—C. I.
.50	248 C	Collar for Governor.....	75 H. P.—C. I.
1.96	132 C	Collar for End of Differential Shaft.....	75 H. P.—C. S.
.26	297 C	Coupling Link for Power Steer Chain.....	75 & 90 H. P.—M. S.
6.72	223	Collar, Clutch Shifting.....	75 & 90 H. P.—Bronze
.50	200 C	Collar for Reverse Gear Pin.....	75 H. P.—C. S.
2.42	168 C	Collar on Sliding Gear Shaft.....	75 H. P.—C. S.
.36	392 C	Collar only for Top Chain Carrier Shaft.....	75 & 90 H. P.—C. I.
.46	392 C	Collar for Top Chain Carrier Shaft with Set Screw and Nut.....	75 & 90 H. P.—C. I.
.90	213 C	Collar, 3" Spacing, for 30" Tracks only.....	75 H. P.—C. I.
1.08	214 C	Collar, 4" Spacing.....	75 H. P.—C. I.
.50	169 C	Collar, Spacing on Front Idler.....	75 H. P.—C. I.
.50	164 C	Collar, Spacing for Front Wheel.....	75 & 90 H. P.—C. I.
.80	456 C	Collar, Dust Collar for Main Crank Shaft.....	75 H. P.—Brass
2.42	168 C	Collar for Direct Drive Shaft.....	75 H. P.—C. S.
	460 C	Collar for Clutch Shifter, 8¼ bore.....	90 H. P.—Bronze
	461 C	Collar for Sliding Clutch.....	90 H. P.—C. S.
	475 C	Collar for Sheave Pin, Special.....	90 H. P.—C. S.
	515 C	Collar on Main Axle, 30" Track Extension.....	75 & 90 H. P.—C. I.
	484 C	Collar for Direct Drive Shaft.....	90 H. P.—C. S.
	488 C	Connector for Clutch Lever.....	90 H. P.—C. S.
1.74	436 C	Coupling for Oiler Drive, 3 pieces.....	75 H. P.—C. R. S.
1.25	437 C	Coupling for K. W. Magneto, 2 pieces.....	75 H. P.—C. R. S.

C. L. BEST GAS TRACTION CO.

2.00	278	C	Coupling for Bosch and Splitdorf Magneto, 3 pieces.....	75 H. P.—C. R. S.
15.04	143	C	Coupling, Solid, with Bevel Gear.....	75 & 90 H. P.—C. S.
13.04	306	C	Coupling, Split, for Stationary Drive, used with Gears 305 C and 307 C (special).....	75 H. P.—C. S.
94	416	C	Control Wire Bracket.....	75 & 90 H. P.—C. S.
4.30	318	C	Conduit Pipe Complete, with Wires.....	75 H. P.
1.48	318	C-1	Conduit Pipe (only).....	75 H. P.
2.50	97	C	Connecting Rod Bearing or Shell, each half	75 H. P.—Special Metal
22.00	173	C	Coil, Splitdorf.....	75 H. P.
.18	427	C	Cover for Gear Case, N. S., Power Steer	75 & 90 H. P.—Galv. Iron
	96	C	Cover for End Bearing.....	75 H. P.
21.00	140	C	Cover for Transmission Gear Case.....	75 H. P.—C. I.
25	290	C	Cover or Cap for Oil Pocket on End Bearing	75 H. P.—C. I.
.95	332	C	Cocks for Water Pipe Drain.....	75 H. P.—Brass
.80	273	C	Cocks, Priming.....	75 H. P.—Brass
1.20	177	C	Cocks, Relief.....	75 H. P.—Brass
.20	397	C	Cover for Oil Caps on Diff. Shaft No. 396 C	75 & 90 H. P.—C. I.
2.00	314	C	Collar, Ball Bearing End Truss on Fan.....	75 H. P.
	590	C	Cover for End of Transmission Case.....	75 & 90 H. P.—C. I.
2.50	591	C	Cover or Hood for Magneto.....	75 & 90 H. P.—Leather
1.50	592	C	Cover or Boot for Gear Shifter.....	75 & 90 H. P.—Leather
	605	C	Collar Clutch Thrust.....	90 H. P.—C. I.
6.00	85	C	Crank Shaft Gear, Valve Cage Motor.....	75 H. P.—C. S.
8.62	228	C	Crank Shaft Gear.....	75 H. P.—Chrome
75.00	1	C	Crank Case, O. S., Upper.....	75 H. P.—C. I.
86.00	2	C	Crank Case, O. S., Lower.....	75 H. P.—C. I.
85.44	234	C	Crank Case, N. S., Upper.....	75 H. P.—C. I.
86.34	224	C	Crank Case, N. S., Lower.....	75 H. P.—C. I.
112.56	334	C	Crank Shaft.....	75 H. P.—Drop Forged
7.74	53	C	Cradle, Fly Wheel End, Valve Cage Motor	75 H. P.—C. I.
5.12	54	C	Cradle Bearings, Valve Cage Motor.....	75 H. P.—C. I.
5.76	55	C	Cradle Center Bearings, Valve Cage Motor	75 H. P.—C. I.
5.40	251	C	Cradle Center Bearings.....	75 H. P.—C. I.
5.86	252	C	Cradle Center Bearings.....	75 H. P.—C. I.
6.20	253	C	Cradle Front End Bearings.....	75 H. P.—C. I.
7.55	254	C	Cradle Fly Wheel End Bearing.....	75 H. P.—C. I.
6.70	376	C	Cutter or Fellow for Front Wheel, $\frac{7}{8} \times 2\frac{1}{2}$	75 H. P.—M. S.
8.14	376	C-1	Cutter or Fellow for Front Wheel, 1x3	75 H. P.—M. S.
9.38	376	C-2	Cutter or Fellow for Front Wheel, 1x3 $\frac{1}{2}$	75 H. P.—M. S.
.52	396	C	Cup, Oil, for Diff. Shaft.....	75 & 90 H. P.—C. I.
.20	397	C	Cup, Cover for 396 C on Diff. Shaft.....	75 & 90 H. P.—C. I.
42.00	3	C	Cylinder only, Valve Cage Type.....	75 H. P.—C. I.
25.00	274	C	Cylinder, Removable Head Type.....	75 H. P.—C. I.
16.00	264	C	Cylinder Head only for 274 C and 473 C	75 & 90 H. P.—C. I.
	473	C	Cylinder, Removable Head Type.....	90 H. P.—C. I.

C. L. BEST GAS TRACTION CO.

D

9.50	158 C	Differential Thrust Roller, Bronze Bushed	75 H. P.—C. S.
15.21	294 C	Differential Thrust Roller and Band, Ball Bearing	75 H. P.—C. S.
4.75	294 C-1	Differential Thrust Roller Band only	75 H. P.—C. S.
41.50	130 C-1	Differential Sleeve Sq. Jaw Clutch, Special, use with 30" Track only, used before 265 C Sprocket was used	75 H. P.—C. S.
39.15	130 C	Differential Sleeve with Sq. Jaw Clutch	75 H. P.—C. S.
43.01	394 C	Differential Sleeve, takes place of 130 C	75 H. P.—C. S.
7.68	133 C	Differential Sleeve Clutch, Sq. Jaws	75 H. P.—C. S.
10.32	404 C	Differential Sleeve Clutch, takes place of 133 C	75 H. P.—C. S.
45.71	403 C	Differential Sleeve with Bushings, Internal Clutch, takes place of 130 C and 394 C	75 & 90 H. P.—C. S.
1.96	132 C	Differential Shaft End Collar	75 H. P.—C. S.
89.77	118 C	Differential Gear (only)	75 H. P.—Chrome
95.29	118 C	Differential Gear with Bushings and Pins only	75 H. P.—Chrome
143.71	118 C	Differential Gear all complete	75 H. P.—Chrome
6.36	121 C	Differential Equalizing Gear or Pinion with Bronze Bushing, O. S.	75 H. P.—Chrome
7.51	388 C	Differential Equalizing Gear or Pinion with Bronze Bushing, N. S.	75 H. P.—Chrome
13.09	504 C	Differential Case (Top)	75 H. P.—Sheet Steel
13.09	505 C	Differential Case (Bottom)	75 H. P.—Sheet Steel
37.82	120½ C	Differential Side Bevel, RH, O. S.	75 H. P.—Chrome
32.30	120 C	Differential Side Bevel, LH, O. S.	75 H. P.—Chrome
35.10	400 C	Differential Side Bevel, RH, N. S.	75 H. P.—C. S.
34.24	399 C	Differential Side Bevel, LH, N. S.	75 H. P.—C. S.
45.40	503 C	Differential Shaft, Special, 40 Carbon	75 & 90 H. P.—C. R. S.
24.42	111 C	Drive Pinion, 12 Teeth, Bronze Bushed, LH	75 H. P.—Chrome
19.15	112 C	Drive Pinion, 12 Teeth, RH	75 H. P.—Chrome
18.90	393 C	Drive Pinion, 12 Teeth, takes place of 111C	75 H. P.—Chrome
22.06	414 C	Drive Pinion, 12 Teeth, takes place of 111C and 393 C, LH	75 & 90 H. P.—Chrome
19.42	415 C	Drive Pinion, 12 Teeth, takes place of 112 C, RH	75 H. P.—Chrome
	458 C	Drum for Side Clutch	90 H. P.—C. S.
11.30	506 C	Draw Bar	75 & 90 H. P.—W. I.
4.92	507 C	Draw Bar Hanger	75 H. P.—W. I.
.80	456 C	Dust Collar for Main Crank Shaft	75 H. P.—Brass
7.72	206 C	Dust Guards for Main Sprocket, LH	75 & 90 H. P.—Sheet Steel
7.72	207 C	Dust Guards for Main Sprocket, RH	75 H. P.—Sheet Steel
.15	539 C	Dust Guard Bracket	75 & 90 H. P.—W. I.
1.74	596 C	Dust Guard on Swing Frame	75 & 90 H. P.—Sheet Steel
		E	
3.28	245 C	End Plate for Governor	75 & 90 H. P.—C. I.
6.64	258 C	End Gear Case Cover	75 H. P.—C. I.

C. L. BEST GAS TRACTION CO.

2.60	266 C	End Cover for Crank Case, Fly Wheel End	75 H. P.—C. I.
7.25	18 C	Exhaust Manifold, Valve Cage Motor	75 H. P.—C. I.
5.70	250 C	Exhaust Manifold Pipe	75 H. P.—C. I.
1.40	243 C	Exhaust Cam	75 H. P.—C. I.
.50	339 C	Exhaust Screen (only) for Exhaust Pipe	75 & 90 H. P.
2.50	338 C	Exhaust Pipe	75 & 90 H. P.
2.07	377 C	Exhaust Pipe Flange Bolts to Canopy Top	75 & 90 H. P.—C. S.
F			
5.00	373	Fan Pulley on Fan Shaft	75 & 90 H. P.—C. I.
15.00	76 C	Fan Bracket, O. S., Valve Cage Motor	75 & 90 H. P.—C. S.
12.00	276 C	Fan Bracket, N. S.	75 H. P.—C. S.
2.00	77 C	Fan Bracket Cap	75 H. P.—C. I.
2.00	78 C	Fan Bracket Cap	75 H. P.—C. I.
3.20	210 C	Fan Shaft	75 H. P.—C. R. S.
2.00	314 C	Fan, Ball Bearing End, Truss Collar	75 H. P.
2.80	297	Fan Spider	75 & 90 H. P.—C. S.
1.00	581 C	Fan Blade	75 & 90 H. P.—Saw Steel
14.30	347 C	Fan Belt, 4½"x6' 2½", Wire Stitched	75 & 90 H. P.
13.60	347 C-1	Fan Belt, 4"x6' 2½", Wire Stitched	75 H. P.
8.76	290-1	Fan Shaft Drive Pulley on Crank Shaft, 2¾" Bore	75 H. P.—C. I.
8.76	290-2	Fan Shaft Drive Pulley on Crank Shaft, 3¼" Bore	75 H. P.—C. I.
1.00	402 C	Filler Piece for Steer Segment No. 401 C	75 H. P.—C. I.
1.00	402 C-1	Filler Piece for Steer Segment No. 401 C-1	75 & 90 H. P.—C. I.
2.07	377 C	Flange for Exhaust Pipe (Bolts to Canopy)	75 & 90 H. P.—C. S.
1.00	395 C	Flange for Exhaust Manifold (special)	75 H. P.—C. I.
.90	80 C	Flange for Rotary Water Pump	75 H. P.—C. I.
1.00	42 C	Flange for Water Pump	75 H. P.—C. I.
.90	80 C	Flange for Water Pipe	75 H. P.—C. I.
.60	236 C	Flange for Oil Overflow	75 H. P.—Brass
25.42	369 C	Floor Plate Checkered over Tracks	75 H. P.—M. S.
	369 C-1	Floor Plate Checkered over Tracks	90 H. P.—M. S.
4.00	370 C	Floor Side Rails	75 & 90 H. P.—M. S.
.30	587 C	Flange, Pipe, Brass, ⅜", P. T.	75 & 90 H. P.—Brass
.40	588 C	Flange, Pipe, Brass, ½", P. T.	75 & 90 H. P.—Brass
.94	589 C	Flange, Pipe, Brass, 1½", P. T.	75 & 90 H. P.—Brass
3.69	144 C	Fork, Shifting Gear in Transmission	75 & 90 H. P.—C. S.
2.72	391 C	Fork, Castings to Hold Head Lights	75 H. P.—Bronze
	578 C	Fork, Clutch Shifter	90 H. P.—C. S.
1.35	411 C	Fork, Clutch Shifter for Power Steer, N. S.	75 & 90 H. P.—C. S.
4.00	415	Fork, Clutch Shifter for Power Steer, O. S.	75 H. P.—C. S.
	607 C	Front Wheel Shaft	90 H. P.—C. R. S.
4.81	353 C	Front Idler Shaft	75 & 90 H. P.—C. R. S.
4.80	501 C	Front Wheel Shaft	75 H. P.—C. R. S.
4.06	348 C	Front Wheel Hood	75 & 90 H. P.—Sheet Steel
.40	350 C	Front Wheel Spokes with Nuts	75 & 90 H. P.—M. S.

C. L. BEST GAS TRACTION CO.

6.70	376 C	Front Wheel Cutter, 7/8"x2 1/2".....	75 H. P.—M. S.
8.14	376 C-1	Front Wheel Cutter, 1"x3".....	75 H. P.—M. S.
9.38	376 C-2	Front Wheel Cutter, 1"x3 1/2".....	75 H. P.—M. S.
3.68	368 C	Frame to hold Dist. & Oil Tanks.....	75 & 90 H. P.—Wood
1.00	180 C	Friction Clutch Spring Block.....	75 H. P.—C. S.
35.50	131 C	Front Idler, O. S., used with Bearings 127 C and 128 C.....	75 H. P.—C. S.
43.64	194 C	Front Idler, O. S., used with Bearings 193 C and 198 C.....	75 H. P.—C. S.
43.64	217 C	Front Idler, N. S., used with Bearings 193 C, 198 C, 295 C and 296 C.....	75 H. P.—C. S.
	493 C	Front Idler.....	90 H. P.—C. S.
25.00	24-1	Front Wheel Hub.....	75 H. P.—C. S.
25.00	608 C	Front Wheel Hub.....	90 H. P.—C. S.

G

.75	319 C	Gaskets for Cylinder Head.....	75 H. P.
.07	320 C	Gaskets for Pump and Water Manifold.....	75 H. P.
.40	321 C	Gaskets, Inlet and Exhaust.....	75 H. P.
.20	586 C	Gaskets for Radiator.....	75 & 90 H. P.—Straw Board
8.00	50 C	Gear, Cam Shaft, Valve Cage Motor.....	75 H. P.—C. S.
9.00	51 C	Gear, Cam Idler, Valve Cage Motor.....	75 H. P.—C. S.
8.50	52 C	Gear, Oil Pump Idler, Valve Cage Motor.....	75 H. P.—C. S.
6.00	85 C	Gear, Crank Shaft, Valve Cage Motor.....	75 H. P.—C. S.
5.50	86 C	Gear, Pump and Magneto, Valve Cage Motor	75 H. P.—C. S.
4.00	89 C	Gear, Oil Pump, Helical Cut, Valve Cage Motor.....	75 H. P.—C. S.
4.00	90 C	Gear, Water Pump.....	75 H. P.—M. S.
1.60	91 C	Gear, Oil Pump.....	75 H. P.—M. S.
41.06	110 C	Gear, Sleeve Idler, 18 Teeth, Sq. Jaw Clutch	75 H. P.—Chrome
47.34	301 C	Gear, Long Sleeve Idler, with Internal Clutch, takes place of 110 C.....	75 & 90 H. P.—Chrome
31.84	109 C	Gear, in Transmission Sliding, 27 Teeth, with Sq. Jaw Clutch.....	75 H. P.—Chrome
34.42	299 C	Gear, in Transmission Sliding Gear, with Internal Clutch, takes place of 109 C	75 H. P.—Chrome
30.50	106 C	Gear, in Transmission (Low), 36 Teeth.....	75 & 90 H. P.—Chrome
25.29	107 C	Gear, in Transmission, 27 Teeth.....	75 & 90 H. P.—Chrome
21.05	108 C	Gear, in Transmission, 20 teeth.....	75 H. P.—Chrome
89.77	118 C	Gear, Differential Gear, only.....	75 H. P.—Chrome
95.29	118 C	Gear, Diff. Gear with Bushing & Pins.....	75 H. P.—Chrome
143.71	118 C	Gear, Diff. Gear all Complete.....	75 H. P.—Chrome
32.20	120 C	Gear, Diff., Side Bevel, LH, O. S.....	75 H. P.—Chrome
37.82	120 1/2 C	Gear, Diff., Side Bevel, RH, O. S.....	75 H. P.—Chrome
34.22	399 C	Gear, Differential Side Bevel, LH, takes place of 120 C.....	75 H. P.—C. S.
35.10	400 C	Gear, Differential Side Bevel, RH, takes place of 120 1/2 C.....	75 H. P.—C. S.
6.36	121 C	Gear, Differential Bevel Pinion, with Bronze Bushings.....	75 H. P.—Chrome
7.51	388 C	Gear, Differential Bevel Pinion, takes place of 121 C, with Bronze Bushings.....	75 H. P.—Chrome

C. L. BEST GAS TRACTION CO.

18.44	167 C	Gear, in Transmission Reverse Idler, 15 Teeth, with Bronze Bushings.....	75 & 90 H. P.—Chrome
27.46	305 C	Gear, Special, Cut for Stationary Drive, 20 Teeth	75 H. P.—Cut Steel
18.70	307 C	Gear, Special, Cut for Stationary Drive, 15 Teeth	75 H. P.—Cut Steel
3.22	98 C	Gear, Bevel Oilier Gear.....	75 H. P.—Mach. Steel
3.22	99 C	Gear, Bevel Oilier Gear.....	75 H. P.—Mach. Steel
9.46	163 C	Gear, Bevel Gear for Stationary Drive, 27/16 Bore	75 H. P.—Chrome
24.42	111 C	Gear or Pinion, 12 Teeth, Bushed, LH, Main Drive	75 H. P.—Chrome
19.15	112 C	Gear, or Pinion, 12 Teeth, RH, Main Drive	75 H. P.—Chrome
18.90	393 C	Gear, or Pinion, 12 Teeth, takes place of 111 C, LH.....	75 H. P.—Chrome
22.06	414 C	Gear or Pinion, 12 Teeth, takes place of 111 C and 393 C, LH.....	75 & 90 H. P.—Chrome
19.42	415 C	Gear or Pinion, 12 Teeth, takes place of 112 C, RH	75 H. P.—Chrome
16.20	225 C	Gear, Cam Shaft.....	75 H. P.—Chrome
8.27	226 C	Gear, Magneto Shaft Drive.....	75 H. P.—Chrome
4.25	289 C	Gear, Special for Oil Pump.....	75 H. P.—C. S.
6.70	227 C	Gear, Magneto Shaft.....	75 H. P.—Chrome
8.62	228 C	Gear, Crank Shaft.....	75 H. P.—Chrome
4.25	288 C	Gear, Spiral, Cam Shaft and Oil Pump.....	75 H. P.—C. S.
4.25	289 C	Gear, Spiral, Cam Shaft and Oil Pump.....	75 H. P.—C. S.
11.55	405 C	Gear, Bevel, without Clutch, Power Steer, N. S.	75 & 90 H. P.—Chrome
13.86	406 C	Gear, Bevel, with Clutch, Long Hub, for Power Steer, N. S., with Bushings.....	75 & 90 H. P.—Chrome
13.57	407 C	Gear, Bevel, with Clutch, Short Hub, for Power Steer, N. S., with Bushings.....	75 & 90 H. P.—Chrome
6.64	212	Gear, Bevel, with Clutch, Power Steer, O. S.	75 H. P.—C. S.
9.30	413	Gear, Bevel Gear and Sprocket, Combined with Clutch, O. S., Power Steer.....	75 H. P.—Chrome
5.49	214	Gear, Bevel, Sprocket, Combined Idler, O. S., Power Steer	75 H. P.—C. S.
3.69	144 C	Gear, Fork, Shifting, Transmission.....	75 & 90 H. P.—C. S.
3.74	145 C	Gear, Shifting Lever (lower section only), Transmission	75 & 90 H. P.—C. S.
8.42	361 C	Gear, Shifting Lever, Transmission, Com- plete	75 & 90 H. P.—M. S.
.17	363 C	Gear, Shifting Lever Notch Rod, Transmis- sion	75 & 90 H. P.—C. R. S.
2.44	366 C	Gear, Shifting Lever Sector, Transmission	75 & 90 H. P.
69.41	113 C	Gear, Case, Transmission.....	75 H. P.—C. S.
21.00	140 C	Gear, Case, Transmission (cover for Trans.)	75 H. P.—C. S.
69.41	479 C	Gear, Case, Transmission, takes place of 113 C	75 H. P.—C. S.
70.00	479 C-1	Gear, Case, Transmission.....	90 H. P.—C. S.

C. L. BEST GAS TRACTION CO.

	457 C	Gear, Bevel Ring.....	90 H. P.—C. S.
	486 C	Gear, Sliding Clutch.....	90 H. P.—C. S.
13.09	504 C	Gear, Case, Differential (top).....	75 H. P.—Sheet Steel
13.09	505 C	Gear, Case, Differential (lower).....	75 H. P.—Sheet Steel
.18	427 C	Gear, Box Cover for Power Steer, Case, N. S.	75 & 90 H. P.—Sheet Steel
1.58	428 C	Gear, Box Bracket, for Power Steer Case, N. S.	75 & 90 H. P.—M. S.
10.32	404 C	Gear, Clutch, Differential.....	75 H. P.—C. S.
6.64	114 C	Gear, Case, Transmission Cap next to Long Sleeve Gear.....	75 & 90 H. P.—C. S.
4.77	115 C	Gear, Case, Transmission Cap, next to 36 Tooth Gear.....	75 & 90 H. P.—C. S.
4.88	116 C	Gear, Case, Transmission Cap, next to Bevel Pinion	75 H. P.—C. S.
3.36	117 C	Gear, Case, Transmission Cap, next to Sta- tionary Drive Bevel.....	75 & 90 H. P.—C. S.
9.08	434 C	Gear, C. I. Bevel Idler (use in place of 405 C with 432 C and 433 C, N. S., Power Steer)	75 H. P.—C. I.
9.38	432 C	Gear, C. I. Bevel, Long Hub, with Steel Clutch No. 431 C, riveted on, used in place of 406 C when Cast Iron Gear is used in place of Steel, N. S., Power Steer	75 H. P.—C. S.
9.28	433 C	Gear, C. I. Bevel, Short Hub and Steel Clutch No. 431 C riveted on, used in place of 407 C when Cast Iron Gears are used in place of Steel, N. S., Power Steer.....	75 H. P.—C. S.
2.00	431 C	Gear, Clutch Attachment, used with 432 C and 433 C when Cast Iron Gears are used in place of Steel, in Power Steer	75 H. P.—C. R. S.
.68	11 C	Glans for Water Pipe.....	75 H. P.—C. I.
3.50	28 C	Governor Casing, Brass, Valve Cage Motor	75 H. P.—Brass
10.00	202 C	Governor Casing, Valve Cage Motor.....	75 H. P.—Brass
4.00	203 C	Governor Casing End, Valve Cage Motor	75 H. P.—Brass
4.00	204 C	Governor Casing End, Valve Cage Motor	75 H. P.—Brass
3.28	245 C	Governor End Plate.....	75 & 90 H. P.—C. I.
5.20	246 C	Governor Casing.....	75 & 90 H. P.—C. I.
.30	247 C	Governor Balls.....	75 & 90 H. P.—C. I.
.50	248 C	Governor Collar.....	75 & 90 H. P.—C. I.
2.80	284 C	Governor Shifting Lever.....	75 & 90 H. P.—Brass
3.00	313 C	Governor Sleeve, O. S.....	75 H. P.—C. R. S.
3.39	313 C-1	Governor Sleeve, N. S.....	75 H. P.—C. R. S.
1.00	327 C	Governor Control Extension Rod.....	75 H. P.—C. R. S.
.64	358 C	Governor Control Rod, 1/8" Pipe.....	75 H. P.
2.00	29 C	Governor Casing End Brass, Valve Cage Motor	75 H. P.—Brass
2.50	30 C	Governor Casing End Brass, Valve Cage Motor	75 H. P.—Brass
1.98	31 C	Governor Shifter Brass.....	75 H. P.—Brass
2.80	32 C	Governor Lever Brass.....	75 H. P.—Brass

C. L. BEST GAS TRACTION CO.

2.20	33 C	Governor Trunion Brass, Valve Cage Motor	75 H. P.—Brass
1.00	34 C	Governor Balls Brass, Valve Cage Motor	75 H. P.—Brass
.80	35 C	Governor Weight Brass, Valve Cage Motor	75 H. P.—Brass
2.25	72 C	Governor Control Lever	75 H. P.—Brass
.15	510 C	Governor Shifter Block	75 H. P.—C. R. S.
1.60	23 C	Guide for Tappett or Cam Rod	75 H. P.—C. I.
1.60	263 C	Guide for Tappett or Cam Rod	75 H. P.—C. I.
3.00	373 C	Gudgeon Pin for Track Rollers	75 & 90 H. P.—C. R. S.
.60	232	Guide or Clamp for Lever Grip Rod (lower), Transmission	75 & 90 H. P.—Brass
.50	164	Guide or Clamp for Lever Grip Rod (upper), Transmission	75 & 90 H. P.—Brass
7.72	206 C	Guards or Dust Frame for Main Sprocket, RH	75 H. P.—Sheet Steel
7.72	207 C	Guards or Dust Frame for Main Sprocket, LH	75 & 90 H. P.—Sheet Steel
1.74	596 C	Guards, Dust, on Swing Frame	75 & 90 H. P.—Sheet Steel

H

2.50	14 C	Hand Hole Plate, Motor	75 H. P.—C. I.
2.50	14 C-1	Hand Hole Plate, Motor	75 H. P.—C. I.
2.50	14 C-2	Hand Hole Plate, Motor	75 H. P.—C. I.
2.50	14 C-3	Hand Hole Plate, Motor	75 H. P.—C. I.
3.75	15 C	Hand Hole Plate, Front, Motor	75 H. P.—C. I.
1.00	16 C	Hand Hole Plate, Cylinder, Motor	75 H. P.—C. I.
2.20	43 C	Hand Hole Plate, Back, Motor	75 H. P.—C. I.
1.00	59 C	Handle for Inspection Plate	75 H. P.—C. S.
.35	275 C	Handle for Inspection Plate	75 H. P.—C. I.
3.18	471 C	Handle for Power Steer Shifting Lever	75 & 90 H. P.—M. S.
4.00	58 C	Hand Wheel on Steering Rod for Hand Steer	75 H. P.—C. I.
4.46	58-1	Hand Wheel on Stering Rod for Hand Steer	75 H. P.—C. I.
.46	563 C	Handle for Hand Wheels No. 58 and 58-1	75 H. P.—C. R. S.
5.00	362 C	Hand Wheel in Steering Rod for Power Steer	75 & 90 H. P.
2.75	580 C	Hand Wheel Alumnninum Spider (only)	75 & 90 H. P.—Aluminum
2.00	582 C	Hand Wheel Rim (only)	75 & 90 H. P.
2.06	300 C	Handle for Sector (Carburetor Control)	75 & 90 H. P.—Brass
2.06	154 C	Handle for Sector(Spark Control)	75 & 90 H. P.—Brass
1.14	372 C	Hanger for Main Sprocket Axle (outside)	75 & 90 H. P.—M. S.
1.14	372 C-1	Hanger for Main Sprocket Axle (inside)	75 & 90 H. P.—M. S.
4.92	507 C	Hanger for Draw or Pull Bar	75 H. P.—M. S.
	584 C	Handle for Clutch Shifter	90 H. P.—M. S.
1.00	63 C	Hand Hole Plate for Main Sprocket (triangle), with Felt Packing	75 H. P.—Sheet Steel
1.00	63 C-1	Hand Hole Plate for Main Sprocket (round), with Felt Packing	75 & 90 H. P.—Sheet Steel

C. L. BEST GAS TRACTION CO.

2.72	391 C	Headlight, Support Fork.....	75 H. P.—Bronze
1.05	378 C	Headlight, Base.....	75 H. P.—C. I.
1.60	352 C	Hose Radiator (bottom).....	75 & 90 H. P.—Rubber
1.10	344 C	Hose Radiator (top).....	75 & 90 H. P.—Rubber
2.50	591 C	Hood or Cover for Magneto.....	75 & 90 H. P.—Leather
4.06	348 C	Hood over Front Wheel.....	75 & 90 H. P.—Sheet Steel
5.06	346 C	Hood or Fan Shield.....	75 & 90 H. P.—Sheet Steel
2.24	508 C	Hot Air Pipe Complete.....	75 & 90 H. P.—Galv. Iron
.20	508 C-1	Hot Air Pipe Ell.....	75 & 90 H. P.—Galv. Iron
.60	508 C-2	Hot Air Pipe Leader Pipe.....	75 & 90 H. P.—Galv. Iron
25.00	24-1	Hub for Front or Lead Wheel.....	75 H. P.—C. S.
.77	520 C	Hub Ring.....	75 & 90 H. P.—M. S.
25.00	608 C	Hub for Front or Lead Wheel.....	90 H. P.—C. S.

I

10.00	355 C	I Beam for Swing Frame, outside, 24" and 30" Track.....	75 H. P.—M. S.
12.00	355 C-1	I Beam for Swing Frame, inside, 30" Track.....	75 H. P.—M. S.
35.50	131 C	Idler for Track, Front End, O. S., used with 127 C and 128 C.....	75 H. P.—C. S.
43.64	194 C	Idler for Track, Front End, O. S., used with 193 C and 198 C.....	75 H. P.—C. S.
43.64	217 C	Idler for Track, Front End, N. S., used with 193 C, 198 C, 295 C and 296 C.....	75 H. P.—C. S.
	493 C	Idler for Track, Front End.....	90 H. P.—C. S.
2.50	41 C	Idler Stud for Cam Shaft.....	75 & 90 H. P.—C. S.
9.00	51 C	Idler Gear Cam.....	75 H. P.—C. S.
1.00	62 C	Idler Gear Bushing.....	75 H. P.—Bronze
2.25	65 C	Idler Stud for Oil Pump.....	75 H. P.—C. S.
3.00	238	Inlet Spout for Radiator.....	75 & 90 H. P.—C. I.
1.40	244 C	Inlet Cam.....	75 H. P.—C. I.
10.00	20 C	Inlet Manifold, lower.....	75 H. P.—C. I.
6.40	249 C	Inlet Manifold Pipe.....	75 H. P.—C. I.
5.50	83 C	Inlet Manifold.....	75 H. P.—C. I.
2.20	240 C	Inspection Plate Lugs with Studs.....	75 H. P.—C. S.
.35	275 C	Inspection Plate Handle.....	75 H. P.—C. I.
1.00	59 C	Inspection Plate Handle.....	75 H. P.—C. S.
	435 C	Insert Piece for N. S. Track Spool.	

K.

	543 C	Key, Pulley End, Stationary Drive, $\frac{5}{8}$ "x6".....	75 H. P.—C. R. S.
	544 C	Key, Gear End, Stationary Drive, $\frac{5}{8}$ "x4½".....	75 H. P.—C. R. S.
.60	550 C	Key, Sleeve Gear Shaft, $\frac{5}{8}$ "x4".....	75 H. P.—C. R. S.
.60	551 C	Key Clutch Spider, $\frac{5}{8}$ "x4".....	75 & 90 H. P.—C. R. S.
1.42	552 C	Keys, Trans. Idler, $\frac{5}{8}$ "x15½".....	$\frac{5}{8}$ "x3¼"x5¾" 75 & 90 H. P.—C. R. S.
1.40	553 C	Keys, Trans. Idler, $\frac{5}{8}$ "x4½".....	$\frac{5}{8}$ "x3¼"x11" 75 & 90 H. P.—C. R. S.
.93	554 C	Key, Transmission Direct Drive, $\frac{5}{8}$ "x3¼"x16¼".....	75 & 90 H. P.—C. R. S.
1.13	555 C	Key, Transmission Direct Drive, $\frac{5}{8}$ "x9/16"x6".....	75 & 90 H. P.—C. R. S.
1.25	568 C	Key for Differential Bevel 400 C or 120½ C, $\frac{5}{8}$ "x3¼"x8¼".....	75 H. P.—C. R. S.

C. L. BEST GAS TRACTION CO.

.59	569 C	Key for Differential Bevel 399 C or 120 C, $\frac{5}{8}$ "x9/16"x4 $\frac{3}{4}$ "	75 H. P.—C. R. S.
.59	574 C	Key, Clutch Collar, $\frac{5}{8}$ "x3"	75 H. P.—C. R. S.
	553 C	Key, for Clutch Spider	90 H. P.—C. R. S.
1.00	84	Knuckle for Steering Rod	75 & 90 H. P.—C. I.
.30	393	Knuckle Block for Steering Rod Knuckle	75 & 90 H. P.—C. I.

L

1.05	378 C	Lamp Bracket or Base	75 H. P.—C. I.
2.72	391 C	Lamp Fork	75 H. P.—Bronze
.39	453 C	Lamp Bracket Stud (holds Lamp on Fork)	75 H. P.—C. R. S.
	599 C	Lever Clutch Shifter (short)	90 H. P.—C. S.
	583 C	Lever Clutch Shifter	90 H. P.—C. S.
.25	286 C	Lever for Throttle Butterfly Control	75 & 90 H. P.—Brass
2.80	32 C	Lever Governor Brass	75 H. P.—Brass
2.25	72 C	Lever Governor Control Brass	75 H. P.—Brass
1.00	176 C	Lever for Band Brake (Cast Steel Part only)	75 H. P.—C. S.
1.81	176 C-1	Lever for Band Brake (with Wrought Part welded short)	75 H. P.
2.21	176 C-2	Lever for Band Brake (with Wrought Part welded long)	75 H. P.
2.06	154 C	Lever for Governor Control	75 & 90 H. P.—Brass
2.06	300 C	Lever for Spark and Magneto Control	75 & 90 H. P.—Brass
3.38	360 C	Lever for Main Clutch	75 & 90 H. P.—M. S.
8.42	361 C	Lever for Gear Shifting in Transmission, Complete	75 & 90 H. P.—M. S.
1.24	422 C	Lever for New Style Clutch Shifter, Power Steer	75 & 90 H. P.—M. S.
3.74	145 C	Lever for Shifting Transmission Gear, Lower Section only	75 & 90 H. P.—C. S.
.75	62	Lever Grip for Transmission Shifting Lever	75 & 90 H. P.—Brass
25.00	24-1	Lead Wheel Hub	75 H. P.—C. S.
5.45	65	Lead Wheel Shaft Box	75 & 90 H. P.—C. I.
.35	78	Lead Wheel Shaft Cap (on end of Shaft)	75 & 90 H. P.—C. I.
4.80	501 C	Lead Wheel Shaft	75 H. P.—C. R. S.
4.06	348 C	Lead Wheel Hood	75 & 90 H. P.—Sheet Steel
.40	350 C	Lead Wheel Spokes with Nuts	75 & 90 H. P.—M. S.
6.70	376 C	Lead Wheel Cutter, $\frac{7}{8}$ "x2 $\frac{1}{2}$ "	75 H. P.—M. S.
8.14	376 C-1	Lead Wheel Cutter, 1"x3"	75 H. P.—M. S.
9.38	376 C-2	Lead Wheel Cutter, 1"x3 $\frac{1}{2}$ "	75 H. P.—M. S.
25.00	608 C	Lead Wheel Hub	90 H. P.—C. S.
	607 C	Lead Wheel Shaft	90 H. P.—C. R. S.
2.71	122 C	Link for Track, RH, Chrome	75 H. P.—Chrome
	122 C	Link for Track, RH	75 H. P.—Mang.
2.00	122 C	Link for Track, RH	75 H. P.—Drop Forged
2.00	122 C-1	Link for Track, RH, Sq. Hole Drop Forged	75 & 90 H. P.—Drop Forged
2.71	123 C	Link for Track, LH	75 & 90 H. P.—Chrome
	123 C	Link for Track, LH	75 & 90 H. P.—Mang.
2.00	123 C	Link for Track, LH	75 & 90 H. P.—Drop Forged

C. L. BEST GAS TRACTION CO.

.26	297	C	Link Coupling, Power Steer Chain..75 & 90 H. P.—M. S.
.48	598	C	Link Offset for Power Steer Chain..75 & 90 H. P.—M. S.
86.00	2	C	Lower Base.....75 H. P.—C. I.
86.34	224	C	Lower Base.....75 H. P.—C. I.
2.20	240	C	Lug for Fastening Inspection Plate, with Stud75 H. P.—C. S.

M

109.50	101	C	Main Drive Sprocket, 24" Track.....75 H. P.—Chrome
92.50	101	C	Main Drive Sprocket, 24" Track.....75 H. P.—Carbon
119.70	265	C	Main Drive Sprocket, 30" Track on 75 H. P.24" and 30" Track on 90 H. P.—Chrome
101.32	265	C	Main Drive Sprocket, 30" Track on 75 H. P.24" and 30" Track on 90 H. P.—Carbon
10.00	6	C	Manifold Top Water Pipe.....75 H. P.—C. I.
12.00	7	C	Manifold Side Water Pipe.....75 H. P.—C. I.
1.80	268	C	Manifold Side Water Pipe.....75 H. P.—C. I.
6.50	8	C	Manifold Center Water Pipe.....75 H. P.—C. I.
3.00	262	C	Manifold Center Water Pipe.....75 H. P.—C. I.
7.25	18	C	Manifold Exhaust.....75 H. P.—C. I.
5.70	250	C	Manifold Exhaust Pipe.....75 H. P.—C. I.
10.00	20	C	Manifold Lower Inlet.....75 H. P.—C. I.
6.40	249	C	Manifold Inlet Pipe.....75 H. P.—C. I.
5.50	83	C	Manifold Inlet.....75 H. P.—C. I.
3.86	285	C	Manifold for Carburetor Intake with Butterfly Valve for 2" E and 2" D Carburetor on Removable Cyl. Head Motor75 H. P.—C. I.
2.50	398	C	Manifold Special used on Valve Cage Motor to change from 2½" L to 2" E Carburetor75 H. P.—C. I.
5.50	86	C	Magneto Gear, Valve Cage Motor.....75 H. P.—C. S.
1.80	92	C	Magneto Bracket, Splitdorf.....75 H. P.—C. S.
1.80	261	C	Magneto Bracket, Bosch & K. W.....75 H. P.—C. I.
8.27	226	C	Magneto Shaft Drive Gear.....75 H. P.—Chrome
6.70	227	C	Magneto Shaft Gear.....75 H. P.—Chrome
2.50	271	C	Magneto Drive Shaft Bearing.....75 H. P.—C. I.
.55	281	C	Magneto Wire Pipe Support for Bosch.....75 & 90 H. P.—C. S.
.74	293	C	Magneto Wire Pipe Support for Splitdorf 75 H. P.—C. S.
.54	357	C	Magneto Wire Control Pipe.....75 H. P.

O

.48	598	C	Offset Link for Power Steer Chain..75 & 90 H. P.—M. S.
2.40	47	C	Oil Shaft Bearing, Valve Cage Motor.....75 H. P.—C. I.
5.70	241	C	Oil Pump, Lower Half.....75 H. P.—C. I.
4.60	242	C	Oil Pump, Upper Half.....75 H. P.—C. I.
2.06	259	C	Oil Pump Drive Bearing.....75 H. P.—C. I.
8.50	52	C	Oil Pump Idler Gear, Valve Cage Motor..75 H. P.—C. S.
5.00	39	C	Oil Pump Casing Cover.....75 H. P.—C. I.
3.50	40	C	Oil Pump Casing Cover.....75 H. P.—C. I.
4.70	56	C	Oil Well Plate Cover.....75 H. P.—C. I.
3.50	57	C	Oil Well Inlet Plate.....75 H. P.—C. I.
.50	58	C	Oil Box Cap.....75 H. P.—C. I.
4.00	89	C	Oil Pump Helical Gear.....75 H. P.—C. S.
1.00	61	C	Oil Pump Bronze Bushing.....75 H. P.—Bronze
1.00	62	C	Oil Pump Idler Gear Bushing.....75 H. P.—Bronze
2.25	65	C	Oil Pump Idler Stud, Valve Cage Motor..75 H. P.—C. S.

C. L. BEST GAS TRACTION CO.

.30	68 C	Oil Caps for Bearing Caps.....	75 H. P.—C. I.
.50	272 C	Oil Pan	75 H. P.—Sheet Steel
.46	308 C	Oil Pump Strainer Casting.....	75 H. P.
.52	396 C	Oil Cup for Differential Shaft.....	75 & 90 H. P.—C. I.
.20	397 C	Oil Cup Cover for 396 C.....	75 & 90 H. P.—C. I.
.90	184 C	Oil Pipe Bearing End.....	75 H. P.—C. I.
1.74	436 C	Oil Drive Coupling, 3 pieces, N. S.....	75 H. P.—C. R. S.
1.00	215 C	Oiler Drive Coupling, 3 pieces, O. S.....	75 H. P.—Brass
.50	216 C		
.25	390 C		
40.00	170 C	Oiler, Hancock, 4 Feed.....	75 & 90 H. P.
40.00	170 C-1	Oiler, McCord, 4 Feed.....	75 & 90 H. P.
1.28	171 C	Oiler Supporting Plate.....	75 H. P.—M. S.
2.00	209 C	Oiler Supporting Plate.....	75 H. P.—C. S.
.40	345 C	Overflow Pipe on Radiator.....	75 & 90 H. P.—B. P.
P			
.60	280 C	Pawl for Gear Shift Lever.....	75 & 90 H. P.—C. S.
.50	88 C	Petticoat for Valve Rod.....	75 H. P.—Brass
19.00	5 C	Piston with Rings and Bushings.....	75 H. P.—C. I.
	472 C	Piston with Rings and Bushings.....	90 H. P.—C. I.
1.00	66 C	Piston Ring.....	75 H. P.—C. I.
1.00	66 C-1	Piston Ring (Oversize).....	75 H. P.—C. I.
	487 C	Piston Ring.....	90 H. P.—Seamless
5.00	79 C	Piston Pin Connecting Piston to Rod.....	75 H. P.—Tubing
1.88	75 C	Piston Pin Bushing.....	Manganese Bronze
1.50	124 C	Pins for Track Link, Half Round, Plain, Both Ends Drilled for Cotter Pins.....	75 H. P.—Chrome
.78	124 C-1	Pins for Track Link, Half Round, Both Ends Drilled for Cotter Pins.....	75 H. P.—Drop Forged
.76	124 C-2	Pins for Track Link, Half Round with Sq. Head	75 & 90 H. P.—Drop Forged
3.00	373 C	Pin, Gudgeon for Flanged Track Rollers 186 C and 187 C.....	75 & 90 H. P.—C. R. S.
.50	336 C	Pin, for Rocker Arm Clevis.....	75 H. P.—C. R. S.
.70	312 C	Pin, for Rocker Arm Stand or Bracket	75 H. P.—C. R. S.
.12	322 C	Pin, for Governor Balls and Weights.....	75 H. P.—C. R. S.
.25	323 C	Pin, for Butterfly Valve in Carburetor Intake Manifold	75 H. P.—C. R. S.
.08	426 C	Pin, for Clutch Shifting Lever, N. S., Power Steer	75 & 90 H. P.—Rivet Steel
3.50	480 C	Pin, for Reverse Idler Gear in Transmission with Nut, use with 113 C Trans. Case only	75 H. P.—C. R. S.
3.12	480 C	Pin, for Reverse Idler Gear in Transmission without Nut, use with 113 C Trans. Case only	75 H. P.—C. R. S.
	480 C-1	Pin, for Reverse Idler Gear in Transmission, use with 479 C Trans. Case only.....	75 & 90 H. P.—C. R. S.
6.36	121 C	Pinion Bevel, for Differential Gear 118 C, with Bushing	75 H. P.—Chrome
7.51	388 C	Pinion Bevel, for Differential Gear 118 C, takes place of 121 C, with Bushing.....	75 H. P.—Chrome
24.42	111 C	Pinion, Main Drive, LH.....	75 H. P.—Chrome
19.15	112 C	Pinion, Main Drive, RH.....	75 H. P.—Chrome

C. L. BEST GAS TRACTION CO.

18.90	393 C	Pinion, Main Drive, LH, takes place of 111 C	75 H. P.—Chrome
22.06	414 C	Pinion, Main Drive, LH, takes place of 111 C and 393 C	75 & 90 H. P.—Chrome
19.42	415 C	Pinion, Main Drive, RH, takes place of 112 C	75 H. P.—Chrome
11.52	119 C	Pinion, Main Drive Bevel, works with 118 C	75 H. P.—Chrome
.40	345 C	Pipe, Overflow, Radiator	75 & 90 H. P.—B. P.
.50	21 C	Pipe Clamps, Exhaust and Intake	75 H. P.—C. S.
10.00	6 C	Pipe, Top Water Pipe	75 H. P.—C. I.
12.00	7 C	Pipe, Side Water	75 H. P.—C. I.
6.50	8 C	Pipe, Center Water	75 H. P.—C. I.
.90	80 C	Pipe Flange for Water Pipe	75 H. P.—C. I.
1.80	268 C	Pipe, Side Water	75 H. P.—C. I.
5.70	250 C	Pipe, Exhaust	75 H. P.—C. I.
6.40	249 C	Pipe, Inlet	75 H. P.—C. I.
2.50	398 C	Pipe, Short Intake Special, when using 2E Schebler Carburetor on O. S. Motor	75 H. P.—C. I.
1.48	318 C-1	Pipe Conduit (only)	75 H. P.
4.30	318 C	Pipe Conduit Complete, with Wires	75 H. P.
.54	357 C	Pipe for Magneto Control Wire	75 H. P.
2.50	338 C	Pipe, Exhaust, 4" O. D. 42" long	75 & 90 H. P.
	466 C	Pinion Bevel	90 H. P.—C. S.
	467 C	Pin for Sliding Clutch Collar	90 H. P.—M. S.
	468 C	Pin for Clutch Wedge	90 H. P.—M. S.
.25	495 C	Pin for Differential Collar	75 & 90 H. P.—Simplex Steel
.26	499 C	Pin for Clutch (Long)	75 & 90 H. P.—C. R. S.
.07	498 C	Pin for Clutch (Short)	75 & 90 H. P.—C. R. S.
2.02	502 C	Pin, Differential Roller, without Nut, O. S.	75 H. P.—C. R. S.
2.37	502 C	Pin, Differential Roller, with nut, O. S.	75 H. P.—C. R. S.
2.25	502 C-1	Pin, Differential Roller, without Nut, N. S.	75 H. P.—C. R. S.
2.60	502 C-1	Pin, Differential Roller, with Nut, N. S.	75 H. P.—C. R. S.
	531 C	Pin, Bevel Gear Thrust	90 H. P.—C. R. S.
.01	562 C	Pin, Cotter, for Track	75 & 90 H. P.—M. S.
1.10	595 C	Pin, for Pull Bar	75 & 90 H. P.—M. S.
.24	567 C	Pin, Power Steer Idler Bevel	75 H. P.—C. R. S.
.26	570 C	Pin, Trans. Lever	75 & 90 H. P.—C. R. S.
	476 C	Pin, Sheave	90 H. P.—M. S.
.30	587 C	Pipe Flange Brass, $\frac{3}{8}$ " P. T.	75 & 90 H. P.—Brass
.40	588 C	Pipe Flange Brass, $\frac{1}{2}$ " P. T.	75 & 90 H. P.—Brass
.94	589 C	Pipe Flange Brass, $1\frac{1}{2}$ " P. T.	75 & 90 H. P.—Brass
5.50	281	Plate, Radiator Side	75 & 90 H. P.—C. I.
25.00	278	Plate, Radiator Tube (Top and Bottom)	75 & 90 H. P.—Brass
2.50	14 C	Plates, Back Hand Hole	75 H. P.—C. I.
3.75	15 C	Plates, Front Hand Hole	75 H. P.—C. I.
1.00	16 C	Plates, Cylinder Hand Hole	75 H. P.—C. I.
2.20	43 C	Plates, Back Hand Hole	75 H. P.—C. I.
4.70	56 C	Plate Cover for Oil Well	75 H. P.—C. I.
3.50	57 C	Plate for Oil Well Inlet	75 H. P.—C. I.
2.50	182 C	Plates, Motor Inspection	75 & 90 H. P.—C. I.
.50	205	Plug for Top of Radiator	75 & 90 H. P.—C. I.

C. L. BEST GAS TRACTION CO.

.55	549 C	Plate for Clutch Shifter Shaft.....	75 & 90 H. P.—M. S.
1.00	63 C	Plate, Hand Hole, Main Sprocket (Triangle)	75 H. P.—Sheet Steel
1.00	63 C-1	Plate, Hand Hole, Main Sprocket (Round)	75 & 90 H. P.—Sheet Steel
	602 C	Plate, Brake Shaft.....	90 H. P.—M. S.
.82	315 C	Push Rod for Valve.....	75 H. P.—T. S.
8.76	290-1	Pulley for Fan Drive on Crank, 2¾" Bore	75 H. P.—C. I.
8.76	290-2	Pulley for Fan Drive on Crank, 3¼" Bore	75 H. P.—C. I.
5.00	373	Pulley for Fan Shaft.....	75 & 90 H. P.—C. I.
3.00	308	Pulley for Belt Tightener (used with Valve Cage Motor only).....	75 H. P.—C. I.
1.20	382 C	Pulley for Lighting Dynamo, Fisher (Solid Pulley), 1½"x3¾" Diam.....	75 H. P.—C. I.
1.36	387 C	Pulley for Lighting Dynamo, 5¼" Diam., Aplco (Split Pulley).....	75 H. P.—C. I.
6.28	410	Pulley for Lighting Dynamo, Aplco (Alumi- num).....	75 H. P.
1.10	595 C	Pull Bar Pin.....	75 & 90 H. P.—M. S.
R			
10.00	230 C	Revolving Drum to carry Track.....	75 H. P.—C. S.
1.20	177 C	Relief Cock for Motor.....	75 H. P.—Brass
2.00	582 C	Rim for Hand Wheel, Hard Wood.....	75 & 90 H. P.
1.00	66 C	Ring for Piston.....	75 H. P.—C. I.
1.00	66 C-1	Ring for Piston (oversize).....	75 H. P.—C. I.
	487 C	Ring for Piston.....	90 H. P.—C. I.
.77	520 C	Ring for Hub.....	75 & 90 H. P.—M. S.
.32	266	Ring for Spark Arrester.....	75 & 90 H. P.—C. I.
16.18	186 C	Roller, Outside Flange.....	75 & 90 H. P.—Chilled Iron
13.10	187 C	Roller, Inside Flange.....	75 & 90 H. P.—Chilled Iron
	195 C	Roller, Outside Flange.....	75 H. P.—Manganese
2.00	60 C	Roller, Chain Carrier.....	75 & 90 H. P.—C. I.
1.92	211 C	Roller, for Idler, without Flange.....	75 & 90 H. P.—C. I.
9.50	158 C	Roller, for Differential (Plain Steel).....	75 H. P.—C. S.
15.21	294 C	Roller for Differential (Ball Bearing), Roller and Band.....	75 H. P.—C. S.
4.75	294 C	Roller for Differential (Band only).....	75 H. P.—C. S.
6.00	172 C	Roller Bracket.....	75 & 90 H. P.—C. S.
5.52	125 C	Roller Bracket.....	75 & 90 H. P.—C. S.
6.00	126 C	Roller Bracket.....	75 & 90 H. P.—C. S.
3.00	373 C	Roller Shaft or Gudgeon Pin.....	75 & 90 H. P.—C. R. S.
2.50	24 C	Rocker Arm Bracket or Stand, O. S.....	75 H. P.—C. S.
2.50	267 C	Rocker Arm Bracket or Stand, N. S.....	75 H. P.—C. I.
4.00	25 C	Rocker Arm with Bushing.....	75 H. P.—C. S.
.65	233 C	Rocker Arm Bushing, Long.....	75 H. P.—Bronze
.60	181 C	Rocker Arm Bushing, Short.....	75 H. P.
4.00	93 C	Rocker Arm with Bushing.....	75 H. P.—C. S.
.07	312 C	Rocker Arm Stand Pin.....	75 H. P.—C. R. S.
.92	534 C	Rod for Brake, LH.....	75 H. P.—M. S.
.76	535 C	Rod for Brake, RH.....	75 H. P.—M. S.
.88	526 C	Rod for Power Steer Safety.....	75 H. P.—M. S.
5.96	356 C	Rod for Steering, Hand Steer.....	75 H. P.—C. R. S.
4.66	356 C-1	Rod for Steering, Power Steer.....	75 & 90 H. P.—C. R. S.
.17	363 C	Rod for Gear Shifting Lever.....	75 & 90 H. P.—C. R. S.
.82	315 C	Rod Push Rod for Valve.....	75 H. P.—T. S.

C. L. BEST GAS TRACTION CO.

1.00	327 C	Rod for Governor Control Extension.	75 H. P.—C. R. S.
.64	358 C	Rod for Governor Control, $\frac{1}{8}$ " Pipe	75 H. P.—Pipe
	585 C	Rod for Lever	90 H. P.—M. S.

S

.50	339 C	Screen for Exhaust or Spark Arrester	75 & 90 H. P.
1.00	557 C	Scraper, LH	75 & 90 H. P.—M. S.
1.00	556 C	Scraper, RH	75 & 90 H. P.—M. S.
.48	558 C	Scraper Brace (long)	75 & 90 H. P.—M. S.
.36	559 C	Scraper Brace (short)	75 & 90 H. P.—M. S.
.80	560 C	Scraper Angle Piece	75 & 90 H. P.—M. S.
1.25	364 C	Seat, Pressed Steel	75 H. P.
3.70	417 C	Seat, Cast Iron	75 & 90 H. P.—C. I.
2.00	367 C	Seat, Spring, Long Section	75 & 90 H. P.—M. S.
.48	367 C-1	Seat, Spring, Short Section	75 & 90 H. P.—M. S.
2.44	356 C	Sector for Transmission Gear Shift Lever	75 & 90 H. P.—M. S.
9.28	155 C	Segment for Steering Worm (on Front Wheel Circle)	75 H. P.—C. I.
15.55	155 C-1	Segment for Steering Worm (on Front Wheel Circle)	75 H. P.—C. S.
12.39	401 C	Segment for Steering Worm, used in place of 155 C-1	75 H. P.—C. S.
12.39	401 C-1	Segment for Steering Worm, used in place of 401 C	75 & 90 H. P.—C. S.
1.00	402 C	Segment, Inserted Center, used with 401 C	75 H. P.—C. I.
1.00	402 C-1	Segment, Inserted Center, used with 401 C-1	75 & 90 H. P.—C. I.
3.00	373 C	Shaft or Gudgeon Pin for 186 C and 187 C Track Roller	75 & 90 H. P.—C. R. S.
.50	316 C	Shaft for Water Pump Idler Gear	75 H. P.—C. R. S.
3.00	329 C	Shaft for Water Pump and Magneto	75 H. P.—C. R. S.
2.50	328 C	Shaft for Water Pump Drive, Long Section	75 H. P.—C. R. S.
.66	330 C	Shaft for Oil Pump Drive, Short Section	75 H. P.—C. R. S.
.64	331 C	Shaft for Oil Pump Idler Gear	75 H. P.—C. R. S.
.86	337 C	Shaft for Oil Pump Drive, Long Section	75 H. P.—C. R. S.
4.81	353 C	Shaft for Front Track Idler, $2\frac{7}{8}$ "x22"	75 & 90 H. P.—C. R. S.
3.20	210 C	Shaft for Fan only	75 H. P.—C. R. S.
.52	429 C	Shaft Connecting Power Steer to Worm	75 & 90 H. P.—C. R. S.
2.01	425 C	Shaft for Power Steer Gear, NS	75 & 90 H. P.—C. R. S.
1.01	421 C	Shaft for Power Steer Clutch Shifter, NS	75 & 90 H. P.—C. R. S.
7.60	333 C	Shaft for Cams (only)	75 H. P.—C. R. S.
112.56	334 C	Shaft Main Crank	75 H. P.—Drop Forged
22.68	371 C	Shaft for Main Sprocket, 24" Track	75 H. P.—C. R. S.
26.04	371 C-1	Shaft for Main Sprocket, 30" Track	75 & 90 H. P.—C. R. S.
480	C-1	Shaft for Reverse Idler in Transmission, used with 479 C Case	75 & 90 H. P.—C. R. S.

C. L. BEST GAS TRACTION CO.

11.11	483	C	Shaft for Transmission Idler Gear, 27 $\frac{7}{8}$ "x 32 $\frac{7}{8}$ ".....	75 & 90 H. P.—40 Carbon Steel
17.87	485	C	Shaft for Direct Drive only, with Keys 3"x40 $\frac{5}{8}$ ".....	75 H. P.—40 Carbon Steel
11.18	490	C	Shaft for Stationary Drive, 24" Track.....	75 H. P.—C. R. S.
12.28	491	C	Shaft for Stationary Drive, 30" Track.....	75 H. P.—C. R. S.
	481	C	Shaft, Direct Drive.....	90 H. P.—Nickel Steel
45.40	503	C	Shaft for Differential (40 Carbon Special)	75 H. P.—C. R. S.
2.52	500	C	Shaft, Clutch Shifter.....	75 & 90 H. P.—C. R. S.
4.80	501	C	Shaft for Front Wheel.....	75 H. P.—C. R. S.
1.75	509	C	Shaft for Chain Carrier Roller, 1 $\frac{1}{4}$ "x16".....	75 & 90 H. P.—Seamless Steel Tubing
.92	516	C	Shaft for Diff. Pinion or Equalizing Gear or Pinion, 1 1/16"x10 $\frac{5}{8}$ ", Simplex Steel.....	75 H. P.
.40	517	C	Shaft for Steering Worm.....	75 & 90 H. P.—C. R. S.
1.03	536	C	Shaft for Brakes.....	75 H. P.—M. S.
1.08	566	C	Shaft for Power Steer Clutch, O. S.....	75 H. P.—C. R. S.
.25	496	C	Shaft for Lubricator.....	75 & 90 H. P.—C. R. S.
1.50	497	C	Shaft for Gear Shifter.....	75 & 90 H. P.—C. R. S.
5.96	356	C	Shaft or Rod for Hand Steer (only).....	75 H. P.—C. R. S.
4.60	356	C-1	Shaft or Rod for Power Steer (only).....	75 & 90 H. P.—C. R. S.
	503	C-1	Shaft, Clutch.....	90 H. P.—C. R. S.
	606	C	Shaft, Side Clutch Lever.....	90 H. P.—C. R. S.
	607	C	Shaft, Front Wheel.....	90 H. P.—C. R. S.
1.35	507	C	Shoe for Track, 18".....	75 H. P.—M. S.
1.53	565	C	Shoe for Track, 20".....	75 H. P.—M. S.
1.53	564	C	Shoe for Track, 22".....	75 H. P.—M. S.
1.75	518	C	Shoe for Track, 24".....	75 H. P.—M. S.
2.06	519	C	Shoe for Track, 30".....	75 & 90 H. P.—M. S.
7.00	70	C	Shoe for Clutch, without Lagging, O. S.....	75 H. P.—C. S.
10.50	70	C	Shoe for Clutch, with Lagging, O. S.....	75 H. P.—C. S.
6.78	292	C	Shoe for Clutch, without Lagging, N. S.....	75 H. P.—C. S.
10.28	292	C	Shoe for Clutch, with Lagging, N. S.....	75 H. P.—C. S.
3.69	144	C	Shifter Fork for Transmission Gear.....	75 & 90 H. P.—C. S.
	578	C	Shifter for Clutch.....	90 H. P.—C. S.
1.35	411	C	Shifter for Power Steer Clutch, N. S.....	75 & 90 H. P.—C. S.
4.00	415		Shifter for Power Steer Clutch, O. S.....	75 H. P.—C. S.
7.00	283	C	Shifter for Main Clutch.....	75 H. P.—C. S.
2.25	31	C	Shifter Governor Brass.....	75 H. P.—Brass
	474	C	Sheave for Cable take up.....	90 H. P.—C. S.
50.72	351	C	Side Bar Main 10" Channel.....	75 H. P.—C. S.
	351	C-1	Side Bar Main 10" Channel.....	90 H. P.—C. S.
5.50	281		Side Radiator.....	75 & 90 H. P.—C. I.
7.60	71	C	Sleeve Clutch.....	75 H. P.—C. S.
3.00	313	C	Sleeve for Governor, O. S.....	75 H. P.—C. R. S.
3.39	313	C-1	Sleeve for Governor, N. S.....	75 H. P.—C. R. S.
41.50	130	C-1	Sleeve on Diff. with Square Jaw Clutch, used with 30" Track only before 265 C Sprocket was used.....	75 H. P.—C. S.
39.15	130	C	Sleeve on Diff. Shaft, with Square Jaw Clutch	75 H. P.—C. S.
43.01	394	C	Sleeve on Diff. Shaft, takes place of 130 C	75 H. P.—C. S.

C. L. BEST GAS TRACTION CO.

45.71	403 C	Sleeve on Diff. Shaft, takes place of 394 C	75 H. P.—C. S.
	403 C-1	Sleeve on Diff. Shaft.....	90 H. P.—C. S.
.75	380 C	Spring for Coupling.....	75 & 90 H. P.
.32	335 C	Spring for Governor.....	75 H. P.—Spring Steel
2.00	367 C	Spring for Seat.....	75 & 90 H. P.—M. S.
.16	438 C	Spring for Trigger on Control Lever (Coil Spring).....	75 & 90 H. P.—Spring Steel
1.00	349 C	Spring for Steering Worm, Main Section.....	75 & 90 H. P.—Spring Steel
.40	349 C-1	Spring for Steering Worm, Short Section.....	75 & 90 H. P.—Spring Steel
.40	511 C	Spring, Clutch Shoe.....	75 & 90 H. P.—Spring Steel
.65	512 C	Spring for Brake Rod.....	75 H. P.—Spring Steel
.60	513 C	Spring for Friction Clutch.....	75 & 90 H. P.—Spring Steel
1.25	514 C	Spring for Steer or Lead Wheel.....	75 & 90 H. P.—Spring Steel
.46	325 C	Spring for Valve for Cylinder Head Motor.....	75 H. P.—Spring Steel
.46	325 C-1	Spring for Valve for Valve Cage Motor.....	75 H. P.—Spring Steel
8.00	419 C	Spring, Double Coil, for Main Frame.....	75 & 90 H. P.
	609 C	Spring, Double, for Main Frame.....	75 & 90 H. P.
	141 C	Spool for Track, Mang.....	75 & 90 H. P.—Mang.
1.15	141 C-1	Spool for Track, Case Hardened.....	75 & 90 H. P.
	492 C	Spool for Track.....	75 H. P.—C. S.
	492 C-1	Spool for Track.....	75 H. P.—C. S.
	492 C-2	Spool for Track.....	75 H. P.—Steel Tubing
	459 C	Spider, 2 Arm, for Clutch.....	90 H. P.—C. I.
2.80	297	Spider for Fan.....	75 H. P.—C. S.
2.75	580 C	Spider for Hand Wheel (Aluminum).....	75 & 90 H. P.
23.67	69 C	Spider, 3 Arm, Clutch, with Bushing.....	75 H. P.—C. S.
.40	350 C	Spokes for Front or Lead Wheel.....	75 & 90 H. P.—M. S.
	310 C	Sprocket for Special Stationary Drive, used on Engine 225 only.....	75 H. P.—C. S.
	311 C	Sprocket for Special Stationary Drive, used on Engine 225 only.....	75 H. P.—C. S.
5.28	410 C	Sprocket for Power Steer, N. S.....	75 H. P.—C. S.
9.30	413	Sprocket for Power Steer, O. S., combined with Bevel Gear.....	75 H. P.—Chrome
3.75	246-1	Sprocket on Crank Shaft for O. S. Power Steer, 2 3/4" Bore.....	75 H. P.—Chrome
3.75	246-2	Sprocket on Crank Shaft for N. S. and O. S. Power Steer, 3 1/4" Bore.....	75 & 90 H. P.—Chrome
109.50	101 C	Sprocket for Main Drive, 18-20-22-24" Track.....	75 H. P.—Chrome
92.50	101 C	Sprocket for Main Drive, 18-20-22-24" Track.....	75 H. P.—40 Carbon
119.70	265 C	Sprocket for Main Drive, 30" Track only, Chrome. 30" Track 75 H. P., 24" and 30" Track 90 H. P.	
101.32	265 C	Sprocket for Main Drive, 30" Track only, 40 Carbon. 30" Track 75 H. P., 24" and 30" Track 90 H. P.	
4.68	593 C	Spring Bar or Spring Support Bar, 24" Track.....	75 H. P.—M. S.
5.12	593 C-1	Spring Bar or Spring Support Bar, 30" Track.....	75 & 90 H. P.—M. S.
2.74	594 C	Spark Arrester, complete.....	75 & 90 H. P.

C. L. BEST GAS TRACTION CO.

.50	339	C	Spark Arrester Screen.....	75 & 90 H. P.
.75	265		Spark Arrester Bowl Casting.....	75 & 90 H. P.—C. I.
.32	266		Spark Arrester Screen Clamp Ring.....	75 & 90 H. P.—C. I.
5.00	136	C	Spring Support with Large Stem, Threaded.....	75 H. P.—C. S.
4.92	136	C-1	Spring Support with Large Stem (bottom).....	75 H. P.—C. S.
4.00	136	C-2	Spring Support with Small Stem (bottom).....	75 & 90 H. P.—C. S.
2.04	137	C	Spring Support, without Stem (top).....	75 & 90 H. P.—C. S.
	478	C	Spring Support (top).....	90 H. P.—C. S.
	477	C	Spring Support (bottom).....	90 H. P.—C. S.
.85	494	C	Starting Bar.....	75 & 90 H. P.—C. R. S.
1.25	67	C	Strainer Casting, Water (only).....	75 H. P.—C. I.
2.00	418	C	Strainer Casting for Air Intake (Harvester Motor only).....	Brass
.46	308	C	Strainer Casting for Oil Pump.....	75 H. P.
2.20	156	C	Steering Worm.....	75 & 90 H. P.—C. I.
1.50	337		Steering Worm Bracket.....	75 & 90 H. P.—C. I.
5.52	174	C	Stationary Drive Outside Bearing or Box.....	75 H. P.—C. S.
3.36	117	C	Stationary Drive Outside Bearing Cap.....	75 H. P.—C. S.
3.36	117	C	Stationary Drive Inside Bearing Cap.....	75 & 90 H. P.—C. S.
.09	423	C	Stud for Clutch Shifting Lever in N. S. Power Steer.....	75 & 90 H. P.—C. R. S.
.21	439	C	Stud for Crank Case, 1"x3½".....	75 H. P.—C. R. S.
.11	440	C	Stud for Lug Holding Inspection Plate in Place, ⅝"x4⅝".....	75 H. P.—T. B. S.
.14	441	C	Stud for Lug 240 C Holding Inspection Plate in Place ⅝"x6".....	75 H. P.—T. B. S.
.09	442	C	Stud for Crank Case Door Guide, ¼"x2⅜".....	75 H. P.—C. R. S.
.07	443	C	Stud for Water Pump, 5/16"x2".....	75 H. P.—C. R. S.
.07	444	C	Stud for Top Water Manifold, ½"x4¼".....	75 H. P.—T. B. S.
.11	445	C	Stud for Side Water Manifold, ½"x3⅝".....	75 H. P.—T. B. S.
.15	446	C	Stud for Tappett Guide, ¾"x3⅝".....	75 H. P.—T. B. S.
.20	447	C	Stud for Cylinder Head, ¾"x7⅝".....	75 H. P.—T. B. S.
.24	448	C	Stud for Cylinder Head and Manifold, ¾"x7¾".....	75 H. P.—T. B. S.
.08	449	C	Stud for Governor Control Lever, ½"x5¼".....	75 H. P.—T. B. S.
.07	450	C	Stud for Rocker Arm Bracket, ½"x1¾".....	75 H. P.—T. B. S.
.31	451	C	Stud for Transmission Case Cover, ⅝"x2⅜".....	75 & 90 H. P.—C. R. S.
.05	452	C	Stud for Governor Block, ⅝"x1".....	75 H. P.—C. R. S.
.39	453	C	Stud for Connecting Head Light to Fork. ½" U. S. S. Thread.....	75 H. P.—C. R. S.
.15	454	C	Stud for Valve Cage, ¾"x2⅞".....	75 H. P.—T. B. S.
	489	C	Stud for Differential Box, ⅞"x9⅛".....	75 & 90 H. P.—C. R. S.
.96	528	C	Stand for Arrow.....	75 & 90 H. P.—M. S.
.55	281	C	Support for Bosch Magneto Wire Pipe.....	75 H. P.—C. S.
.74	293	C	Support for Splitdorf Magneto Wire Pipe.....	75 H. P.—C. S.
2.14	159	C	Support for Band Brake.....	75 H. P.—C. S.
1.28	171	C	Support Plate for Oiler.....	75 H. P.—M. S.

C. L. BEST GAS TRACTION CO.

2.00	209 C	Support Plate for Oiler.....	75 H. P.—C. S.
10.00	355 C	Swing Frame I Beam, 24" Track and Outside 30" Track	75 H. P.—M. S.
12.00	355 C-1	Swing Frame I Beam, 30" Track Inside.....	75 H. P.—M. S.
3.00	192 C	Swing Frame Side Bracket (Female).....	75 H. P.—C. S.
3.00	384 C	Swing Frame Side Bracket (Female), takes place of 192 C	75 & 90 H. P.—C. S.
4.78	201 C	Swing Frame Inside Slide Standard (Male),	75 H. P.—C. S.
4.90	385 C	Swing Frame Inside Slide Standard (Male), takes place of 201 C	75 & 90 H. P.—C. S.
4.78	191 C	Swing Frame Outside Slide Standard (Male),	75 H. P.—C. S.
4.90	386 C	Swing Frame Outside Slide Standard (Male), takes place of 191 C	75 & 90 H. P.—C. S.

T

1.25	82 C	Tappett for Valve.....	75 H. P.—C. I.
1.60	23 C	Tappett Guide, Valve Cage Motor.....	75 H. P.—C. I.
1.60	263 C	Tappett Guide.....	75 H. P.—C. I.
39 12	365 C	Tank for Distillate, Galv. Steel.....	75 & 90 H. P.
16.52	365 C-1	Tank for Oil, Galv. Steel.....	75 & 90 H. P.
3.68	368 C	Tank Saddle or Frame, Wood.....	75 & 90 H. P.
.35	218 C	Thumb Screw for Differential Case.....	75 H. P.—Brass
3.86	285 C	Throttle Intake Pipe.....	75 H. P.—C. I.
6.10	153 C	Throttle Bracket for Hand Steer.....	75 H. P.—C. I.
6.10	298 C	Throttle Bracket for Power Steer.....	75 H. P.—C. I.
2.06	154 C	Throttle Lever Spark Control.....	75 & 90 H. P.—Brass
2.06	300 C	Throttle Lever Curb Control.....	75 & 90 H. P.—Brass
1.07	229 C	Toggle for Band Brake.....	75 H. P.—C. S.
	464 C	Toggle for Clutch.....	90 H. P.—C. S.
2.71	122 C	Track Link, RH, Chrome.....	75 H. P.
	122 C	Track Link, RH, Mang.....	75 H. P.
2.00	122 C	Track Link, RH, Drop Forged.....	75 H. P.
2.00	122 C-1	Track Link, RH, Sq. Hole.....	75 & 90 H. P.
2.71	123 C	Track Link, LH, Chrome.....	75 & 90 H. P.
	123 C	Track Link, LH, Mang.....	75 & 90 H. P.
2.00	123 C	Track Link, LH, Drop Forged.....	75 & 90 H. P.
1.15	141 C	Track Spool, Case Hardened.....	75 & 90 H. P.
	492 C	Track Spool	75 H. P.—C. S.
	492 C-1	Track Spool	75 H. P.—C. S.
	492 C-2	Track Spool, Steel Tubing.....	75 H. P.—C. S.
1.35	597 C	Track Shoe, 18".....	75 H. P.—M. S.
1.53	565 C	Track Shoe, 20".....	75 H. P.—M. S.
1.53	564 C	Track Shoe, 22".....	75 H. P.—M. S.
1.75	518 C	Track Shoe, 24".....	75 H. P.—M. S.
2.06	519 C	Track Shoe, 30".....	75 & 90 H. P.—M. S.
1.50	124 C	Track Pin, Half Round, Plain, both ends drilled	75 H. P.—Chronite
.78	124 C-1	Track Pin, Half Round, drilled for Cotter Pins	75 H. P.—Drop Forged
.76	124 C-2	Track Pin, Half Round, with Square Head	75 & 90 H. P.—Drop Forged
.01	562 C	Track Cotter Pin.....	75 & 90 H. P.—M. S.
21.00	140 C	Transmission Gear Case Cover.....	75 H. P.—C. I.
69.41	113 C	Transmission Gear Case.....	75 H. P.—C. S.
69.41	479 C	Transmission Gear Case, takes place 113C	75 H. P.—C. S.

C. L. BEST GAS TRACTION CO.

70.00	479	C-1	Transmission Gear Case.....	90 H. P.—C. S.
6.64	114	C	Transmission Gear Case Cap, next to Long Sleeve	75 & 90 H. P.—C. S.
4.77	115	C	Transmission Gear Case Cap, next to 36 Tooth Gear	75 & 90 H. P.—C. S.
4.88	116	C	Transmission Gear Case Cap, next to Bevel Pinion	75 H. P.—C. S.
3.36	117	C	Transmission Gear Case Cap, next to Stationary Drive Gear.....	75 & 90 H. P.—C. S.
1.25	354	C	Track Tightening Bolt or Rod used with 127 C Bracket, without Nut.....	75 H. P.
2.50	354	C-1	Track Tightening Bolt or Rod, used with 193 C and 198 C Bracket, with Nuts.....	75 H. P.
.83	354	C-2	Track Tightening Bolt or Rod, used with 295C and 296C Bracket, without nuts 75 & 90 H. P.	
16.18	186	C	Track Flange Roller.....	75 & 90 H. P.—Chilled Iron
13.10	187	C	Track Flange Roller.....	75 & 90 H. P.—Chilled Iron
5.52	125	C	Track Roller Bracket.....	75 & 90 H. P.—C. S.
6.00	126	C	Track Roller Bracket.....	75 & 90 H. P.—C. S.
6.00	172	C	Track Roller Bracket.....	75 & 90 H. P.—C. S.
2.00	60	C	Track Carrying Roller (Flanged) (top)	75 & 90 H. P.—C. I.
1.92	211	C	Track Carrying Roller (without Flange)	75 & 90 H. P.—C. I.
3.00	175	C	Track Wrench, O. S.....	75 H. P.—C. S.
2.20	33	C	Trunion Governor Brass.....	75 H. P.—Brass
1.11	521	C	Tube for Radiator, 46".....	75 & 90 H. P.—Brass Tubing
1.00	521	C-1	Tube for Radiator, 42".....	75 H. P.—Brass Tubing
25.00	278		Tube Plate for Radiator.....	75 & 90 H. P.—Brass

U

.25	374	C	Universal Ball & Socket Joint for Governor Lever	75 & 90 H. P.
-----	-----	---	--	---------------

V

3.50	324	C	Valve Intake and Exhaust.....	75 H. P.—Nickel Steel
.50	162	C	Valve Stem Washer (Solid).....	75 H. P.—C. R. S.
.25	100	C	Valve Stem Washer (Split).....	75 H. P.—C. R. S.
.82	315	C	Valve Rod	75 H. P.—T. S.
1.25	82	C	Valve Tappett	75 H. P.—C. I.
5.55	26	C	Valve Cage	75 H. P.—C. I.
1.25	84	C	Valve Cage Bushing.....	75 H. P.—C. I.
2.50	27	C	Valve Rod Clevis for Rocker Arm.....	75 H. P.—Drop Forged
1.60	23	C	Valve Tappett Guide.....	75 H. P.—C. I.
1.25	277	C	Valve Stem Bushing (Cyl. Head Motor).....	75 H. P.—C. I.

W

15.00	9	C	Water Pump Casing with Bushing.....	75 H. P.—C. I.
5.60	10	C	Water Pump Casing Cover.....	75 H. P.—C. I.
.68	11	C	Water Pump Casing Glands.....	75 H. P.—C. I.
15.00	237	C	Water Pump Casing, N. S.....	75 H. P.—C. I.
4.00	90	C	Water Pump Gears.....	75 H. P.—Mach. Steel
1.00	42	C	Water Pump Flange.....	75 H. P.—C. I.
.90	80	C	Water Pipe Flange.....	75 H. P.—C. I.
1.25	67	C	Water Strainer Casting.....	75 H. P.—C. I.

C. L. BEST GAS TRACTION CO.

.95	332 C	Water Pipe Drain Cock.....	75 H. P.—Brass
.50	100 C	Washer for Valve Stem (Split).....	75 H. P.—C. R. S.
.25	162 C	Washer for Valve Stem (Solid).....	75 H. P.—C. R. S.
1.16	525 C	Washer for Sprocket Axle.....	75 H. P.—Saw Steel
	532 C	Washer for Bevel Gear Thrust Pin.....	90 H. P.—C. R. S.
.10	527 C	Washer for Sprocket Axle.....	75 H. P.—W. I.
.16	540 C	Washer for Differential Shaft.....	75 H. P.—Saw Steel
1.50	541 C	Washer for Differential.....	75 H. P.—Ground Steel
.10	542 C	Washer for Differential.....	75 H. P.—W. I.
.10	545 C	Washer for Gudgeon Pin.....	75 & 90 H. P.—W. I.
.16	546 C	Washer for Gudgeon Pin.....	75 & 90 H. P.—Saw Steel
.06	547 C	Washer for Differential Pinion Pin.....	75 H. P.—Saw Steel
.30	576 C	Washer for Differential Roller Pin.....	75 H. P.—C. R. S.
.06	430 C	Washer for Gear Bushing, N. S., Power Steer	75 & 90 H. P.—Galv. Iron
.10	94 C	Washer for Front Idler.....	75 & 90 H. P.—W. I.
.30	247 C	Weight, Governor, Iron.....	75 & 90 H. P.—C. I.
.80	35 C	Weight, Governor, Brass.....	75 H. P.—Brass
	462 C	Wedge for Clutch.....	90 H. P.—M. S.
4.46	58-1	Wheel for Hand Steering.....	75 H. P.—C. I.
5.00	362 C	Wheel for Power Steering.....	75 & 90 H. P.
2.00	582 C	Wheel Rim only, for Power Steering.....	75 & 90 H. P.—Hard Wood
.40	350 C	Wheel Spokes (Front).....	75 & 90 H. P.—M. S.
2.00	309	Wheel Front Inside Circle Brace Castg., R. H.	75 & 90 H. P.—C. I.
2.00	310	Wheel Front Inside Circle Brace Castg., L. H.	75 & 90 H. P.—C. I.
2.75	580 C	Wheel Spider (only) for Power Steering.....	Aluminum
9.28	155 C	Worm Gear or Segment for Steering on Front Wheel Circle.....	75 H. P.—C. I.
15.55	155 C-1	Worm Gear or Segment for Steering on Front Wheel Circle, takes place of 155 C	75 H. P.—C. S.
12.39	401 C	Worm Gear or Segment for Steering on Front Wheel Circle, with Legs and inserted C. I. Center Piece.....	75 H. P.—C. S.
12.39	401 C-1	Worm Gear or Segment for Steering on Front Wheel Circle, with Legs and in- serted C. I. Center Piece, takes place of 401-C	75 & 90 H. P.—C. S.
1.00	402 C	Worm or Segment inserted Center Piece, used with 401 C.....	75 H. P.—C. I.
1.00	402 C-1	Worm or Segment inserted Center Piece, used with 401 C-1.....	75 & 90 H. P.—C. I.
2.20	156 C	Worm for Steering Wheel.....	75 & 90 H. P.—C. I.
5.00	79 C	Wrist Pin Connecting Piston to Connecting Rod	75 H. P.—Seamless Tubing

NUMERICAL LIST OF 75 and 90 H. P.

C. L. B. TRACKLAYER PARTS

Items marked *** are used on Valve Cage Motor only.

Items marked ** are used on Removable Cyl. Head Motors.

Items marked * are used on both Valve Cage and Removable Cyl. Head Motors.

\$ 75.00	***	1	C	Base, upper	75 H. P.—C. I.
86.00	***	2	C	Base, lower	75 H. P.—C. I.
55.20	***	3	C	Cylinder complete with Studs and Valve Cage	75 H. P.—C. I.
42.00	***	3	C	Cylinder only	75 H. P.—C. I.
90.60	*	4	C	Fly Wheel	75 H. P.—C. I.
19.00	*	5	C	Piston with Bushing & Rings complete	75 H. P.—C. I.
10.00	***	6	C	Water Manifold or Pipe—Top	75 H. P.—C. I.
12.00	*	7	C	Water Manifold or Pipe—Side	75 H. P.—C. I.
6.50	***	8	C	Center Water Manifold or Pipe	75 H. P.—C. I.
15.00	***	9	C	Pump Water Casing with Bushing	75 H. P.—C. I.
5.60	*	10	C	Cover for Pump Water Casing	75 H. P.—C. I.
.68	*	11	C	Gland for Pump Casing	75 H. P.—C. I.
11.00	***	12	C	Gear Casing for Water Pump, O. S.	75 H. P.—C. I.
4.50	***	13	C	Cover for Gear Case No. 12, C. O. S.	75 H. P.—C. I.
2.50	*	14	C	Back Hand Hole Plate	75 H. P.—C. I.
2.50	*	14	C-1	Hand Hole Plate	75 H. P.—C. I.
2.50	*	14	C-2	Hand Hole Plate	75 H. P.—C. I.
2.50	*	14	C-3	Hand Hole Plate	75 H. P.—C. I.
3.75	*	15	C	Front Hand Hole Plate	75 H. P.—C. I.
1.00	***	16	C	Hand Hole Plate for Cylinder	75 H. P.—C. I.
4.60	*	17	C	Housing for Oil Bevel Gear	75 H. P.—C. I.
7.25	***	18	C	Exhaust Pipe or Manifold	75 H. P.—C. I.
.90	*	19	C	Bushing for Water Pumps	75 H. P.—Plastic Bronze
10.00	***	20	C	Lower Inlet Manifold	75 H. P.—C. I.
.50	*	21	C	Pipe Clamp	75 H. P.—C. S.
.55	*	22	C	Guide Clamp for Cam Rod	75 H. P.—C. S.
1.60	*	23	C	Cam Rod Guide	75 H. P.—C. I.
25.00	*	24-1		Hub for Lead Wheel	75 H. P.—C. S.
2.50	***	24	C	Rocker Arm Bracket	75 H. P.—C. S.
4.00	*	25	C	Rocker Arm with Bushings	75 H. P.—C. S.
5.55	***	26	C	Valve Cage only	75 H. P.—C. I.
2.50	*	27	C	Valve Rod Clevis	75 H. P.—Drop Forged
3.50	***	28	C	Governor Casing	75 H. P.—Brass
2.00	***	29	C	Governor Case End	75 H. P.—Brass
2.50	***	30	C	Governor Case End	75 H. P.—Brass
2.25	*	31	C	Governor Shifter or Eccentric	75 H. P.—Brass
2.80	***	32	C	Governor Lever	75 H. P.—Brass
2.20	***	33	C	Governor Trunion	75 H. P.—Brass
1.00	***	34	C	Governor Weight	75 H. P.—Brass
.80	***	35	C	Governor Weight	75 H. P.—Brass
7.00	***	36	C	Cap, Fly Wheel End	75 H. P.—C. I.
7.00	***	37	C	Cap, Front End	75 H. P.—C. I.
5.70	***	38	C	Cap, Center Bearing Crank Case	75 H. P.—C. I.
5.00	***	39	C	Oil Pump Casing	75 H. P.—C. I.
3.00	***	40	C	Oil Pump Cover	75 H. P.—C. I.
3.50	***	41	C	Idle Stud for Cam Shaft Idler	75 H. P.—C. S.
1.00	***	42	C	Water Pump Flange	75 H. P.—C. I.

C. L. BEST GAS TRACTION CO.

2.20	***	43	C	Back Hand Hole Plate—Motor.....	75 H. P.—C. I.
20.08	*	44	C-1	Connecting Rod complete.....	75 H. P.—Drop Forged
		45	C	Cap for Connecting Rod, furnished with Rod only	Drop Forged
		46	C		
2.40	*	47	C	Oiler Shaft Bearing.....	75 H. P.—C. I.
2.20	***	48	C	Cam Shaft Bearing, Front End.....	75 H. P.—C. I.
2.00	***	49	C	Cam Shaft Bearing, Fly Wheel End.....	75 H. P.—C. I.
8.00	***	50	C	Cam Shaft Gear.....	75 H. P.—C. S.
9.00	***	51	C	Idler Shaft Gear for Cam Shaft, Bushed	75 H. P.—C. S.
8.50	***	52	C	Oiler Pump Gear.....	75 H. P.—C. S.
7.74	***	53	C	Cradle, Fly Wheel End.....	75 H. P.—C. S.
5.12	***	54	C	Cradle, Front End.....	75 H. P.—C. I.
5.76	***	55	C	Cradle, Center Bearing.....	75 H. P.—C. I.
4.70	***	56	C	Cover for Oil Well on Base.....	75 H. P.—C. I.
3.50	*	57	C	Panel Plate with Oil Inlet.....	75 H. P.—C. I.
4.00	*	58		Hand Wheel on Steering Rod, 14" Diam.	75 H. P.—C. I.
4.46	*	58-1		Hand Wheel on Steering Rod, 19" Diam.	75 H. P.—C. I.
.50	*	58	C	Cap for Oil Box.....	75 H. P.—C. I.
1.00	***	59	C	Handle for Oil Plate.....	75 H. P.—C. S.
2.00	***	60	C	Chain Carrier Roller with Flange.....	75 & 90 H. P.—C. I.
1.00	***	61	C	Bushing for Oil Pump.....	75 H. P.—Bronze
1.00	***	62	C	Bushing for Oil Pump Gear.....	75 H. P.—Bronze
.75		62		Lever Grip	75 & 90 H. P.—Brass
1.00		63	C	Hand Hole Plate for Main Sprocket Tri- angle	75 H. P.—Sheet Steel
1.00		63	C-1	Hand Hole Plate for Main Sprocket.....	75 H. P.—Sheet Steel
4.00		64	C	Belt Tightener Casting only.....	75 H. P.—C. S.
5.45		65		Box or Bearing for Steering Wheel Shaft	75 & 90 H. P.—C. I.
2.25	***	65	C	Idler Stud for Oil Pump.....	75 H. P.—C. S.
1.00	*	66	C	Piston Ring (Standard).....	75 H. P.—C. I.
1.00	*	66	C-1	Piston Ring (Oversize).....	75 H. P.—C. I.
1.25	*	67	C	Water Strainer Casting only.....	75 H. P.—C. I.
.30	***	68	C	Oil Cover for Bearing Cap.....	75 H. P.—C. I.
23.67	*	69	C	3-Arm Clutch Spider with Bushing.....	75 H. P.—C. S.
7.00	***	70	C	Clutch Shoe, O. S., without Lagging.....	75 H. P.—C. S.
10.50	***	70	C	Clutch Shoe, O. S., with Lagging.....	75 H. P.—C. S.
7.60	*	71	C	Clutch Sleeve.....	75 H. P.—C. S.
2.25	***	72	C	Governor Control Lever.....	75 H. P.—Brass
1.75	***	73	C	Bushing for Pump End Drive Gear.....	75 H. P.—Bronze
	***	74	C	Connecting Rod Cap furnished only with Rod	75 H. P.—C. S.
1.88	*	75	C	Bushing for Piston Pin.....	75 H. P.—Bronze
15.00	***	76	C	Fan Bracket Double Bearing with Caps	75 H. P.—C. S.
2.00	*	77	C	Long Cap for 76 C and 276 C Fan Bracket	75 H. P.—C. I.
.35		78		Cap for End of Steer Wheel Axle.....	75 & 90 H. P.—C. I.
2.00	*	78	C	Short Cap for 76 C and 276 C Fan Bracket	75 H. P.—C. I.
5.00	*	79	C	Wrist Pin.....	75 H. P.—Seamless Steel Tubing
.90	*	80	C	Water Manifold and Pump Flange.....	75 H. P.—C. I.
1.00		81	C	Bushing for Diff. Roller, O. S.....	75 H. P.—Bronze

C. L. BEST GAS TRACTION CO.

1.25	**	82	C	Valve Tappett.....	75 H. P.—C. I.
5.50	***	83	C	Upper Inlet Manifold.....	75 H. P.—C. I.
1.00		84		Knuckle for Steer Rod.....	75 & 90 H. P.—C. I.
1.25	***	84	C	Bushing for Valve Stem in Valve Cage.....	75 H. P.—C. I.
6.00	***	85	C	Helical Cut Gear, RH, Crank Shaft.....	75 H. P.—C. S.
5.50	***	86	C	Magneto Gear, Helical, LH.....	75 H. P.—C. S.
4.37	*	87	C	Bushing for Clutch Spider.....	75 & 90 H. P.—Bronze
.50	*	88	C	Brass Petticoat—covers Tappett Guide.....	75 H. P.—Brass
4.00	***	89	C	Helical Gear, RH, for Oil Pump.....	75 H. P.—C. S.
4.00	*	90	C	Spur Gear Water Pump.....	75 H. P.—Mach. Steel
1.60	*	91	C	Spur Gear Oil Pump.....	75 H. P.—Mach. Steel
1.80	*	92	C	Bracket for Magneto—Splitdorf.....	75 H. P.—C. S.
4.00	*	93	C	Rocker Arm with Bushing.....	75 H. P.—C. S.
.10		94	C	Washer for Front Idler.....	75 & 90 H. P.—W. I.
2.25	***	95	C	Bushing for End Gear Case Cover.....	75 H. P.—Bronze
	***	96	C	End Cover for End Bearing.....	75 H. P.
2.50	*	97	C	Babbitt Bearing for Connecting Rod, each half.....	75 H. P.
1.00		98		Cap for Power Steer Bracket No. 208C.....	75 H. P.—C. I.
3.22	*	98	C	Gear Bevel for Oiler.....	75 H. P.—Mach. Steel
3.22	*	99	C	Gear Bevel for Oiler.....	75 H. P.—Mach. Steel
.25	*	100	C	Valve Spring Washer (Split).....	75 H. P.—C. R. S.
109.50		101	C	Intr. Gear Sprocket with Bronze Bushing.....	75 H. P.—Chrome Steel
92.50		101	C	Intr. Gear Sprocket with Bronze Bushing.....	75 H. P.—40 Carbon Steel
20.12		102	C	Differential Shaft Bearing without Babbitt.....	75 H. P.—C. S.
22.00		102	C-1	Bearing for Differential Shaft without Babbitt.....	75 H. P.—C. S.
12.52		103	C	Cap for 102 C, RH, long, without Babbitt.....	75 H. P.—C. S.
14.00		103	C-1	Cap for 102 C-1, without Babbitt.....	75 H. P.—C. S.
15.20		104	C	Differential Shaft Bearing, without Babbitt.....	75 H. P.—C. S.
17.00		104	C-1	Differential Shaft Bearing, without Babbitt.....	75 H. P.—C. S.
10.44		105	C	Cap for 104 C, Short, without Babbitt.....	75 H. P.—C. S.
12.00		105	C-1	Cap for 104 C-1, without Babbitt.....	75 H. P.—C. S.
30.50		106	C	Transmission Low Gear, 36 Teeth, Cut.....	75 & 90 H. P.—Chrome Steel
25.29		107	C	Transmission Gear 2,7 Teeth, Cut.....	75 & 90 H. P.—Chrome Steel
21.05		108	C	Transmission Gear, 20 Teeth, Cut.....	75 H. P.—Chrome Steel
31.84		109	C	Transmission Sliding Gear, 27 Teeth, Cut.....	75 H. P.—Chrome Steel
41.06		110	C	Sleeve Idler Gear, 18 Teeth, Cut, with Bushing.....	75 H. P.—Chrome Steel
24.42		111	C	Bull Pinion, LH, with Bushing.....	75 H. P.—Chrome Steel
19.15		112	C	Bull Pinion, RH.....	75 H. P.—Chrome Steel
69.41		113	C	Transmission Case, lower half.....	75 H. P.—C. S.
6.64		114	C	Transmission Casing Cap, next to Long Sleeve.....	75 & 90 H. P.—C. S.

C. L. BEST GAS TRACTION CO.

4.77	115 C	Transmission Casing Cap, next to 36 Tooth Gear	75 & 90 H. P.—C. S.
4.88	116 C	Transmission Casing Cap, next to Bevel Pinion	75 H. P.—C. S.
3.36	117 C	Transmission Casing Cap, next to Stationary Drive Bevel	75 & 90 H. P.—C. S.
89.77	118 C	Differential Gear only with Bushing	75 H. P.—Chrome Steel
95.29	118 C	Differential Gear with Bushings and Pins	75 H. P.—Chrome Steel
143.71	118 C	Differential Gear all complete	75 H. P.—Chrome Steel
11.52	119 C	Bevel Pinion	75 H. P.—Chrome Steel
32.36	120 C	Differential Side Bevel Gear, LH	75 H. P.—Chrome Steel
37.82	120½ C	Differential Side Bevel Gear, RH	75 H. P.—Chrome Steel
6.36	121 C	Differential Equalizer Gear with Bronze Bushing	75 H. P.—Chrome Steel
2.71	122 C	Track Links, RH	75 H. P.—Chrome Steel
	122 C	Track Link, RH	75 H. P.—Mang. Steel
2.00	122 C	Track Link, RH	75 H. P.—Drop Forged
2.00	122 C-1	Track Link, RH, for Sq. Head Pin	75 & 90 H. P.—Drop Forged
2.71	123 C	Track Links, LH	75 & 90 H. P.—Chrome Steel
	123 C	Track Links, LH	75 & 90 H. P.—Mang. Steel
2.00	123 C	Track Links, LH	75 & 90 H. P.—Drop Forged
1.50	124 C	Track Pin drilled for Cotter Pins	75 H. P.—Chrome Steel
	124 C	Track Pin drilled for Cotter Pins	75 H. P.—Mang. Steel
.78	124 C-1	Track Pin drilled for Cotter Pins	75 H. P.—Drop Forged
.76	124 C-2	Track Pin with Sq. Head	75 & 90 H. P.—Drop Forged
5.52	125 C	Swing Frame Roller Bracket, 3 Centers, R & L	75 & 90 H. P.—C. S.
6.00	126 C	Swing Frame Roller Bracket, Right Rear and Left Front	75 & 90 H. P.—C. S.
5.00	127 C	Swing Frame Bearing	75 H. P.—C. S.
3.00	128 C	Cap for Swing Frame 127 C	75 H. P.—C. S.
9.06	129 C	Swing Frame Bearing, O. S.	75 H. P.—C. S.
9.06	129 C-1	Swing Frame Bearing, N. S.	75 & 90 H. P.—C. S.
39.15	130 C	Differential Sleeve with Bushings with Jaw Clutch	75 H. P.—C. S.
41.50	130 C-1	Differential Sleeve with Bushings with Jaw Clutch, for O. S. 30" Track only	75 H. P.—C. S.
35.50	131 C	Front Idler, O. S., used with 127 C and 128 C	75 H. P.—C. S.
1.96	132 C	Differential Shaft Collar	75 H. P.—C. S.
7.68	133 C	Differential Shaft Clutch	75 H. P.—C. S.
10.20	134 C	Swing Frame Flange Roller	75 H. P.—C. S.
8.24	135 C	Swing Frame Flange Roller	75 H. P.—C. S.
10.60	135 C-1	Swing Frame Flange Roller	75 H. P.—C. S.
5.00	136 C	Spring Support with Rod threaded with Nut	75 H. P.—C. S.
4.92	136 C-1	Spring Support with Rod—Large Stem, no Thread	75 H. P.—C. S.

C. L. BEST GAS TRACTION CO.

4.00	136 C-2	Spring Support with Rod—Small Stem.....	75 & 90 H. P.—C. S.
2.04	137 C	Spring Support	75 & 90 H. P.—C. S.
.35	138 C	Hexical Nut for Spring Support.....	75 & 90 H. P.—C. S.
1.50	139 C	Swing Frame Pull Rod Bracket.....	75 H. P.—C. S.
21.00	140 C	Gear Case Cover.....	75 H. P.—C. S.
	141 C	Track Layer Spool for Track Chain.....	75 & 90 H. P.—Mang. Steel
1.15	141 C-1	Track Layer Spool for Track Chain.....	75 & 90 H. P.—Case Hardened Steel
17.90	142 C	Flexible Coupling, 2 pcs, with Bolts.....	75 & 90 H. P.—C. S.
15.04	143 C	Bevel Gear Coupling.....	75 & 90 H. P.—C. S.
3.69	144 C	Sliding Gear Shifter or Fork.....	75 & 90 H. P.—C. S.
3.74	145 C	Shifting Lever, lower half only.....	75 & 90 H. P.—C. S.
1.00	146 C	Differential Equalizing Bushing.....	75 H. P.—Bronze
7.56	147 C	Sleeve Bushing, 6" Long, used on 130C and 403 C.....	75 & 90 H. P.—Bronze
5.25	148 C	Sleeve Bushing, 4" Long, used on 130C and 403 C.....	75 & 90 H. P.—Bronze
8.64	149 C	Differential Bushing for 118 C Gear.....	75 H. P.—Bronze
7.02	150 C	Bushing for Sleeve Gear No. 110 C and 301 C.....	75 & 90 H. P.—Bronze
9.24	151 C	Bushing for Bull Pinion No. 111 C.....	75 & 90 H. P.—Bronze
.50	152 C	Grip on Spark and Throttle Sector Handle.....	75 & 90 H. P.—Brass
6.10	153 C	Throttle Bracket Only.....	75 H. P.—C. I.
2.06	154 C	Sector Handle for Spark and Throttle.....	75 & 90 H. P.—Brass
9.28	155 C	Steering Worm Segment.....	75 H. P.—C. I.
15.55	155 C-1	Steering Worm Segment.....	75 H. P.—C. S.
2.20	156 C	Steering Worm	75 & 90 H. P.—C. I.
	157 C	Brake Drum Brackets.....	75 H. P.—C. S.
9.50	158 C	Roller in Diff. with Bushing.....	75 H. P.—C. S.
2.14	159 C	Support for Band Brake Lever.....	75 H. P.—C. S.
.60	160 C	Clamps for Band Brake.....	75 H. P.—C. S.
.70	160 C-1	Clamps for Band Brake.....	75 H. P.—C. S.
.50	*162 C	Valve Spring Washer (solid).....	75 H. P.—C. R. S.
9.46	163 C	Bevel Pinion for Rear or Stationary Drive.....	75 H. P.—Chrome Steel
.50	164	Top Clamps or Guide for Lever Grip Rod.....	75 & 90 H. P.—Brass
.50	164 C	Spacing Collar for Front Wheel.....	75 & 90 H. P.—C. I.
.30	165 C	Hexical Nut for Spring Support.....	75 H. P.—C. S.
8.40	166 C-1	Bushing for Sprocket, without Flange.....	75 H. P.—Bronze
8.56	166 C	Bushing for Sprocket, with Flange.....	75 & 90 H. P.—Bronze
18.44	167 C	Reverse Gear in Transmission, with Bronze Bushing	75 H. P.—Chrome Steel
2.42	168 C	Special Collar for Direct Drive Shaft.....	75 H. P.—C. S.
.50	169 C	Spacing Collar on Front Idler.....	75 H. P.—C. I.
40.00	*170 C	Hancock Oiler.....	75 H. P.
40.00	*170 C-1	McCord Oiler.....	75 H. P.
1.28	171 C	Supporting Plate for Oiler.....	75 H. P.—W. I.

C. L. BEST GAS TRACTION CO.

6.00	172 C	Swing Frame Bracket, Right Front and Left Rear	75 & 90 H. P.—C. S.
22.00	173 C	Splitdorf Coil.....	75 H. P.
5.52	174 C	Stationary Drive Bracket.....	75 H. P.—C. S.
3.00	175 C	Wrench for Tightening Chain, O. S.....	75 H. P.—C. S.
1.00	176 C	Lever for Brake (casting only).....	75 H. P.—C. S.
1.81	176 C-1	Lever for Brake, with Wrought Part Welded.....	75 H. P.
2.21	176 C-2	Lever for Brake, with Wrought Part Welded.....	75 H. P.
1.20	*177 C	Relief Cock	75 H. P.
70.00	178 C	Splitdorf Magneto.....	75 H. P.
2.66	179 C	Bushing for Reverse Gear Idler 167 C.....	75 & 90 H. P.—Bronze
1.00	*180 C	Friction Spring Pull Block.....	75 H. P.—C. S.
.60	*181 C	Bushing for Rocker Arm, Short.....	75 H. P.—Bronze
2.50	***182 C	Plate	
2.50	***183 C	Plate	
.90	***184 C	End Oil Pipe Bearings.....	75 H. P.—C. I.
.90	***185 C	End Oil Pipe Bearings.....	75 H. P.—C. I.
16.18	186 C	Double Flange Roller, Outside Flange.....	75 & 90 H. P.—Chilled Iron
13.10	187 C	Double Flange Roller, Inside Flange.....	75 & 90 H. P.—Chilled Iron
	188 C	R. & L. Hand Filler Plate.....	75 H. P.—C. S.
	189 C	Double Flange Roller.....	75 H. P.—C. S.
2.92	190 C	Bushing (2 pieces) for Track Rollers 186 C and 187 C	75 & 90 H. P.—C. I.
4.78	191 C	Bracket for Holding Swing Frame.....	75 H. P.—C. S.
3.00	192 C	Filler Bracket for 191 C.....	75 H. P.—C. S.
3.35	193 C	RH Clamp Box Front Idler.....	75 H. P.—C. S.
43.64	194 C	Front Idler used with 198 C and 193 C.....	75 H. P.—C. S.
	195 C	Double Steel Rollers—same as 186 C.....	75 H. P.—Mang. Steel
6.84	196 C	Bracket for Chain Carriers Roller Front	75 & 90 H. P.—C. S.
4.78	197 C	Male Slide, LH.....	75 & 90 H. P.—C. S.
3.35	198 C	LH Front Idler Box.....	75 H. P.—C. S.
	199 C	Manganese Inside Roller, same as 187 C.....	75 H. P.—Mang. Steel
.50	200 C	Reverse Gear Idler Pin Collar.....	75 H. P.—C. S.
4.78	201 C	Inside Bracket, Male.....	75 H. P.—C. S.
10.00	202 C	Governor Casing.....	75 H. P.—Brass
4.00	203 C	Governor Casing End.....	75 H. P.—Brass
4.00	204 C	Governor Casing End.....	75 H. P.—Brass
.50	205	Radiator Plug.....	75 & 90 H. P.—C. I.
4.78	205 C	Male Slide, RH.....	75 & 90 H. P.—C. S.
7.72	206 C	Dust Guard Cap, LH, Drive Socket.....	75 H. P.—Sheet Steel
7.72	207 C	Dust Guard Cap, RH, Drive Sprocket.....	75 H. P.—Sheet Steel
12.16	208 C	Power Steer Bracket, RH, Babbitt.....	75 H. P.—C. S.
2.00	209 C	Bracket for Lubricator.....	75 H. P.—C. S.
3.20	*210 C	Fan Shaft only.....	75 H. P.—C. R. S.
3.36	211	Double Clutch for Power Steer.....	75 H. P.—C. S.
1.92	211 C	Track Roller without Flange Top Idler.....	75 & 90 H. P.—C. S.
6.64	212	Bevel Gear with Clutch for Power Steer	75 H. P.—C. S.

C. L. BEST GAS TRACTION CO.

4.98	212 C	Bushing (2 pcs) for Front Idler.....	75 & 90 H. P.—C. I.
.90	213 C	Spacing Collar, 3".....	75 H. P.—C. I.
5.49	214	Bevel Gear without Clutch, for Power Steer.....	75 H. P.—C. S.
1.08	214 C	Spacing Collar, 4".....	75 H. P.—C. S.
1.00	215 C	Double Knuckle Joint (Oiler).....	75 H. P.—Brass
.50	216 C	End Knuckle Joint (Oiler).....	75 H. P.—Brass
43.64	217 C	Five Spoke Idler, takes place of 194 C, used with 193 C, 195 C, 275, 296.....	75 H. P.—C. S.
.35	218 C	Thumb Screw for Differential.....	75 H. P.—Brass
	219 C		
	220 C	Front End Bearing Cover.....	75 H. P.—C. I.
1.60	221 C	Bushing, 2 pcs., for Rollers 195 C and 199 C	75 H. P.—C. S.
4.50	222 C	Boss for Gear Case Truss Roller.....	75 H. P.—C. S.
3.00	223 C	Bushing for Cam Shaft Idler Gear.....	75 H. P.—Bronze
6.72	223	Shifter Ring.....	75 & 90 H. P.—Bronze
86.34	**224 C	Lower Crank Case.....	75 H. P.—C. I.
16.20	**225 C	Cam Shaft Gear, 88 Teeth, Cut.....	75 H. P.—Chrome Steel
8.27	**226 C	Magneto Shaft Drive Gear, 54 Teeth, Cut	75 H. P.—Chrome Steel
6.70	**227 C	Magneto Shaft Drive Gear, 27 Teeth, Cut	75 H. P.—Chrome Steel
8.62	**228 C	Crank Shaft Gear, 44 Teeth, Cut.....	75 H. P.—Chrome Steel
1.07	229 C	Toggle for Band Brake.....	75 H. P.—C. S.
10.00	230 C	Revolving Drum, to Carry Track.....	75 H. P.—C. S.
7.50	231 C	Swing Frame Roller Bearing Bracket, RH	75 H. P.—C. S.
.60	232	Lower Clamp or Guide for Lower Grip Rod.....	75 & 90 H. P.—Brass
2.50	232 C	Bell Crank for Brake Bands.....	75 H. P.—C. S.
.65	233 C	Long Bushing for Rocker Arm.....	75 H. P.—Brass
85.44	**234 C	Upper Crank Case.....	75 H. P.—C. I.
7.00	235 C	Swing Frame Roller Bearing Bracket, LH	75 H. P.—C. S.
.60	236 C	Flange for Oil Overflow.....	75 H. P.—Brass
15.00	**237 C	Water Pump Body.....	75 H. P.—C. I.
7.00	238 C	Ball Race Swing Frame Bracket.....	75 H. P.—C. S.
3.00	*238	Inlet Spout Top of Radiator.....	75 & 90 H. P.—C. I.
6.00	239 C	Ball Race Revolving Drum.....	75 H. P.—C. I.
2.20	*240 C	Lug for fastening Insp. Plate with Stud.....	75 H. P.—C. S.
5.70	**241 C	Lower Half for Oil Pump.....	75 H. P.—C. I.
4.60	**242 C	Upper Half for Oil Pump.....	75 H. P.—C. I.
1.40	*243 C	Exhaust Cam.....	75 H. P.—Chilled Iron
1.40	*244 C	Inlet Cam.....	75 H. P.—Chilled Iron
3.28	**245 C	End Plate for Governor.....	75 & 90 H. P.—C. I.
3.75	246-1	Sprocket for Power Steer on Crank Shaft, 2¾" Bore, 13 Teeth.....	75 H. P.—Chrome Steel
3.75	246-2	Sprocket for Power Steer on Crank Shaft, 3¼" Bore, 13 Teeth.....	75 & 90 H. P.—Chrome Steel
5.20	**246 C	Housing for Governor.....	75 H. P.—C. I.
.30	**247 C	Governor Ball.....	75 H. P.—C. I.
.50	**248 C	Collar for Governor.....	75 H. P.—C. I.
6.40	**249 C	Inlet Pipe.....	75 H. P.—C. I.
5.70	**250 C	Exhaust Pipe or Manifold.....	75 H. P.—C. I.

C. L. BEST GAS TRACTION CO.

4.25	250 C-1	Exhaust Pipe or Manifold with Flange, Special	75 H. P.—C. I.
5.40	251 C	Cradle for Center Crank Shaft Bearing.....	75 H. P.—C. I.
5.86	**252 C	Cradle for Center Crank Shaft Bearing.....	75 H. P.—C. I.
6.20	**253 C	Cradle for Short Crank Shaft Front Bear- ing End	75 H. P.—C. I.
7.55	**254 C	Cradle for Long Crank Shaft Fly Wheel Bearing End	75 H. P.—C. I.
5.20	**255 C	Cap for Center Bearing in Crank Case.....	75 H. P.—C. I.
5.20	**256 C	Cap for Short Bearing in Crank Case, Front End.....	75 H. P.—C. I.
7.00	**257 C	Cap for Long Bearing in Crank, Fly Wheel End	75 H. P.—C. I.
6.64	**258 C	End Gear Case Cover.....	75 H. P.—C. I.
2.06	**259 C	Oil Pump Drive Bearing.....	75 H. P.—C. I.
1.50	**260 C	Water Pump and Magneto Coupling.....	75 H. P.—C. I.
1.80	*261 C	Magneto Bracket, Bosch and K. W.....	75 H. P.—C. I.
3.00	**262 C	Center Water Pipe.....	75 H. P.—C. I.
1.60	**263 C	Tappet Guide.....	75 H. P.—C. I.
16.00	**264 C	Cylinder Head only.....	75 H. P.—C. I.
101.32	**265 C	Internal Gear and Sprocket with Bronze Bushings (used with 30" Track only)	75 & 90 H. P.—40 Carbon Steel
119.70	265 C	Internal Gear and Sprocket with Bronze Bushing (used with 30" Track only)	75 & 90 H. P.—Chrome Steel
.76	*265	Spark Arrester Casting.....	75 & 90 H. P.—C. I.
2.60	**266 C	End Cover for Crank Chamber, Fly Wheel End	75 H. P.—C. I.
.32	*266	Spark Arrester Ring.....	75 & 90 H. P.—C. I.
2.50	**267 C	Rocker Arm Bracket.....	75 & 90 H. P.—C. I.
1.80	268 C	Side Top Water Pipe.....	75 H. P.—C. I.
1.60	**269 C	Bearing for Cam Shaft, Center.....	75 H. P.—C. I.
1.60	**270 C	Bearing for Cam Shaft, Fly Wheel End.....	75 H. P.—C. I.
2.50	**271 C	Bearing for Magneto Drive Shaft.....	75 H. P.—C. I.
.50	**272 C	Oil Pan	75 H. P.—Sheet Steel
.80	*273 C	Priming Cock	75 H. P.—Brass
25.00	**274 C	Cylinder with Studs.....	75 H. P.—C. I.
.35	*275 C	Hand Wheel for Insp. Plate.....	75 H. P.—C. I.
12.00	**276 C	Fan Bracket and Caps only.....	75 H. P.—C. S.
1.25	**277 C	Valve Stem Bushing.....	75 H. P.—C. I.
25.00	278	Radiator Tube Plate.....	75 & 90 H. P.—Brass
2.00	*278 C	Magneto Coupling, 3 pcs., Bosch and Split- dorf	75 H. P.—C. R. S.
5.58	279 C	Rear Chain Carrying Roller Bracket.....	75 & 90 H. P.—C. S.
.60	280 C	Pawl for Gear Shifter Lever.....	75 & 90 H. P.—C. S.
5.50	281	Radiator Side Plate.....	75 & 90 H. P.—C. I.
.55	281 C	Support for Magneto Wire Pipe on Bosch Magneto	75 H. P.—C. S.
1.60	**282 C	Cam Shaft Drive End Bearing.....	75 H. P.—C. S.
7.00	283 C	Clutch Shifter for Main Clutch.....	75 H. P.—C. S.
2.80	**284 C	Governor Shifting Lever.....	75 H. P.—Brass
3.86	**285 C	Shrot Throttle Intake Pipe complete.....	75 H. P.—C. I.
.25	**286 C	Butterfly Control Lever.....	75 H. P.—Brass
	287 C	Flangeless Center Swing Frame Roller.....	75 H. P.—C. I.
4.25	**288 C	Spiral Gear on Cam Shaft.....	75 H. P.—C. S.

C. L. BEST GAS TRACTION CO.

4.25	**289	C	Oil Pump Spiral Gear.....	75 H. P.—C. S.
8.76	***290-1		Fan Pulley, 16" Diam., 2¾" Bore.....	75 H. P.—C. I.
8.76	**290-2		Fan Pulley, 16" Diam., 3¼" Bore.....	75 H. P.—C. I.
.25	**290	C	Cover for End Bearing Caps Oil Bracket.....	75 H. P.—C. I.
	291	C		
6.78	*292	C	Clutch Shoe, N. S., without Lining.....	75 H. P.—C. S.
10.28	292	C	Clutch Shoe, N. S., with Lining.....	75 H. P.—C. S.
.74	293	C	Magneto Support for Splitdorf.....	75 H. P.—C. S.
15.21	294	C	Differential Thrust Roller & Band only.....	75 H. P.—C. S.
4.75	294	C-1	Differential Thrust Roller Band only.....	75 H. P.—C. S.
3.25	295	C	Clamp Box for Front Idler, L.H.....	75 & 90 H. P.—C. S.
3.25	296	C	Clamp Box for Front Idler, R.H.....	75 & 90 H. P.—C. S.
2.80	*297		Fan Spider only.....	75 H. P.—C. S.
.26	297	C	Link Coupling Roller Chain.....	75 & 90 H. P.—M. S.
12.50	298		Radiator Top with Spout.....	75 & 90 H. P.—C. I.
6.10	298	C	Throttle Bracket for Power Steer.....	75 H. P.—C. I.
10.25	299		Radiator Bottom.....	75 & 90 H. P.—C. I.
34.42	299	C	Transmission Sliding Clutch Gear, takes place of 109 C.....	75 H. P.—Chrome Steel
2.06	300	C	Sector Handle.....	75 & 90 H. P.—Brass
47.34	301	C	Sleeve Idler Gear, takes place of 110 C.....	75 & 90 H. P.—Chrome Steel
.50	**302	C	Cap for Oil Pocket Plate on 114 C.....	75 H. P.—C. I.
.50	**303	C	Cap for Oil Pocket Plates 103 C and 105 C.....	75 & 90 H. P.—C. I.
4.16	304	C	Chain Tightener Bracket on 8-inch Beam.....	75 & 90 H. P.—C. S.
27.46	305	C	Bevel Gear for Stationary Drive, Special, 15 Teeth.....	75 H. P.—Cut Steel
13.04	306	C	Split Coupling for Stationary Drive, Special.....	75 H. P.—C. S.
18.70	307	C	Bevel Pinion for Stationary Drive, Special, 10 Teeth.....	75 H. P.—Cut Steel
3.00	**308		Belt Tightener Pulley, O. S.....	75 H. P.—C. I.
.46	308	C	Strainer for Oil Pumps.....	75 H. P.
2.00	309		Bracket Inside Steer Wheel Circle.....	75 & 90 H. P.—C. I.
2.14	309	C	Safety Lug for Power Steer.....	75 H. P.—C. S.
2.00	310		Bracket Inside Steer Wheel Circle.....	75 & 90 H. P.—C. I.
	310	C	Sprocket (Special).....	75 H. P.—C. S.
	311	C	Sprocket (Special).....	75 H. P.—C. S.
.70	*312	C	Rocker Arm Stand Pin.....	75 H. P.—C. R. S.
3.00	313	C	Sleeve Bushing for Governor, O. S.....	75 H. P.—C. R. S.
3.39	313	C-1	Sleeve Bushing for Governor, N. S.....	75 H. P.—C. R. S.
2.00	314	C	Ball Bearing End Truss Collar, Fan.....	75 H. P.
.82	315	C	Push Rod for Valves.....	75 H. P.—T. S.
.50	316	C	Water Pump Idler Gear Shaft.....	75 H. P.—C. R. S.
	317	C		
4.30	318	C	Conduit Pipe with Wiring.....	75 H. P.
1.48	318	C-1	Conduit Pipe only.....	75 H. P.
.75	319	C	Cylinder Gasket.....	75 H. P.—Coppered Asbestos
.07	320	C	Water Pipe Gasket.....	75 H. P.—Garlocks
.40	321	C	Inlet Exhaust Manifold Gasket.....	75 H. P.—Coppered Asbestos
.12	322	C	Governor Ball Pin.....	75 H. P.—C. R. S.
.25	323	C	Butterfly Control Pin.....	75 H. P.—C. R. S.
3.50	324	C	Valve Intake or Exhaust.....	75 H. P.—Nickel Steel

C. L. BEST GAS TRACTION CO.

.46	325 C	Valve Spring for Cylinder Head Motor.....	75 H. P.
.46	325 C-1	Valve Spring for Valve Cage Motor.....	75 H. P.
7.20	326 C	Clutch Shifter for Main Clutch, takes place of 283 C	75 & 90 H. P.—C. S.
1.00	327 C	Governor Control Extension Rod.....	75 H. P.—C. R. S.
2.50	328 C	Water Pumps Drive Shaft, Long Section	75 H. P.—C. R. S.
3.00	329 C	Water Pumps and Magneto Shaft.....	75 H. P.—C. R. S.
.66	330 C	Oil Pump Drive Shaft Short Section	75 H. P.—C. R. S.
.64	331 C	Oil Pump Drive Shaft Short Section	75 H. P.—C. R. S.
.95	332 C	Water Pipe Drain Cock, $\frac{3}{8}$ "	75 H. P.—Brass
7.60	333 C	Cam Shaft only.....	75 H. P.—C. R. S.
112.56	334 C	Crank Shaft.....	75 H. P.—Drop Forged
.32	335 C	Governor Spring.....	75 H. P.—Spring Steel
.50	336 C	Rocker Arm Clevis Pin.....	75 H. P.—C. R. S.
1.50	337	Swing for Worm.....	75 & 90 H. P.—C. I.
.86	337 C	Oil Pump Drive Shaft Long Section.....	75 H. P.—C. R. S.
.50	338	End Bracket for 337 Front.....	75 & 90 H. P.—C. I.
2.50	338 C	4" O. D. Exhaust Pipe, 42" long.....	75 & 90 H. P.
.50	339	End Bracket for 337 Rear.....	75 & 90 H. P.
.50	339 C	Exhaust Screen only, each.....	75 & 90 H. P.
.12	340 C	Canopy Angle Post Brace.....	75 & 90 H. P.—Mild Steel
80.28	341 C	Canopy Top Complete.....	75 & 90 H. P.
1.32	342 C	Canopy Upright or Post (Front).....	75 & 90 H. P.—Mild Steel
.90	342 C-1	Canopy Upright or Post (Rear).....	75 & 90 H. P.—Mild Steel
.25	343 C	Hose Clamp top of Radiator.....	75 & 90 H. P.
1.10	344 C	Top Radiator Hose without Clamp.....	75 & 90 H. P.
.40	345 C	Overflow Pipe	75 & 90 H. P.—B. P.
5.06	346 C	Radiator Hood or Fan Shield.....	75 & 90 H. P.
14.30	347 C	Fan Drive Belt, 4½" wide, 6' 2½" long	75 & 90 H. P.
13.60	347 C-1	Fan Drive Belt, 4" wide, 6' 2½" long.....	75 H. P.
4.06	348 C	Hood over Front Wheel.....	75 & 90 H. P.
1.00	349 C	Worm Spring, Long.....	75 & 90 H. P.—Spring Steel
.40	349 C-1	Worm Spring, Short.....	75 & 90 H. P.—Spring Steel
.40	350 C	Front Wheel Spokes with Nuts.....	75 & 90 H. P.—M. S.
50.72	351 C	Main Side Bar 10" Channel.....	75 H. P.—S. S.
	351 C-1	Main Side Bar 10" Channel.....	90 H. P.—S. S.
1.60	352 C	Bottom Radiator Hose without Clamps	75 & 90 H. P.—Rubber
4.81	353 C	Front Idler Shaft, 27¼"x22"	75 & 90 H. P.—40 Carbon C. R. S.
1.26	354 C	Front Idler Pull Rod or Track Adjuster, without Nut	75 H. P.
2.50	354 C-1	Front Idler Pull Rod or Track Adjuster, without Nut	75 H. P.
.92	354 C-2	Front Idler Pull Rod or Track Adjuster, without Nut	75 & 90 H. P.
1.60	354 C-2	Front Idler Pull Rod or Track Adujster, with Nut	75 & 90 H. P.
10.00	355 C	Swing Frame I Beam, Inside or Outside 24" Track	75 H. P.—M. S.
12.00	355 C-1	Swing Frame I Beam, Inside, 30" Track	75 H. P.—M. S.
5.96	356 C	Steering Rod only.....	75 H. P.—C. R. S.

C. L. BEST GAS TRACTION CO.

4.66	356 C-1	Steering Rod for Power Steer	75 & 90 H. P.—C. R. S.
.54	357 C	Magneto Wire Control Pipe.....	75 H. P.
.64	358 C	Governor Control Rod, 1/8" Pipe.....	75 H. P.
	359 C	Flexible Conduit Pipe, 1".	Write for prices.
3.38	360 C	Clutch Hand Lever.....	75 & 90 H. P.—M. S.
8.42	361 C	Gear Shift Hand Lever, Wrought Part only, complete.....	75 & 90 H. P.—M. S.
5.00	362 C	Wood Hand Wheel with Aluminum Spider	75 & 90 H. P.
.17	363 C	Gear Shift Notch Rod.....	75 & 90 H. P.—C. R. S.
1.25	364 C	Seat.....	75 H. P.—Pressed Steel
39.12	365 C	Distillate Tank.....	75 & 90 H. P.—Galv. Steel
16.52	365 C-1	Oil Tank.....	75 & 90 H. P.—Galv. Steel
2.44	366 C	Gear Shift Sector.....	75 & 90 H. P.—M. S.
2.00	367 C	Seat Spring, Long Section.....	75 & 90 H. P.—M. S.
.48	367 C-1	Seat Spring, Short Section.....	75 & 90 H. P.—M. S.
3.68	368 C	Tank Support Frame, Wood.....	75 & 90 H. P.—Wood
25.42	369 C	Floor Plate over Tracks.....	75 H. P.—M. S.
	369 C-1	Floor Plate over Tracks.....	90 H. P.—M. S.
4.00	370 C	Floor Side Rails.....	75 & 90 H. P.—M. S.
22.68	371 C	Back 4" Axle, 22" and 24" Track.....	75 H. P.—Case Hardened C. R. S.
26.04	371 C-1	Back 4" Axle, 30" Track.....	75 & 90 H. P.—C. R. S.
1.14	372 C	Axle Hanger Straps, Outside.....	75 & 90 H. P.—M. S.
1.14	372 C-1	Axle Hanger Straps, Inside.....	75 & 90 H. P.—M. S.
3.00	373 C	Track Roller Gudgeon Pin.....	75 & 90 H. P.—C. R. S.
5.00	373	Fan Pulley.....	75 & 90 H. P.—C. I.
.25	*374 C	Ball and Socket Joint.....	75 & 90 H. P.
.15	375 C	2 1/4" Iron Ball in Front Wheel Circle.....	75 & 90 H. P.—C. I.
6.70	376 C	Fellow for Front Wheel, 7/8"x2 1/2".....	75 H. P.—M. S.
	376	Fork for Oil Stud Fan Belt Tightener.....	75 H. P.—C. S.
8.14	376 C-1	Fellow for Front Wheel, 1"x3".....	75 H. P.—M. S.
9.38	376 C-2	Fellow for Front Wheel, 1"x3 1/2".....	75 H. P.—M. S.
	377	Bracket for Old Style Fan Belt Tightener.....	C. S.
2.07	377 C	Exhaust Pipe Canopy Flange.....	75 & 90 H. P.—C. S.
1.05	378 C	Base Bracket for Headlight Support.....	75 H. P.—C. I.
	379 C		
.75	380 C	Coupling Spring.....	75 & 90 H. P.
	381 C		
1.20	382 C	Pulley for Lighting Dynamo, 1 1/2"x3 3/4" Diam.	75 H. P.—C. I.
.90	383 C	Bushing for Oil Pump, Drive End.....	75 H. P.—Bronze
3.00	384 C	Female Swing Frame Slide Bracket.....	75 & 90 H. P.—C. S.
4.90	385 C	Inside Male Bracket for Swing Frame.....	75 & 90 H. P.—C. S.
4.90	386 C	Outside Male Bracket for Swing Frame.....	75 & 90 H. P.—C. S.
1.36	387 C	Fisher Lighting Dynamo Pulley, 1 1/8"x5 1/4" Diam.	75 H. P.—C. I.
7.51	388 C	Bevel Pinion for Diff. Equalizer, with Bronze Bushing, N. S.	75 H. P.—Chrome
2.50	389 C	Truck Axle Hanger Bracket.....	75 & 90 H. P.—C. S.
.25	390 C	Knuckle Joint Center Block Oiler Drive	75 H. P.—C. R. S.
2.72	391 C	Headlight Support Fork.....	75 H. P.—Bronze

C. L. BEST GAS TRACTION CO.

.36	392 C	Collar only for Chain Carrier Roller Shaft	75 & 90 H. P.—C. I.
.46	392 C	Colar only for Chain Carrier Roller Shaft, with Set Screws and Nuts.....	75 H. P.—C. I.
18.90	393 C	Drive Bull Pinion, LH.....	75 H. P.—Chrome
.30	393	Knuckle Block for Steer Knuckle.....	75 & 90 H. P.—C. I.
43.01	394 C	Differential Sleeve with Bronze Bushing.....	75 H. P.—C. S.
1.00	395 C	Special Exhaust Flange.....	75 H. P.—C. I.
.52	396 C	Oil Cups for Axle Shaft (diff.).....	75 & 90 H. P.—C. I.
.20	397 C	Oil Cups Cover for 396 C.....	75 & 90 H. P.—C. I.
2.50	398 C	Short Intake Pipe, Special, for 2½" L. Schebler Carburetor.....	C. I.
34.22	399 C	Differential Side Gear, LH.....	75 H. P.—C. S.
35.10	400 C	Differential Side Gear, RH.....	75 H. P.—C. S.
12.39	401 C	Worm Steering Segment (only).....	75 H. P.—C. S.
12.39	401 C-1	Worm Steering Segment (only).....	75 & 90 H. P.—C. S.
	401 C-1	Worm Steering Segment all complete, less Brackets	
	401 C-1	Worm Steering Segment all complete, with Brackets	
14.65	401 C	Worm Steering Segment all complete, less Brackets.....	75 H. P.—C. S.
16.31	401 C	Worm Steering Segment all complete, with Brackets.....	75 H. P.—C. S.
1.00	402 C	Filler Segment for 401-C.....	75 H. P.—C. I.
1.00	402 C-1	Filler Segment for 401 C-1.....	75 & 90 H. P.—C. I.
45.71	403 C	Differential Sleeve with Bronze Bushing.....	75 & 90 H. P.—C. S.
	403 C-1	Differential Sleeve.....	90 H. P.—C. S.
10.32	404 C	Gear Clutch.....	75 H. P.—C. S.
11.55	405 C	Power Steer Bevel Gear Idler.....	75 & 90 H. P.—Chrome
13.86	406 C	Power Steer Bevel Gear Long Hub with Bronze Bushing.....	75 & 90 H. P.—Chrome
13.57	407 C	Power Steer Bevel Gear, Front Wheel End, with Bronze Bushing.....	75 & 90 H. P.—Chrome
5.82	408 C	Power Steer Case only (upper half).....	75 & 90 H. P.—C. I.
6.12	409 C	Power Steer Case only (lower half).....	75 & 90 H. P.—C. I.
.50	409	Spring Button.....	75 & 90 H. P.—C. I.
5.28	410 C	Power Steer Sprocket.....	75 & 90 H. P.—Chrome
6.28	410	Pulley (Fisher & Aplco Dynamo).....	75 H. P.—Aluminum
1.35	411 C	Power Steer Clutch Shifter, new style.....	75 & 90 H. P.—C. S.
3.11	412 C	Power Steer Bushing for Case.....	75 & 90 H. P.—Bronze
.72	413 C	Power Steer Bushing for Bevel Gears.....	75 & 90 H. P.—Bronze
9.30	413	Combined Sprocket and Bevel Gears.....	75 H. P.—Chrome
22.06	414 C	Sleeve Bull Pinion, N. S., LH, 5¾" Bore.....	75 & 90 H. P.—Chrome
1.66	414	Bronze Bushing for 212 and 415.....	75 H. P.—Bronze
19.42	415 C	Bull Pinion, N. S., RH, 4" Bore.....	75 H. P.—Chrome
4.00	415	Clutch Shifter for Power Steer, Old Style.....	75 H. P.—C. S.
4.50	416	Guide for Safety Rod, Old Style.....	75 H. P.—C. S.
.94	416 C	Control Wire Bracket.....	75 & 90 H. P.—C. S.

C. L. BEST GAS TRACTION CO.

3.70	417 C	Seat	75 & 90 H. P.—C. I.
2.00	418 C	Air Intake Pipe Strainer Casting, Special, for Harvester Motor.....	Brass
8.00	419 C	6" High Double Coil Main Spring.....	75 & 90 H. P.
2.52	420 C	Clutch Dog for Power Steer.....	75 & 90 H. P.—C. R. S.
1.01	421 C	Clutch Shifting Shaft for Power Steer.....	75 & 90 H. P.—C. R. S.
1.24	422 C	Clutch Shifting Lever for Power Steer.....	75 & 90 H. P.—M. S.
.09	423 C	Clutch Shifting Lever Stud for Power Steer, $\frac{5}{8}$ "x2".....	75 & 90 H. P.—C. R. S.
.10	424 C	Shifting Lever Stud Nut for Power Steer.....	75 & 90 H. P.
2.01	425 C	Power Steer Shaft for Power Steer.....	75 & 90 H. P.—C. R. S.
.08	426 C	Clutch Shifting Lever Pin for Power Steer	75 & 90 H. P.—Rivet Steel
.18	427 C	Gear Box Cover for Power Steer.....	75 & 90 H. P.—Galvd. Iron
1.58	428 C	Gear Box Bracket for Power Steer.....	75 & 90 H. P.—M. S.
.52	429 C	Connecting Shaft Power Steer to Worm	75 & 90 H. P.—C. R. S.
.06	430 C	Gear Bushing Washer for Power Steer....	75 & 90 H. P.—Galv. Iron
2.00	431 C	Gear Clutch Attachment.....	75 H. P.—C. R. S.
9.38	432 C	Bevel Gear Long Hub, Power Steer.....	75 H. P.—C. I.
9.28	433 C	Bevel Gear Short Hub, Power Steer.....	75 H. P.—C. I.
9.08	434 C	Bevel Gear Idler, Power Steer.....	75 H. P.—C. I.
	435 C	Insert Piece for Track Spool.....	75 H. P.—Tool Steel
1.74	436 C	Coupling for Oilier, 3 pcs.....	75 H. P.—C. R. S.
1.25	437 C	Coupling for K. W. Magneto, 2 pcs.....	75 H. P.—C. R. S.
.16	438 C	Sector Trigger Spring.....	75 & 90 H. P.—Spring Steel
.21	439 C	Crank Case Stud, 1"x3 $\frac{1}{2}$ ".....	75 H. P.—C. R. S.
.11	440 C	Short Crank Case Door Stud, $\frac{5}{8}$ "x4 $\frac{5}{8}$ "	75 H. P.—T. B. S.
.14	441 C	Long Crank Case Door Stud, $\frac{5}{8}$ "x6".....	75 H. P.—T. B. S.
.09	442 C	Crank Case Door Guide Stud, $\frac{1}{2}$ "x2 $\frac{3}{8}$ ".....	75 H. P.—C. R. S.
.07	443 C	Water Pump Stud, 5/16"x2".....	75 H. P.—C. R. S.
.07	444 C	Top Water Pipe Stud, $\frac{1}{2}$ "x4 $\frac{1}{4}$ ".....	75 H. P.—T. B. S.
.11	445 C	Side Water Pipe Stud, $\frac{1}{2}$ "x3 $\frac{1}{8}$ ".....	75 H. P.—T. B. S.
.15	446 C	Tappett Guide Stud, $\frac{3}{4}$ "x3 $\frac{7}{8}$ ".....	75 H. P.—T. B. S.
.20	447 C	Short Cylinder Head Stud, $\frac{3}{4}$ "x7 $\frac{1}{8}$ ".....	75 H. P.—T. B. S.
.24	448 C	Long Cylinder Head Stud and Manifold Clamp, $\frac{3}{4}$ "x7 $\frac{3}{4}$ ".....	75 H. P.—T. B. S.
.08	449 C	Governor Control Lever Stud, $\frac{1}{2}$ "x5 $\frac{1}{4}$ "	75 H. P.—C. R. S.
.07	450 C	Rocker Arm Stand Stud, $\frac{1}{2}$ "x1 $\frac{3}{4}$ ".....	75 H. P.—T. B. S.
.31	451 C	Transmission Case Cover Stud, $\frac{5}{8}$ "x2 $\frac{3}{8}$ "	75 & 90 H. P.—C. R. S.
.05	452 C	Governor Block Stud, $\frac{3}{8}$ "x1".....	75 H. P.—C. R. S.
.39	453 C	Lamp Bracket Stud, $\frac{1}{2}$ "x4 1/16".....	75 H. P.—C. R. S.
.15	454 C	Valve Case Stud, $\frac{3}{4}$ "x2 $\frac{7}{8}$ ".....	75 H. P.—T. B. S.
	455 C		
.80	456 C	Dust Collar for Crank Shaft.....	75 H. P.—Brass
	457 C	Gear Bevel Ring.....	90 H. P.—C. S.

C. L. BEST GAS TRACTION CO.

	458 C	Drum Clutch.....	90 H. P.—C. S.
	459 C	Spider, 2-Arm Clutch.....	90 H. P.—C. I.
	460 C	Collar Clutch Shifter.....	90 H. P.—Bronze
	461 C	Collar Sliding Clutch.....	90 H. P.—C. S.
	462 C	Wedge for Clutch.....	90 H. P.—M. S.
	463 C	Bolt Eye for Side Clutch.....	90 H. P.—M. S.
	464 C	Toggle for Clutch.....	90 H. P.—C. S.
	465 C	Band for Clutch.....	90 H. P.—C. I.
	466 C	Pinion Bevel.....	90 H. P.—C. S.
	467 C	Pin Sliding Clutch Collar.....	90 H. P.—M. S.
	468 C	Pin Clutch Wedge.....	90 H. P.—M. S.
.86	469 C	Plate Power Steer Hand Shifter Lever Guide.....	75 & 90 H. P.—W. I.
.10	470 C	Clip for Power Steer Guide Plate.....	75 & 90 H. P.—W. I.
3.18	471 C	Lever Power Steer Hand Shifter.....	75 & 90 H. P.—W. I.
	472 C	Piston.....	90 H. P.
	473 C	Cylinder.....	90 H. P.—C. I.
	474 C	Sheave Cable take up, Special.....	90 H. P.—C. S.
	475 C	Collar Sheave Pin.....	90 H. P.—C. S.
	476 C	Pin for Sheave.....	90 H. P.—M. S.
	477 C	Bottom Spring Support.....	90 H. P.—C. S.
	478 C	Top Spring Support.....	90 H. P.—C. S.
69.41	479 C	Transmission Case, lower half.....	75 H. P.—C. S.
70.00	479 C-1	Transmission Case, lower half.....	90 H. P.—C. S.
3.12	480 C	Shaft Reverse Idler Gear, O. S., without nut.....	75 H. P.—C. R. S.
3.50	480 C	Shaft Reverse Idler Gear, O. S., with nut.....	75 & 90 H. P.—C. R. S.
	480 C-1	Pin, Reverse Idler Gear, N. S.....	75 & 90 H. P.—C. R. S.
	481 C	Shaft, Direct Drive Transmission.....	90 H. P.—Nickel Steel
	482 C	Cap for Bevel Pinion Bearing.....	90 H. P.—C. S.
11.11	483 C	Shaft, Transmission Idler, 27/8".....	75 & 90 H. P.—40 Carbon Steel
2.72	484 C	Collar for Direct Drive Trans. Shaft.....	90 H. P.—C. S.
17.87	485 C	Shaft, Direct Drive, only, with Keys Trans., 3".....	75 H. P.—40 Carbon Steel
	486 C	Sliding Clutch Gear.....	90 H. P.—C. I.
	487 C	Piston Ring.....	90 H. P.—C. I.
	488 C	Clutch Lever Connector.....	90 H. P.—C. S.
	489 C	Differential Box Stud, 7/8"x9".....	75 & 90 H. P.—C. R. S.
11.18	490 C	Stationary Drive Shaft, 24" Track, 2 7/16".....	75 H. P.—C. R. S.
12.28	491 C	Stationary Drive Shaft, 30" Track, 2 7/16".....	75 H. P.—C. R. S.
	492 C	Track Spool.....	75 H. P.—C. S.
	492 C-1	Track Spool.....	75 H. P.—C. S.
	492 C-2	Track Spool.....	75 H. P.—Steel Tubing
	493 C	Front Track Idler.....	90 H. P.—C. S.
.85	494 C	Starting Bar, 15/16"x36".....	75 & 90 H. P.—C. R. S.
.25	495 C	Differential Collar Pin, 7/8"x4 11/16".....	75 & 90 H. P.—Simplex Steel
.25	496 C	Lubricator Shaft, 5/8"x11 5/8".....	75 & 90 H. P.—C. R. S.
1.50	497 C	Gear Shifter Shaft, 1 3/16"x37".....	75 & 90 H. P.—C. R. S.
.07	498 C	Clutch Pin, 5/8"x2 3/4".....	75 & 90 H. P.—C. R. S.
.26	499 C	Clutch Pin, 13/16"x3 5/8".....	75 & 90 H. P.—C. R. S.
2.52	500 C	Clutch Shifter Shaft, 1 1/2"x43 7/8".....	75 & 90 H. P.—C. R. S.

C. L. BEST GAS TRACTION CO.

4.80	501 C	Front Wheel Shaft, 2 7/16"x35 1/2".....	75 H. P.—C. R. S.
2.02	502 C	Differential Roller Pin, O. S., without nut, 2 3/16"x6 9/16".....	75 H. P.—C. R. S.
2.37	502 C	Differential Roller Pin, O. S., with Nut	
2.25	502 C-1	Differential Roller Pin, N. S., without Nut,	75 H. P.—C. R. S.
2.60	502 C-1	Differential Roller Pin, N. S., with Nut	
45.40	503 C	Differential Shaft, Special, 4"x75".....	75 H. P.—40 Carbon Steel
	503 C-1	Shaft Clutch, 4".....	90 H. P.—C. R. S.
13.09	504 C	Differential Case, Top.....	75 H. P.—Sheet Steel
13.09	505 C	Differential Case, Bottom.....	75 H. P.—Sheet Steel
11.30	506 C	Draw Bar.....	75 & 90 H. P.—W. I.
4.92	507 C	Draw Bar Hangers.....	75 H. P.—W. I.
2.24	508 C	Hot Air Pipe, complete.....	75 H. P.—Galv. Iron
.20	508 C-1	Hot Air Pipe Ell.....	C. S.
.60	508 C-2	Hot Air Pipe Leader Pipe.....	C. S.
1.75	509 C	Chain Carrier Roller Shaft, 1 1/4"x16".....	75 & 90 H. P.—Seamless Tubing
.15	510 C	Governor Shifter Block, 5/8"x1 1/4".....	75 H. P.—C. R. S.
.40	511 C	Clutch Shoe Spring.....	75 & 90 H. P.—Spring Steel
.65	512 C	Brake Rod Spring.....	75 H. P.—Spring Steel
.60	513 C	Friction Clutch Spring.....	75 & 90 H. P.—Spring Steel
1.25	514 C	Steer Wheel Spring.....	75 & 90 H. P.—Spring Steel
	515 C	Collar on Main Axle, 30" Track Extension	75 H. P.—C. I.
.92	516 C	Equalizer Gear Shaft, 1-1/16"x10 5/8".....	75 H. P.—Simplex Steel
.40	517 C	Steering Worm Shaft, 1-3/16"x10".....	75 & 90 H. P.—C. R. S.
1.75	518 C	Track Shoe, 24".....	75 H. P.—W. I.
2.06	519 C	Track Shoe, 30".....	75 & 90 H. P.—W. I.
.77	520 C	Hub Ring.....	75 & 90 H. P.—W. I.
1.11	521 C	Radiator Tube, 46".....	75 & 90 H. P.—Brass Tubing
1.00	521 C-1	Radiator Tube, 42".....	75 H. P.
.32	522 C	Radiator Brace—Circular.....	75 H. P.—W. I.
.12	523 C	Radiator Brace—Straight.....	75 & 90 H. P.—W. I.
.40	524 C	Bolt Eye or Guide for Power Steer Safety Rod.....	75 H. P.—W. I.
.16	525 C	Washer, Sprocket Axle.....	75 H. P.—Saw Steel
.88	526 C	Rod for Power Steer Safety.....	75 H. P.—W. I.
.10	527 C	Washer Sprocket Axle.....	75 H. P.—W. I.
.96	528 C	Arrow Stand.....	75 & 90 H. P.—W. I.
.10	529 C	Arrow.....	75 & 90 H. P.—Sheet Steel
.83	530 C	Bracket for Worm Steer Segment.....	75 H. P.—W. I.
	531 C	Pin Bevel Gear Thrust.....	90 H. P.—C. R. S.
	532 C	Washer for Bevel Gear Thrust Pin.....	90 H. P.—C. R. S.
	533 C	Key for Clutch Spider.....	90 H. P.—C. R. S.
.92	534 C	Brake Rod, LH.....	75 H. P.—W. I.
.76	535 C	Brake Rod, RH.....	75 H. P.—W. I.
1.03	536 C	Brake Shaft.....	75 H. P.—W. I.
6.84	537 C	Brake Band, complete.....	75 H. P.
1.64	538 C	Foot Brake.....	75 H. P.—W. I.
.15	539 C	Dust Guard Bracket.....	75 & 90 H. P.—W. I.
.16	540 C	Washer for Differential Shaft.....	75 H. P.—Saw Steel
1.50	541 C	Washer for Differential.....	75 H. P.—Ground Steel
.10	542 C	Washer for Differential.....	75 H. P.—W. I.

C. L. BEST GAS TRACTION CO.

1.13	543 C	Key, Pulley End Stationary Drive, $\frac{5}{8}$ "x6"	75 H. P.—C. R. S.
1.11	544 C	Key, Gear End Stationary Drive, $\frac{5}{8}$ "x4 $\frac{1}{2}$ "	75 H. P.—C. R. S.
.10	545 C	Washer for Gudgeon Pin.....	75 & 90 H. P.—W. I.
.16	546 C	Washer for Gudgeon Pin.....	75 & 90 H. P.—Saw Steel
.06	547 C	Washer for Diff. Pinion Pin.....	75 H. P.—Saw Steel
.46	548 C	Eye Bolt for Clutch.....	75 & 90 H. P.—M. S.
.55	549 C	Clutch Shifter Shaft Plate.....	75 & 90 H. P.—W. I.
.60	550 C	Key for Sleeve Gear Shaft, $\frac{5}{8}$ "x4".....	75 H. P.—C. R. S.
.60	551 C	Key for Clutch Spider, $\frac{5}{8}$ "x4".....	75 & 90 H. P.—C. R. S.
1.42	552 C	Key for Transmission Idler, 2 Keys, $\frac{5}{8}$ "x15 $\frac{1}{2}$ ", $\frac{5}{8}$ "x3 $\frac{3}{4}$ "x5 $\frac{3}{4}$ ".....	75 & 90 H. P.—C. R. S.
1.40	553 C	Key for Transmission Idler, 2 Keys, $\frac{5}{8}$ "x4 $\frac{5}{8}$ ", $\frac{5}{8}$ "x3 $\frac{3}{4}$ "x11".....	75 & 90 H. P.—C. R. S.
.93	554 C	Key for Transmission Direct Drive (Long) $\frac{5}{8}$ "x3 $\frac{3}{4}$ "x16 $\frac{1}{4}$ ".....	75 & 90 H. P.—C. R. S.
1.13	555 C	Key for Transmission Direct Drive (Short) $\frac{5}{8}$ "x9/16"x6".....	75 & 90 H. P.—C. R. S.
1.00	556 C	Scraper, RH.....	75 & 90 H. P.—W. I.
1.00	557 C	Scraper, LH.....	75 & 90 H. P.—W. I.
.48	558 C	Scraper Brace (Long).....	75 & 90 H. P.—W. I.
.36	559 C	Scraper Brace (Short).....	75 & 90 H. P.—W. I.
.80	560 C	Scraper Angle.....	75 & 90 H. P.—W. I.
.30	561 C	Eye Bolt for Brake.....	75 H. P.—M. S.
.01	562 C	Cotter Pin for Track.....	75 & 90 H. P.—M. S.
.46	563 C	Handle for Steer Wheel, used on 58 and 58-1.....	75 H. P.—C. R. S.
1.53	564 C	Track Shoe, 22".....	75 H. P.—W. I.
1.53	565 C	Track Shoe, 20".....	75 H. P.—W. I.
1.08	566 C	Shaft for Power Steer Clutch.....	75 H. P.—C. R. S.
.24	567 C	Pin for Power Steer Idler Bevel.....	75 H. P.—C. R. S.
1.25	568 C	Key for Differential Bevel 400 C or 120 $\frac{1}{2}$ C $\frac{5}{8}$ "x3 $\frac{3}{4}$ "x8 $\frac{3}{4}$ ".....	75 H. P.—C. R. S.
.59	569 C	Key for Differential Bevel 399C or 120C, $\frac{5}{8}$ "x9/16"x4 $\frac{3}{4}$ ".....	75 H. P.—C. R. S.
.26	570 C	Pin for Transmission Lever.....	75 & 90 H. P.—C. R. S.
.11	571 C	Track Link Bolt, $\frac{5}{8}$ "x8 $\frac{3}{4}$ ".....	75 & 90 H. P.—M. S.
.12	572 C	Track Shoe Bolt, O. S., $\frac{7}{8}$ "x2 $\frac{1}{4}$ ".....	75 H. P.—M. S.
.15	573 C	Track Shoe Bolt, N.S., Sq. Shank, $\frac{7}{8}$ "x 2 $\frac{1}{4}$ ".....	75 & 90 H. P.—M. S.
.59	574 C	Key for Clutch Collar, $\frac{5}{8}$ "x3".....	75 H. P.—C. R. S.
.09	575 C	Flexible Coupling Bolt, $\frac{3}{4}$ "x3 $\frac{3}{4}$ ".....	75 & 90 H. P.—M. S.
.30	576 C	Washer for Differential Roller Pin.....	75 H. P.—C. R. S.
	577 C	Clutch Shifter Bracket, LH.....	90 H. P.—C. S.
	578 C	Clutch Shifter Fork.....	90 H. P.—C. S.
	579 C	Clutch Shifter Bracket, RH.....	90 H. P.—C. S.
	580 C	Spider for Hand Wheel.....	75 & 90 H. P.—Aluminum
1.00	581 C	Blade for Fan.....	75 & 90 H. P.—No. 16 Saw Steel
	582 C	Rim for Hand Wheel.....	75 & 90 H. P.
	583 C	Lever Clutch Shifter.....	90 H. P.—C. S.
	584 C	Handle for Clutch Shifter Lever.....	90 H. P.—W. I.
	585 C	Rod Lever.....	90 H. P.—W. I.
.25	586 C	Washer or Gasket for Radiator.....	75 & 90 H. P.—Straw Board
.30	587 C	Pipe Flange, $\frac{3}{8}$ ".....	75 & 90 H. P.—Brass
.40	588 C	Pipe Flange, $\frac{1}{2}$ ".....	75 & 90 H. P.—Brass

C. L. BEST GAS TRACTION CO.

.94	589 C	Pipe Flange, 1½"	75 & 90 H. P.—Brass
	590 C	Cover on End Trans. Case	75 & 90 H. P.—C. I.
2.50	591 C	Magneto Cover or Hood	75 & 90 H. P.—Leather
1.50	592 C	Gear Shifter Boot or Cover	75 & 90 H. P.—Leather
4.68	593 C	Spring Bar or Support, 24" Track	75 H. P.—W. I.
5.12	593 C-1	Spring Bar or Support, 30" Track	75 & 90 H. P.—W. I.
2.74	594 C	Spark Arrester, complete	75 & 90 H. P.
1.10	595 C	Pull Bar Pin	75 & 90 H. P.—W. I.
1.74	596 C	Dust Guard on Swing Frame	75 & 90 H. P.—Sheet Steel
1.35	597 C	Track Shoe, 18" Wide	75 H. P.—W. I.
.48	598 C	Link Offset Power Steer Chain	75 & 90 H. P.—M. S.
	599 C	Lever Clutch Shifter (Short)	90 H. P.—C. S.
	600 C	Collar Front Wheel Filler	75 & 90 H. P.
	601 C	Bracket Steering Segment	90 H. P.—W. I.
	602 C	Plate Brake Shaft	90 H. P.—W. I.
	603 C	Case Clutch, Upper	90 H. P.—Sheet Steel
	604 C	Case Clutch, Lower	90 H. P.—Sheet Steel
	605 C	Collar Clutch Thrust	90 H. P.—C. I.
	606 C	Shaft Side Clutch Lever	90 H. P.—C. R. S.
	607 C	Shaft, Front Wheel, 2 7/16"x30"	90 H. P.—C. R. S.
25.00	608 C	Hub Front or Lead Wheel	90 H. P.—C. S.
	609 C	Spring, Main Coil	75 & 90 H. P.—S. S.

MISCELLANEOUS PARTS—75 H. P.

A.
B.

Babbitt, C. L. B., Crank Pin	Special, per lb. \$.54
Babbitt, C. L. B., Journal	.24
Ball Bearing End Truss Collar Differential, 3 pcs.	6.00
Batteries, 6", No. 406	
Batteries, 8", No. 413	
Band for Front or Lead Wheel	24.56

Bolts, Machine, Price per Hundred.

Length in Inches	¼	5/16	¾	7/16	½	9/16 & 5/8	¾	7/8	1	1½	1¾
1½	1.70	2.00	2.40	2.80	3.60	5.20	7.70	10.50	15.10	22.50	30.00
2	1.78	2.12	2.56	3.00	3.86	5.58	8.25	11.20	16.00	23.70	31.50
2½	1.86	2.24	2.72	3.20	4.12	5.96	8.80	11.90	16.90	24.90	33.00
3	1.94	2.36	2.88	3.40	4.38	6.34	9.35	12.60	17.80	26.10	34.50
3½	2.02	2.48	3.04	3.60	4.64	6.72	9.90	13.30	18.70	27.30	36.00
4	2.10	2.60	3.20	3.80	4.90	7.10	10.45	14.00	19.60	28.50	37.50
4½	2.18	2.72	3.36	4.00	5.16	7.48	11.00	14.70	20.50	29.70	39.00
5	2.26	2.84	3.52	4.20	5.42	7.86	11.55	15.40	21.40	30.90	40.50
5½	2.34	2.96	3.68	4.40	5.68	8.24	12.10	16.10	22.30	32.10	42.00
6	2.42	3.08	3.84	4.60	5.94	8.62	12.65	16.80	23.20	33.30	43.50
6½	2.50	3.20	4.00	4.80	6.20	9.00	13.20	17.50	24.10	34.50	45.00
7	2.58	3.32	4.16	5.00	6.46	9.38	13.75	18.20	25.00	35.70	46.50
7½	2.66	3.44	4.32	5.20	6.72	9.76	14.30	18.90	25.90	36.90	48.00
8	2.74	3.56	4.48	5.40	6.98	10.14	14.85	19.60	26.80	38.10	49.50
9	2.90	3.80	4.80	5.80	7.50	10.90	15.95	21.00	28.60	40.50	52.50

C. L. BEST GAS TRACTION CO.

Bolts, Machine, Price per Hundred.

Length in inches	1/4	5/16	3/8	7/16	1/2	9/16 & 5/8	3/4	7/8	1	1 1/8	1 1/4
10	3.06	4.04	5.12	6.20	8.02	11.66	17.05	22.40	30.40	42.90	55.50
11	3.22	4.28	5.44	6.60	8.54	12.42	18.15	23.80	32.20	45.30	58.50
12	3.38	4.52	5.76	7.00	9.06	13.18	19.25	25.20	34.00	47.70	61.50
13	6.08	7.40	9.58	13.94	20.35	26.60	35.80	50.10	64.50
14	6.40	7.80	10.10	14.70	21.45	28.00	37.60	52.50	67.50
15	6.72	8.20	10.62	15.46	22.55	29.40	39.40	54.90	70.50
16	7.04	8.60	11.14	16.22	23.65	30.80	41.20	57.30	73.50
17	11.66	16.98	24.75	32.20	43.00	59.70	76.50
18	12.18	17.74	25.85	33.60	44.80	62.10	79.50
19	12.70	18.50	26.95	35.00	46.60	64.50	82.50
20	13.22	19.26	28.05	36.40	48.40	66.90	85.50
21	29.15	37.80	50.20	69.30	88.50
22	30.25	39.20	52.00	71.70	91.50
23	31.35	40.60	53.80	74.10	94.50
24	32.45	42.00	55.60	76.50	97.50
25	33.55	43.40	57.40	78.90	100.50
26	34.65	44.80	59.20	81.30	103.50
27	35.75	46.20	61.00	83.70	106.50
28	36.85	47.60	62.80	86.10	109.50
29	37.95	49.00	64.60	88.50	112.50
30	39.05	50.40	66.40	90.90	115.50

.60 Bolts for Connecting Rod, 7/8"x7 3/4".

3.60 Bolts for Fly Wheel, 3/4"x3 1/4"

305 Boxes, Steel, Dry Batteries, 14"x8"x9 1/2"

4.80 Boxes, Steel, Tools, 22"x9"x9

Brake Lining, 3/16"x2 1/2", Non Burn.....	per ft.	\$ 1.10
Brake Lining, 1/4"x2 1/2", Non Burn.....	per ft.	1.50
Brake Lining, 3/16"x4", Non Burn.....	per ft.	1.70
Brake Lining, 1/4"x4", Non Burn.....	per ft.	2.20
Brake Lining, 3/16"x2 1/2", Longwear.....	per ft.	.98
Brake Lining, 1/4"x2 1/2", Longwear.....	per ft.	1.30
Brake Lining, 3/16"x4", Longwear.....	per ft.	1.44
Brake Lining, 1/4"x4", Longwear.....	per ft.	1.92
Brake Lining, 3/16"x2 1/2", Thermoid.....	per ft.	1.10
Brake Lining, 1/4"x2 1/2", Thermoid.....	per ft.	1.50
Brake Lining, 3/16"x4", Thermoid.....	per ft.	1.70
Brake Lining, 1/4"x4", Thermoid.....	per ft.	2.20
Brake Lining, 3/4"x5", Thermoid.....	per ft.	2.70
Bracket for Lamp, complete.....		4.52

C

Cable, Low Tension, Primary, 3/16".....	per ft.	.05
Cable, High Tension, Secondary, 5/16".....	per ft.	.10
Carburetors, Schebler, 2 1/2", Model L.....		60.00
Carburetors, Schebler, 2", Model E.....		37.50
Carburetors, Schebler, 2", Model D.....		33.00
Cardboard, per sheet.....		
Cam Shaft with Cams, 1 Spiral, 1 Bevel, Oiler Gear and Bearing....		24.82
Cam Shaft, complete, with all Gears, etc.....		49.82
Canopy Top, Galvanized, Corrugated Armco Iron.....	per sheet	3.84
Chain for Power Steer, Baldwin.....	per ft.	1.54
Chain for Power Steer, Baldwin.....	per length	10.32

C. L. BEST GAS TRACTION CO.

Clamps for Magneto Loom.....	.05
Clamps for Magneto Wire Pipe or Conduit.....	.05
Clutch, Complete.....	69.06
Clutch Lining—See Lining.....	
Coil, Splittorf Dual.....	22.00
Coil, Bosch Dual A.....	22.00
Coil, Eisman.....	17.00
Cock for Water Pump Drain, $\frac{3}{8}$ ".....	
Collars, Ball Bearing, for End Truss Diff. Shaft.....	6.00
Collar for Magneto Control Pipe, $7/16$ " Face, $\frac{3}{8}$ " Hole, $\frac{7}{8}$ " Diam.....	.25
Controller for Electric Starter.....	
Cotters, Spring, Assorted.....per 100	.80
Cups, Grease, No. 00, $\frac{1}{8}$ ", Empress Steel.....	.15
Cups, Grease, No. 0, $\frac{1}{4}$ ", Empress Steel.....	.20
Cups, Grease, No. 1, $\frac{1}{4}$ ", Empress Steel.....	.25
Cups, Grease, No. 2, $\frac{3}{8}$ ", Empress Steel.....	.30
Cups, Grease, No. 3, $\frac{1}{2}$ ", Empress Steel.....	.45
Cups, Grease, No. 4, $\frac{1}{2}$ ", Empress Steel.....	.75
Cups, Oil, No. 1, $\frac{1}{4}$ ", Lunkenheimer Tiger, Brass.....	1.05
Cups, Oil, for Rocker Arm, No. 5.....	.15
Cylinder Head, complete.....	29.87
D	
Disc for Throttle, Saw Steel.....	.06
E	
F	
Fan Spider and Blades.....	8.18
Fan and Bracket, complete.....	31.62
Felt Wool.....per sq. ft.	
Felt, $\frac{1}{2}$ " Wide, $\frac{3}{8}$ " Thick.....per ft.	.06
Felt, $1\frac{1}{2}$ " Wide, $\frac{1}{2}$ " Thick.....per ft.	.07
Funnel, same as in Tool Box Equipment.....	1.25
G	
Grinding Compound for Valves, Clover Brand.....per can	.40
Gasket, Sq., Type "B," Copper, Brass, Asb., $3\frac{5}{8}$ ", for valve cage, top.....	.40
Gasket, McKinn, Copper, Asb., $3\frac{3}{8}$ "x $3\frac{5}{8}$ ", for Valve Cage, bottom.....	.16
Gauges, Pressure, for Oil.....	4.00
Governor, complete, with Shaft.....	20.98
Generator, Aplco, for Lighting System.....	31.00
Generator, Fisher, for Lighting System.....	40.00
Generator, KW, for Lighting System.....	35.00
Grease, Arctic Cup, No. 3.. Write for prices.....	
Grease Cups, No. 00, Empress Steel, $\frac{1}{8}$ " Shank, Pipe Thread.....	.15
Grease Cups, No. 0, Empress Steel, $\frac{1}{4}$ " Shank, Pipe Thread.....	.20
Grease Cups, No. 1, Empress Steel, $\frac{1}{4}$ " Shank, Pipe Thread.....	.25
Grease Cups, No. 2, Empress Steel, $\frac{3}{8}$ " Shank, Pipe Thread.....	.30
Grease Cups, No. 3, Empress Steel, $\frac{1}{2}$ " Shank, Pipe Thread.....	.45
Grease Cups, No. 4, Empress Steel, $\frac{1}{2}$ " Shank, Pipe Thread.....	.75
Grease Cups, No. 5, Wahlstrom, $\frac{1}{4}$ ", for Rocker Arm.....	.15
Grease Cups, No. 1, Lunkenheimer Tiger, $\frac{1}{4}$ ".....	1.05
H	
I	
J	
K	
Keys, Woodroff, for Water Pump Gear.....	.07
Keys, Woodroff, for Oil Pump Gear.....	.05

C. L. BEST GAS TRACTION CO.

Keys, Coil, for Bosch and Splitdorf Coil.....	10
Keys, for Crank Shaft Gear.....	
Keys, Cam Shaft, Whitney.....	10
Key, for Cam Shaft, Straight.....	25
Knuckle Joint, Double, for Oil Steel.....	2.00
Knuckle, complete, for Steering Rod.....	.94
Lacing, Leather, 1/4".....per ft. .03 c per 100 ft.	2.50
Lacing, Leather, 5/16".....per ft. .03 1/2 c per 100 ft.	3.09
Lacing, Leather, 3/8".....per ft. .04 c per 100 ft.	3.75
Lacing, Leather, 7/16".....per ft. .05 c per 100 ft.	4.50
Lacing, Leather, 1/2".....per ft. .06 c per 100 ft.	5.50
Lacing, Leather, 5/8".....per ft. .07 c per 100 ft.	6.50
Lacing, Leather, 3/4".....per ft. .08 c per 100 ft.	7.50
Lever for Relief Cocks (on Motor).....	.50

L

Lever for Priming Cocks (on Motor).....	.50
Lighting System, Fisher, complete.....	75.00
Lighting System, K. W., complete.....	75.00
Lighting System, Presto Light, complete.....	75.00
Lighting System, Aplco, complete, with Trouble Lamp.....	140.00
Lighting System, Battery, 6 Volts, 80 Amperes.....	20.00
Lighting System, Battery, 6 Volts, 100 Amperes.....	27.00
Lighting System, Deck Control, 20 C. P. Lights.....each	1.50
Lighting System Switch, 4 Points.....	1.50
Lighting System Switch, 3 Points.....	
Lining, Non Burn Brake, 3/16"x2 1/2"—See Brake Lining.	
Lining, Non Burn Brake, 3/16"x3 1/4"—See Brake Lining.	
Lining, Non Burn Brake, 3/16"x3 1/2"—See Brakes Lining.	
Lining, Non Burn Brake, 3/16"x4"—See Brake Lining.	
Lining, Thermoid, 1/4"x4"—See Brake Lining.	
Lighting System Generator, Aplco, S R 2.....	31.00
Lighting System Generator, Fisher.....	40.00
Lighting System Generator, K. W.....	35.00
Lighting System Indicating Switch for Aplco System.....	10.00
Lighting System Presto Lite Tank A.....	25.00
Lighting System Presto Lite Tank B.....	18.00
Lighting System Generator Pulley K. W., 5" Diam.....	3.00
Lubricator, Class R, McCord.....	40.00
Lubricator, Hancock.....	40.00
Lamp Bracket, complete, with Lamp Studs.....	4.75

M

Magneto Wire Pipe or Conduit Clamp.....	.05
Magneto Loom Clamp.....	.05
Magneto, Splitdorf.....	65.00
Magneto, Bosch, Z R 4.....	95.00
Magneto and Coil, Splitdorf W.....	81.00
Magneto and Coil, Bosch Z R 4.....	109.00
Magneto, K. W., with Impulse Starter.....	85.00
Magneto, Eiseman.....	58.00
Magneto and Coil, Eiseman.....	75.00

N

Nuts, C. P. Hex, Tapped, 1/4".....each .02 1/2 c per 100	2.00
Nuts, C. P. Hex, Tapped, 5/16".....each .03 c per 100	2.50
Nuts, C. P. Hex, Tapped, 3/8".....each .03 3/4 c per 100	3.25
Nuts, C. P. Hex, Tapped, 7/16".....each .04 1/2 c per 100	3.75

C. L. BEST GAS TRACTION CO.

Nuts, C. P. Hex, Tapped, $\frac{1}{2}$ "	each	.05	c	per 100	4.50
Nuts, C. P. Hex, Tapped, $\frac{5}{8}$ "	each	.06	c	per 100	6.50
Nuts, C. P. Hex, Tapped, $\frac{3}{4}$ "	each	.09	c	per 100	8.50
Nuts, C. P. Hex, Tapped, $\frac{7}{8}$ "	each	.13	c	per 100	12.00
Nuts, C. P. Hex, Tapped, 1"	each	.18	c	per 100	17.50
Nuts, C. P. Hex, Tapped, $1\frac{1}{8}$ "	each	.25	c	per 100	24.00
Nuts, C. P. Hex, Tapped, $1\frac{1}{4}$ "	each	.35	c	per 100	33.00
Nuts, C. P. Hex, Tapped, $1\frac{3}{8}$ "	each	.50	c	per 100	49.00
Nuts, C. P. Hex, Tapped, $1\frac{1}{2}$ "	each	.70	c	per 100	69.00
Nuts, for Adjusting on Swing Frame, 2"					1.00
Nuts for Fan Shaft, $\frac{7}{8}$ "					.13
Nuts for Connecting Rod Bolts, $\frac{7}{8}$ ", Alam.					.13
Nuts for Clutch Eye Bolts, $\frac{5}{8}$ "					.06
Nuts for Clutch Eye Bolts, Castellated, $\frac{5}{8}$ "					.07
Nuts for Connecting Rod, Alam., Castellated, $\frac{7}{8}$ "					.14
Nuts for Transmission Idler Gear Pin, $1\frac{1}{2}$ "					.70
Nuts for Track Tightener Bolt No. 354 C-2					.24

O

Oil, C. L. B., Red Engine—Write for Prices.					
Oil, C. L. B. Gas Cylinder—Write for Prices.					
Oil Cans, No. 5, zinc					.18
Oil Cans, Pump					1.25
Oil Pressure Gauge, Nickel Plated					4.00
Oil Rings				each	.100
Oiler, Hancock					40.00
Oiler, McCord					40.00
Oil Pump, complete					13.32

P

Packing, Mobeline	per lb.	1.25
Packing Asbestos Cord	per lb.	.70
Packing, Permanite	per lb.	
Packing, Garlock	per lb.	
Packing, Rainbow Rubber	per lb.	.80
Packing, Sq. Flax	per lb.	
Pin for Belt Tightener Pulley, Valve Cage Motor		.50
Power Steer Gears and Case, all complete, N. S.		89.50
Power Steer, complete, with Aluminum Center Wood Hand Wheel, N. S., Gears inclosed		134.26
Compound, Clover Brand, for Valve Grinding	per lb.	
Pump, Rotary, for filling Distillate Tank		14.00
Pump, Oil, complete		13.32
Pump, Water, complete		27.82
Pump, 1" Rotary, for Gasoline or Oil		14.00
Pulley for K. W. Lighting Generator, 5"		3.00

R

Radiator, with 155 $\frac{1}{2}$ "x42" Tubes, complete		230.00
Radiator with 155 $\frac{1}{2}$ "x46" Tubes, complete		272.00
Rivets, Copper, for Brake Lining	per lb.	1.00
Reamer, for Valve Seat		10.00
Ring Oiler		1.00
Rocker Arm Washer, 1", Wrought		.02
Roller and Screw for Governor Control Lever		.35

S

Screw for Governor Control Lever		.10
Shaft Cam, complete		24.82
Shaft Cam, complete, with all Gears, Cams, etc.		49.82

C. L. BEST GAS TRACTION CO.

Shims, No. 5, $\frac{1}{8}$ " Brass, for Connecting Rods.....	each	.10
Shims, No. 4, Front End Bearing.....	each	.04
Shims, No. 3, Fly Wheel End Bearing.....	each	.04
Shims, No. 2, Center Bearing.....	each	.03
Shims, No. 1, Connecting Rod, Copper.....	each	.03
Shims, No. 1, Connecting Rod, Zinc.....	each	.03
Solder, Wire.....		
Spark Plug Wrench.....		.26
Spark Arrester, Bird Cage Type.....		15.00
Spoke, Stub End.....		.15
Spring Belt Tightener.....		.30
Spring Washers (see Washers).....		
Spring, Main (outside Coil only).....		5.50
Spring, Main (inside Coil only).....		3.00
Starter, Remy Electric, complete—Write for Prices.		
Starter, Aplco Electric, complete—Write for Prices.		
Starter, Aplco Electric, parts—Write for Prices.		
Aplco Generator, Model A 7 (No. 8585).		
Storage Battery.		
Controller, No. 1310, Type A 7.		
1 Silent Chain, $\frac{5}{8}$ ", P. 4 ft. 8" long.		
(General Sprockets for same, 19 T) & 56 Teeth.		
1 No. 143 Hub, Turned $4\frac{1}{8}$ " to receive chain sprocket.		
Plate $5/16'' \times 14'' \times 37\frac{1}{2}''$, with 8 Bolts.		
Iron Brace, $\frac{1}{2}'' \times 1\frac{1}{2}''$.		
Strainer, Water, complete.....		3.46
Stationary Drive, without Pulley, 24" Track.....		21.12
Stationary Drive, without Pulley, 30" Track.....		22.22
Steel Tool Box.....		
Steel Battery Box.....		
Swing Frame, Right or Left Hand, complete with Rollers.....		177.52
Swing Frame, Right or Left, complete, without Rollers or Gudgeons		90.66
Swing Frame I Beam and Gusset Plate, only.....		25.25

Spring Cotters, Price per Thousand.

Wire Gauge No.....		17	13	11	7	4	1		
Diameter		1/16	3/32	1/8	3/16	1/4	5/16	3/8	1/2
Length	$\frac{1}{2}$	3.50	3.50	5.00
Inches	$\frac{3}{4}$	4.15	4.15	5.85	11.10
	1	4.80	4.80	6.70	12.80	20.00	32.50
	$1\frac{1}{4}$	5.45	5.45	7.55	14.50	23.50	37.50
	$1\frac{1}{2}$	6.10	6.10	8.40	16.20	27.00	42.50	72.00
	$1\frac{3}{4}$	6.75	6.75	9.25	17.90	30.50	47.50	79.20
	2	7.40	7.40	10.10	19.60	34.00	52.50	86.40	148.50
	$2\frac{1}{4}$	10.95	21.30	37.50	57.50	93.60	163.50
	$2\frac{1}{2}$	11.80	23.00	41.00	62.50	100.80	178.50
	$2\frac{3}{4}$	24.70	44.50	67.50	108.00	193.50
	3	26.40	48.00	72.50	115.20	208.50
	$3\frac{1}{4}$	51.50	77.50	122.40	223.50
	$3\frac{1}{2}$	55.00	82.50	129.60	238.50
	$3\frac{3}{4}$	58.50	87.50	136.80	253.50
	4	62.00	92.50	144.00	268.50
	$4\frac{1}{2}$	298.50

C. L. BEST GAS TRACTION CO.

Spring Cotter Assortments.....price, per box .80
Contents—

10—3/32x 3/4	10— 1/8x1 1/4	10—3/16x1 1/2	10— 1/4x2
10—3/32x1	10—3/16x1 1/4	10— 1/4x1 3/4	10—5/16x2
10— 1/8x1			10—5/16x2 1/2

Screws, Cap, Price per Hundred.

Diam. of Screw		1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8	1
Diam. of Head		7/16	1/2	9/16	5/8	3/4	7/8	1	1 1/8	1 1/4
Length of Head		1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8	1
Threads to In.		20	18	16	14	12	11	10	9	8
Length under head to extreme point	1/2	3.00	3.25	3.75	-----	-----	-----	-----	-----	-----
	5/8	3.00	3.25	3.75	-----	5.70	-----	-----	-----	-----
	3/4	3.00	3.25	3.75	4.50	5.70	9.25	-----	-----	-----
	1	3.25	3.50	4.00	4.90	5.90	9.25	12.50	-----	-----
	1 1/4	3.50	3.75	4.25	5.30	6.50	9.50	12.50	18.40	22.75
	1 1/2	3.75	4.00	4.50	5.70	7.10	10.00	13.50	18.40	22.75
	1 3/4	4.00	4.25	4.85	6.10	7.70	10.75	14.50	19.70	22.75
	2	4.25	4.85	5.20	6.50	8.30	11.50	15.50	21.00	25.00
	2 1/4	4.70	5.35	5.55	7.15	8.90	12.60	16.50	22.40	27.25
	2 1/2	5.25	5.80	6.00	7.50	9.50	13.60	17.50	23.70	29.50
	2 3/4	5.75	6.30	6.65	7.90	10.10	14.40	19.00	25.00	31.75
	3	6.25	6.80	7.20	8.40	10.70	15.20	20.60	26.40	34.00
	3 1/2	-----	-----	-----	-----	-----	-----	23.70	30.00	38.50
	4	-----	-----	-----	-----	-----	-----	26.90	33.60	43.00
	4 1/2	-----	-----	-----	-----	-----	-----	30.10	-----	-----
	5	-----	-----	-----	-----	-----	-----	33.30	-----	-----

Screws, Set, Price per Hundred.

Diam. of Screw.		1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8	1
Threads to In.		20	18	16	14	12	11	10	9	8
Length under head to extreme point	1/2	1.80	2.00	2.35	-----	-----	-----	-----	-----	-----
	5/8	1.90	2.10	2.45	2.80	3.30	-----	-----	-----	-----
	3/4	2.00	2.20	2.50	2.90	3.40	5.00	-----	-----	-----
	1	2.15	2.35	2.65	3.10	3.80	5.75	10.00	-----	-----
	1 1/4	2.30	2.50	2.85	3.50	4.30	6.50	11.00	15.50	-----
	1 1/2	2.50	2.70	3.10	4.00	4.80	7.25	12.00	16.20	22.00
	1 3/4	2.75	3.00	3.50	4.50	5.40	8.00	12.80	17.70	24.00
	2	3.25	3.50	4.00	5.15	6.00	8.80	13.60	19.20	26.00
	2 1/4	3.75	4.00	4.50	5.75	6.75	9.60	14.50	20.70	28.00
	2 1/2	4.25	4.50	5.00	6.35	7.50	10.40	15.40	22.20	30.00
	2 3/4	4.75	5.00	5.50	6.75	8.25	11.20	16.30	23.70	32.00
	3	5.25	5.50	6.00	7.20	9.00	12.00	17.30	25.70	34.00
	3 1/4	-----	-----	-----	7.60	9.75	12.75	18.40	26.70	36.00
	3 1/2	-----	-----	-----	8.00	10.50	13.50	19.50	28.20	38.00
	3 3/4	-----	-----	-----	8.50	11.25	14.30	20.75	29.70	40.00
	4	-----	-----	-----	9.00	12.00	15.10	22.00	31.20	42.00
	4 1/4	-----	-----	-----	-----	-----	15.90	23.50	32.70	44.00
	4 1/2	-----	-----	-----	-----	13.50	16.70	25.00	34.20	46.00
	4 3/4	-----	-----	-----	-----	-----	-----	26.50	35.70	48.00
	5	-----	-----	-----	-----	-----	-----	28.00	37.20	50.00

C. L. BEST GAS TRACTION CO.

Screw, Machine, Round and Flat Head, Iron. Price per Gross.

Nos.	2	4	6	8	10	12	14	16	18	20	24
Threads per in.	56	36	32	32	24-32	24	20-24	18	18	18	16
Diam.	.0842	.1105	.1368	.1631	.1894	.2158	.2421	.2684	.2947	.3210	.3737
Length	1/4	.30	.30	.35	.40	.60	.70	.85	-----	-----	-----
Inches	5/16	.32	.32	.37	.44	.65	.75	.90	1.15	-----	-----
	3/8	.32	.32	.37	.44	.65	.75	.90	1.15	1.50	1.90
	1/2	.34	.34	.39	.48	.70	.80	.95	1.20	1.60	2.00
	5/8	.37	.37	.42	.52	.75	.85	1.00	1.25	1.70	2.10
	3/4	.41	.41	.46	.56	.80	.90	1.05	1.30	1.80	2.20
	7/8	.45	.45	.50	.60	.85	.95	1.15	1.40	1.90	2.30
	1	.50	.50	.55	.65	.90	1.00	1.25	1.50	2.00	2.40
	1 1/4	-----	.60	.65	.75	1.10	1.20	1.45	1.75	2.40	2.80
	1 1/2	-----	.70	.75	.85	1.30	1.40	1.65	2.10	2.80	3.20
	1 3/4	-----	.90	.95	1.05	1.50	1.60	1.85	2.50	3.20	3.60
	2	-----	1.10	1.15	1.25	1.70	1.80	2.20	2.90	3.60	4.00
	2 1/4	-----	-----	1.25	1.45	1.90	2.20	2.60	3.30	4.00	4.40
	2 1/2	-----	-----	-----	1.65	2.20	2.50	2.80	3.50	4.40	4.90
	2 3/4	-----	-----	-----	1.90	2.50	2.90	3.20	4.00	4.90	5.40
	3	-----	-----	-----	2.30	2.90	3.50	3.80	4.50	5.60	6.00
		-----	-----	-----	-----	-----	-----	-----	-----	-----	7.40

T

Throttle, complete	-----	.06
Throttle Disc, Saw Steel	-----	-----
Tool Box, Steel	-----	-----
Track, complete, less Shoes, with Chrome Links	each	153.59
Track, complete, less Shoes, with D. F. Links	each	157.39
Track, complete, with 18" Shoes, D. F. Links	each	192.65
Track, complete, with 22" Shoes, D. F. Links	each	195.44
Track, complete, with 24" Shoes D. F. Links	each	199.16
Track, complete, with 30" Shoes, D. F. Links	each	204.59
Track, complete, with 18" Shoes, Chrome Links	each	206.70
Track, complete, with 22" Shoes, Chrome Links	each	215.10
Track, complete, with 24" Shoes, Chrome Links	each	220.76
Track, complete, with 30" Shoes, Chrome Links	each	230.29
Tubing, Copper, 1/8", No. 20	per ft. .10	per lb. 2.00
Tubing, Copper, 1/4", No. 20	per ft. .20	per lb. 1.75
Tubing, Copper, 3/8", No. 20	per ft. .30	per lb. 1.75
Tubing, Copper, 5/16", No. 20	per ft. .25	per lb. 1.50
Tubing, Copper, 7/16", No. 20	per ft. .35	per lb. 1.40

U V

Valve Cage Gaskets, Top	-----	.40
Valve Cage Gaskets, Bottom	-----	.16
Valve Cage complete, with Springs and Valve	-----	13.00
Valve Seating Reamer	-----	10.00

W

Washers, Lock—	-----	-----	-----
Size	Each	per 100	per 1000
1/4" -----	.01	.86	4.24
5/16" -----	.01	.86	4.24
3/8" -----	.01	.86	4.24
1/2", Light	.02	.97	5.40
1/2", Heavy	.02	1.30	9.18
5/8", Light	.02	1.47	9.52

C. L. BEST GAS TRACTION CO.

Size	Each	per 100	per 1000
5/8", Heavy.....	.02	1.64	10.54
3/4", Light.....	.02 1/2	1.33	8.73
3/4", Heavy.....	.02 1/2	1.94	13.34
7/8", Light.....	.03	2.20	15.14
7/8", Heavy.....	.03	2.60	17.74
1", Light.....	.03	2.50	17.08
1", Heavy.....	.03 1/2	3.33	22.48
Washer for Rocker Arm Bracket.....			.02
Waste, No. 1, 10 lb bales, 100 lb bales—Write for Prices.			
Waste, No. 2, 10 lb bales, 100 lb bales—Write for Prices.			
Waste, No. 3, 10 lb bales, 100 lb bales—Write for Prices.			
Water Pump, complete.....			27.82
Water Strainer, complete.....			3.46
Wheel, Front, 10", Special.....			75.00
Wheel, Front, 24", Standard.....			95.00
Wind Shield, front of Motor.....			2.20
Wrench, Spark Plug.....			.26
Wrench, Valve Grinding.....			.25
Wrench, Bosch or Splittorf Magneto.....			.10
Wrench, No. 175, for 2" Adjusting Nuts.....			3.00
Wrench, 10" Trimo Pipe.....			.85
Wrench, 8" Coes Knife Handle.....			.85
Wrench, 12" Coes Knife Handle.....			1.18
Wrench, 15° D. F., Double End, for 3/8"x1 1/2" Nut.....			.45
Wrench, 15° D. F., Double End, for 1/2"x5/8" Nut.....			.75
Wrench, 15° D. F., Double End, for 5/8"x3/4" Nut.....			.95
Wrench, 15° D. F., Double End, for 7/8"x 1" Nut.....			1.95
Wrench, 15° D. F., Single End, for Track Bolt, Special.....			1.00
Wrench, 15° D. F., Single End, for Track Tightener Bolts.....			3.15
Wrench, 15° D. F., Single End, for Diff. Roller Nut.....			1.95

UNITS—CAM SHAFT PARTS

282 C	Bearing, Drive End.....	\$	1.60
269 C	Bearing, Center.....		1.60
270 C	Bearing, Flywheel End.....		1.60
333 C	Cam Shaft.....		7.60
243 C	Cams, Exhaust.....		1.40
244 C	Cams, Inlet.....		1.40
288 C	Gear, Spiral.....		4.25
225 C	Gear, 88 Teeth.....		16.20
226 C	Gear, Magneto Drive.....		8.27
98 C	Gear, Bevel, for Oilcr.....		3.22
	Keys, Whitney, 1/4"x1 1/4", No. 21.....		.10
	Pins, Taper, 2 1/2", No. 5.....		.05
	Pins, Taper, 2 1/2", No. 6.....		.06
	Pins, Straight, 7/4"x2 1/2".....		.03
	Pins, Cotter, 1/8"x1 1/2".....		.01
	Screw Caps, 1/2"x2 1/4".....		.09

CLUTCH PARTS

87 C	Bushing for Spider.....	4.37
548 C	Bolt Eye.....	.46
223	Collar, Clutch Shifting.....	6.72
551 C	Key for Spider.....	.60

C. L. BEST GAS TRACTION CO.

	Lagging, $\frac{1}{4}$ "x4"x15" (See Lining).....	price per ft.	
	Nuts for Eye Bolt, $\frac{5}{8}$ ".....		.06
	Nuts, Castellated, $\frac{5}{8}$ ".....		.07
499 C	Pin, for Clutch, $\frac{13}{16}$ "x $3\frac{5}{8}$ ".....		.26
498 C	Pin, for Clutch, $\frac{5}{8}$ "x $2\frac{3}{4}$ ".....		.07
	Pin, Plain, for Shoe, $\frac{3}{8}$ "x $3\frac{3}{4}$ ".....		.05
	Pins, Cotter, $\frac{3}{16}$ "x $1\frac{1}{2}$ ".....		.02
	Pins, Cotter, $\frac{1}{8}$ "x $1\frac{1}{2}$ ".....		.02
180 C	Pull Block		1.00
	Rivets, Copper, 1", No. 8.....	per lb.	
	Screws, Cap, $\frac{1}{2}$ "x2".....		.09
69 C	Spider		23.67
71 C	Sleeve		7.60
513 C	Spring, Friction Clutch.....		.60
511 C	Spring, for Clutch Shoe.....		.40
292 C	Shoes, with Lagging.....		10.28

GOVERNOR PARTS.

247 C	Ball30
313 C	Bushing, Sleeve.....		3.00
248 C	Collar50
227 C	Gear		6.70
246 C	Housing		5.20
	Pins, Taper, No. 6.....		.06
	Pins, Cotter, $\frac{1}{16}$ "x1".....		.01
245 C	Plate, End.....		3.28
	Pins, Plain, $\frac{3}{8}$ "x $2\frac{1}{8}$ ".....		.05
328 C	Shaft		2.50
335 C	Spring32

DIFFERENTIAL PARTS, OLD STYLE.

149 C	Bushing for Main Bevel Gear.....		8.64
148 C	Bushing for Sleeve, 4" Long.....		5.25
147 C	Bushing for Sleeve.....		7.56
146 C	Bushing for Pinion 121 C.....		1.00
151 C	Bushing for Bull Pinion 111 C.....		9.24
102 C	Bearing or Box, R. H.....		20.12
104 C	Bearing or Box, L. H.....		15.20
103 C	Cap for Bearing No. 102 C.....		12.52
105 C	Cap for Bearing No. 104 C.....		10.44
132 C	Collar for Shaft.....		1.96
133 C	Clutch		7.68
118 C	Gear, Main Bevel only.....		89.77
120 $\frac{1}{2}$ C	Gear, Side Bevel.....		37.82
120 C	Gear, Side Bevel.....		32.30
112 C	Pinion, Main Drive, R. H.....		19.15
111 C	Pinion, Main Drive, L. H.....		24.42
121 C	Pinion, Equalizer.....		6.36
495 C	Pin for Diff. Shaft Collar.....		.25
516 C	Pin for Equalizer Pinion.....		.92
130 C	Sleeve		39.15
503 C	Shaft		45.40

DIFFERENTIAL PARTS, NEW STYLE.

149 C	Bushing for Main Bevel Gear.....		8.64
148 C	Bushing for Sleeve, 4" Long.....		5.25
147 C	Bushing for Sleeve, 6" Long.....		7.56

C. L. BEST GAS TRACTION CO.

146 C	Bushing for Pinion 388 C.....	1.00
102 C	Bearing or Box, R. H.....	20.12
104 C	Bearing or Box, L. H.....	15.20
103 C	Cap for Bearing No. 102 C.....	12.52
105 C	Cap for Bearing No. 104 C.....	10.44
132 C	Collar for Shaft.....	1.96
404 C	Clutch.....	10.32
118 C	Gear, Main Bevel, only.....	89.77
400 C	Gear, Side Bevel, R. H.....	35.10
399 C	Gear, Side Bevel, L. H.....	34.22
415 C	Pinion, Main Drive, R. H.....	19.42
414 C	Pinion, Main Drive, L. H.....	22.06
388 C	Pinion, Equalizer.....	7.51
495 C	Pin for Diff. Shaft.....	.25
516 C	Pin for Equalizer Pinion.....	.92
403 C	Sleeve.....	45.71
503 C	Shaft.....	45.40
547 C	Washer for Equalizer Pin.....	.06

POWER STEER PARTS, NEW STYLE.

412 C	Bushing for Case.....	3.11
413 C	Bushing for Bevel Gear.....	.72
428 C	Bracket for Gear Case.....	1.58
337	Bracket for Worm.....	1.50
338	Bracket with Pin, for 37 (front).....	.50
339	Bracket with Pin, for 337 (back).....	.50
393	Block for Knuckle.....	.30
408 C	Case (top half).....	5.82
409 C	Case (lower half).....	6.12
427 C	Cover for Gear Case.....	.18
470 C	Clips for Plate or Guide No. 469 C.....	.10
420 C	Clutch Dog.....	2.52
411 C	Clutch Shifter or Fork.....	1.35
405 C	Gear, Idler, Bevel.....	11.55
406 C	Gear, Long Hub, Bevel.....	13.86
407 C	Gear, Front Wheel End, Bevel.....	13.57
431 C	Gear, Clutch Attachment used with 432 C and 433 C.....	2.00
432 C	Gear, Long Hub, Bevel, used with 431 C.....	9.38
433 C	Gear, Short Hub, Bevel, used with 431 C.....	9.28
434 C	Gear, Idler, Bevel, used with 431 C.....	9.08
362 C	Hand Wheel with Aluminum Spider.....	5.00
582 C	Hand Wheel Rim (only).....	2.00
580 C	Hand Wheel Spider (only).....	2.75
84	Knuckle.....	1.00
393	Knuckle Block.....	.30
422 C	Lever for Shifting Clutch.....	1.24
424 C	Nut for Shifting Stud.....	.10
469 C	Plate or Guide for Control Rod No. 471 C.....	.86
426 C	Pin for Clutch Shifting Lever.....	.08
471 C	Rod, Power Steer Control.....	3.18
356 C-1	Rod or Shaft for Steering.....	4.66
517 C	Shaft for Worm.....	.40
425 C	Shaft.....	2.01
421 C	Shaft, Shifting Clutch.....	1.01
429 C	Shaft Connecting Power Steer to Worm.....	.52
410 C	Sprocket.....	5.28
349 C	Spring for Worm (Long Section).....	1.00

C. L. BEST GAS TRACTION CO.

349 C-1	Spring for Worm (Short Section).....	.40
246-1	Sprocket on Crank Shaft, 2 $\frac{3}{4}$ " Bore.....	3.75
246-2	Sprocket on Crank Shaft, 3 $\frac{1}{4}$ " Bore.....	3.75
423 C	Stud, Clutch Shifting Lever.....	.09

RADIATOR PARTS, 46".

521 C	Radiator Tubes.....	1.11
278 C	Radiator Tube Plate (brass), Top and Bottom.....	25.00
281	Radiator Sides.....	5.50
299	Radiator Bottom.....	2.25
298	Radiator Top.....	12.50
238	Radiator Inlet Spout for 298.....	3.00
205	Radiator Plug for 298.....	.50
346 C	Radiator Hood or Fan Shield.....	5.06
345 C	Radiator Overflow Pipe.....	.40
344 C	Radiator Hose (Top).....	1.10
352	Radiator Hose (Bottom).....	1.60
343 C	Radiator Hose Clamp (Top or Bottom).....	.25
297	Radiator Fan Spider.....	2.80
581 C	Radiator Fan Blades.....	1.00
210 C	Radiator Fan Shaft only.....	3.20
314 C	Radiator Fan Shaft Ball Truss Collar.....	2.00
	Radiator Tube Bushing.....	.07
	Radiator Tube Packing Asbestos String.....per lb.	1.50
522 C	Radiator Brace, Circular.....	.32
523 C	Radiator Brace, Straight.....	.12
586 C	Radiator Gasket.....	.25

PARTS FOR POWER STEER, OLD STYLE.

208 C	Bracket.....	2.16
338	Bracket with Pin for 337 (Front).....	.50
339	Bracket with Pin for 337 (Rear).....	.50
337	Bracket for Worm.....	1.50
393	Block for Knuckles.....	.30
524 C	Bolt Eye or Guide.....	.40
414	Bushing for 212 and 415.....	1.66
98	Cap for Bracket No. 208 C.....	1.00
470 C	Clip for Guide or Plate No. 469 C.....	.10
211	Clutch, Double.....	3.36
415	Clutch Shifter.....	4.00
416	Guide for Safety Rod.....	.50
469 C	Guide or Plate for Control Rod.....	.86
212	Gear, Bevel, with Clutch.....	6.64
214	Gear, Bevel, Idler, without Clutch.....	5.49
413	Gear, Bevel and Sprocket combined.....	9.30
362 C	Hand Wheel with Aluminum Spider.....	5.00
582 C	Hand Wheel Rim only.....	2.00
580 C	Hand Wheel Spider only.....	2.75
84	Knuckles.....	1.00
393	Knuckle Block.....	.30
422 C	Lever, Clutch Shifter.....	1.24
309 C	Lug for Safety Trip.....	2.14
471 C	Power Steer Control Rod.....	3.18
526 C	Rod, Safety.....	.88
356 C-1	Rod or Shaft for Steering.....	4.66
566 C	Shaft for Power Steer Clutch.....	1.08
567 C	Shaft for Idler Bevel No. 241.....	.24

C. L. BEST GAS TRACTION CO.

517 C	Shaft for Worm.....	.40
429 C	Shaft Connecting Power Steer to Worm.....	.52
246-1	Sprocket on Crank Shaft, $2\frac{3}{4}$ " Bore.....	3.75
246-2	Sprocket on Crank Shaft, $3\frac{1}{4}$ " Bore.....	3.75
349 C-1	Spring for Worm (Short Section).....	.40
349 C	Spring for Worm (Long Section).....	1.00
156 C	Worm	2.20

OIL PUMP PARTS, OLD STYLE.

Used with Valve Cage Motor

39 C	Casing	5.00
40 C	Cover	3.50
	Gasket10
89 C	Gear, Helical.....	4.00
	Key, Whitney, $\frac{1}{4}$ "x1", No. 15.....	.05
330 C	Shaft66
331 C	Shaft, Idler.....	.64
	Packing for Gland, per Ring.....	.05

OIL PUMP PARTS, NEW STYLE.

Used with Removable Cyl. Head Motor

241 C	Body, Lower Half.....	5.70
242 C	Body, Upper Half.....	4.60
	Gasket10
91 C	Gear, Spur.....	1.60
	Key, Whitney, $\frac{1}{4}$ "x1", No. 15.....	.05
330 C	Shaft66
331 C	Shaft, Idler.....	.64
	Screws, Cap, $\frac{3}{8}$ "x1 $\frac{3}{4}$ ".....	.05
	Packing for Gland, per Ring.....	.05

WATER PUMP PARTS, OLD STYLE.

Used with Valve Cage Motor

9 C	Casing with Bushing.....	15.00
10 C	Cover	5.60
19 C	Casing Bushing.....	.90
11 C	Gland68
90 C	Gear, Spur.....	4.00
	Key, Whitney, $\frac{1}{4}$ "x1 $\frac{1}{4}$ ".....	.07
	Packing Ring.....	.05
329 C	Shaft	3.00
316 C	Shaft, Idler.....	.50
443 C	Studs07
	Screws, Cap, $\frac{3}{8}$ "x $\frac{3}{4}$ ".....	.04
	Screws, Cap, $\frac{3}{8}$ "x1".....	.04

WATER PUMP PARTS, NEW STYLE.

Used with Removable Cyl. Head Motor

237 C	Body	15.00
19 C	Bushing for Body.....	.90
10 C	Cover	5.60
11 C	Gland68
90 C	Gear, Spur.....	4.00
	Key, Whitney, $\frac{1}{4}$ "x1 $\frac{1}{4}$ ".....	.07

C. L. BEST GAS TRACTION CO.

	Nuts, 5/16".....	.03
	Packing Ring.....	.05
329 C	Shaft.....	3.00
316 C	Shaft, Idler.....	.50
443 C	Studs.....	.07
	Screws, Cap, 3/8"x3/4".....	.04
	Screws, Cap, 3/8"x1".....	.04

SWING FRAME PARTS AND DRIVE SPROCKETS.

127 C	Box for Front Idler.....	5.00
193 C	Box for Front Idler, R. H.....	3.35
198 C	Box for Front Idler, L. H.....	3.35
295 C	Box for Front Idler, L. H.....	3.25
296 C	Box for Front Idler, R. H.....	3.25
354 C	Bolt for Track Adjuster or Chain Tightener, use with 127 C (without Nuts).....	1.25
354 C-1	Bolt for Track Adjuster or Chain Tightener, use with 193 C and 198 C (without Nuts).....	2.50
354 C-2	Bolt for Track Adjuster or Chain Tightener, use with 295 C and 296 C, without Nuts.....	.83
166 C	Bushing for Main Sprocket.....	8.56
212 C	Bushing for Front Idler, 2 pieces.....	4.98
190 C	Bushing for Track Roller, 2 pieces.....	2.92
125 C	Bracket for Track Rollers.....	5.52
126 C	Bracket for Track Rollers.....	6.00
172 C	Bracket for Track Rollers.....	6.00
196 C	Bracket for Chain Carrier Roller (Front).....	6.84
279 C	Bracket for Chain Carrier Roller (Rear).....	5.58
139 C	Bracket for Chain Tightener.....	1.50
304 C	Bracket for Chain Tightener.....	4.16
201 C	Bracket, Inside (Male).....	4.78
385 C	Bracket, Inside (Male).....	4.90
386 C	Bracket, Outside (Male).....	4.90
191 C	Bracket, Inside (Male).....	4.78
129 C	Bearing for Main Sprocket Axle, O. S.....	9.06
129 C-1	Bearing for Main Sprocket Axle, N. S.....	9.06
128 C	Cap for Front Idler Box No. 127 C.....	3.00
392 C	Collar for Chain Carrier Roller only.....	.36
	Gussets for Truck, 24" Track.....	15.68
	Gussets for Truck, 30" Track.....	18.36
355 C	I Beam, Inside or Outside, 24" Track.....	10.00
355 C-1	I Beam, Inside, 30" Track.....	12.00
217 C	Idler, Front.....	43.64
63 C-1	Plate, Hand Hole in Sprocket, Round.....	1.00
63 C	Plate, Hand Hole in Sprocket, Triangle.....	1.00
186 C	Roller for Track (Outside Flange).....	16.18
187 C	Roller for Track (Inside Flange).....	13.10
60 C	Roller for Track Carrier (with Flange).....	2.00
211 C	Roller for Track Carrier (without Flange).....	1.92
101 C	Sprocket, Main Drive, 24" Track, Chrome.....	109.50
101 C	Sprocket, Main Drive, 24" Track, 40 Carbon.....	92.50
265 C	Sprocket, Main Drive, 30" Track, Chrome.....	119.70
265 C	Sprocket, Main Drive, 30" Track, 40 Carbon.....	101.32
197 C	Slide, L. H., (Male).....	4.78
205 C	Slide, R. H., (Male).....	4.78
192 C	Slide (Female).....	3.00

C. L. BEST GAS TRACTION CO.

384 C	Slide (Female).....	3.00
373 C	Shaft or Gudgeon for Track Rollers.....	3.00
353 C	Shaft for Front Idler.....	4.81
371 C	Shaft for Main Drive Sprocket, 24" Track.....	21.68
371 C-1	Shaft for Main Drive Sprocket, 30" Track.....	26.04
509 C	Shaft for Track Carrier Roller.....	1.75
419 C	Spring, Main, Double Coil.....	8.00
593 C	Spring Bar, with Angle, 24" Track.....	4.68
593 C-1	Spring Bar, with Angle, 30" Track.....	5.12
136 C	Support for Spring (with Rod Threaded).....	5.00
136 C-1	Support for Spring (Large Stem).....	4.92
136 C-2	Support for Spring (Small Stem).....	4.00
137 C	Support for Spring.....	2.40

TOOL BOX EQUIPMENT.

Can, Pump, Oil.....	1.25
Can, 1 gal., for filling Lubricator.....	.70
Cans, No. 5, Spring Bottom.....	.18
Funnel.....	1.25
Hammer, 1½ lb., Machinist.....	1.13
Jack Screw, 2"x12".....	5.00
Screw Driver, 10".....	.25
Vise.....	5.00
Wrench, Pipe, 10".....	.85
Wrench, Coes Knife Handle, 8".....	.85
Wrench, Coes Knife Handle, 12".....	1.18
Wrench, 7/8", Single End, Special for Track Bolt.....	1.00
Wrench, 3/8", Single End, for Track Tightener Bolt.....	3.15
Wrench, 1¼", 15°.....	1.95
Wrench, 3/8"x½" Nut, 15°.....	.45
Wrench, 5/8"x½" Nut, 15°.....	.75
Wrench, ¾"x¾" Nut, 15°.....	.95
Wrench, 7/8"x1" Nut, 15°.....	1.95
Wrench, Spark Plug.....	.26
Wrench, Valve Grinding.....	.25
Wrench, Magneto.....	.10

TRACK PARTS.

571 C	Bolts for Track Link, 5/8"x8¾".....	.11
572 C	Bolts for Track Shoe, 7/8"x2¼".....	.12
573 C	Bolts for Track Shoe (Square Shank), 7/8"x2¼".....	.15
562 C	Cotter or Pin for Track Pin.....	.01
122 C	Links, R. H. (Chrome).....	2.71
122 C	Links, R. H. (Manganese).....	
122 C	Links, R. H. (Drop Forged).....	2.00
122 C-1	Links, R. H. (Drop Forged) (Square Hole).....	2.00
123 C	Links, L. H. (Chrome).....	2.71
	Links, L. H. (Manganese).....	
123 C	Links, L. H. (Drop Forged).....	2.00
124 C	Pins (Drilled for Cotter Pins) (Chrome).....	1.50
124 C	Pins (drilled for Cotter Pins) (Manganese).....	
124 C-1	Pins (Drilled for Cotter Pins) (Drop Forged).....	.78
124 C-2	Pins (with Square Head) (Drop Forged).....	.76
141 C	Spools, Manganese.....	
141 C	Spools, Case Hardened.....	1.15

C. L. BEST GAS TRACTION CO.

518 C	Shoes, 24".....	1.75
519 C	Shoes, 30".....	2.06
564 C	Shoes, 22".....	1.53
565 C	Shoes, 20".....	1.53
597 C	Shoes, 18".....	1.35

TRANSMISSION PARTS, OLD STYLE.

179 C	Bushings for Reverse Gear No. 167 C.....	2.66
150 C	Bushings for Sleeve Gear No. 110 C.....	7.02
113 C	Case, Lower Half.....	67.41
140 C	Case, Upper Half.....	21.00
114 C	Cap for Casing.....	6.64
115 C	Cap for Casing.....	4.77
116 C	Cap for Casing.....	4.88
117 C	Cap for Casing.....	3.36
143 C	Coupling that Keys on 110 C.....	15.04
168 C	Collar for Direct Drive Shaft.....	2.42
106 C	Gear, Low, 36 Teeth.....	30.50
107 C	Gear, 27 Teeth.....	25.29
108 C	Gear, 20 Teeth.....	21.05
109 C	Gear, Sliding, 27 Teeth.....	31.84
110 C	Gear, Sleeve, 18 Teeth.....	41.06
167 C	Gear, Reverse, 15 Teeth.....	18.44
119 C	Pinion, Bevel, 11 Teeth.....	11.52
554 C	Key for Trans. Direct Drive (Long).....	.93
555 C	Key for Trans. Direct Drive (Short).....	1.13
552 C	Key for Trans. Idler (Long).....	1.42
553 C	Key for Trans. Idler (Short).....	1.40
550 C	Key for Sleeve Gear.....	.60
483 C	Shaft, Trans. Idler.....	11.11
485 C	Shaft, Trans. Direct Drive.....	17.87
497 C	Shaft, Gear Shifter.....	1.50
480 C	Shaft for Reverse Gear, without Nut.....	31.12
145 C	Shifting Lever, Lower Section only.....	3.74
144 C	Shifter for Sliding Gear.....	3.69

TRANSMISSION PARTS, NEW STYLE.

179 C	Bushing for Reverse Gear No. 167 C.....	2.66
150 C	Bushing for Sleeve Gear No. 301 C.....	7.02
479 C	Case, Lower Half.....	29.41
140 C	Case, Upper Half.....	21.00
114 C	Cap for Casing.....	6.64
115 C	Cap for Casing.....	4.77
116 C	Caps for Casing.....	4.88
117 C	Cap for Casing.....	3.36
143 C	Coupling that Keys on 301 C.....	15.04
168 C	Collar for Direct Drive Shaft.....	2.42
106 C	Gear, Low, 36 Teeth.....	30.50
107 C	Gear, 27 Teeth.....	25.29
108 C	Gear, 20 Teeth.....	21.05
299 C	Gear, Sliding, 27 Teeth.....	34.42
301 C	Gear, Sleeve, 18 Teeth.....	47.34
167 C	Gear, Reverse, 15 Teeth.....	18.44
554 C	Key for Trans. Direct Drive (Long).....	.93
555 C	Key for Trans. Direct Drive (Short).....	1.13

C. L. BEST GAS TRACTION CO.

552 C	Key for Trans. Idler (Long).....	1.42
553 C	Key for Trans. Idler (Short).....	1.40
550 C	Key for Sleeve Gear.....	.60
119 C	Pinion Bevel, 11 Teeth.....	11.52
483 C	Shaft, Trans. Idler.....	11.11
485 C	Shaft, Trans. Direct Drive.....	17.87
497 C	Shaft, Gear Shifter.....	1.50
480 C-1	Shaft, for Reverse Gear.....	
145 C	Shifting Lever, Lower Section only.....	3.74
144 C	Shifting for Sliding Gear.....	3.69

FRONT OR LEAD WHEEL PARTS.

309	Brackets	2.00
310	Brackets	2.00
65	Box or Bearing for Steer Wheel Shaft.....	5.45
	Bolts for Hub Rings, $\frac{3}{8}$ "x3".....	.04
	Bolts for Lead Wheel, $\frac{7}{8}$ "x16 $\frac{3}{4}$ ".....	.32
78	Cap for No. 65.....	.35
600 C	Collar Spacing, 2 7/16"x2".....	.50
164 C	Collar Spacing, 2 7/16"x2".....	.50
376 C	Cutter or Fellow, $\frac{7}{8}$ "x2 $\frac{1}{2}$ ".....	6.70
376 C-1	Cutter or Fellow, 1"x3".....	8.14
376 C-2	Cutter or Fellow, 1"x3 $\frac{1}{2}$ ".....	9.38
24-1	Hub	25.00
	Knee Irons, $\frac{1}{4}$ "x2"x2"x2".....	.12
	Nuts for Spokes, $\frac{3}{4}$ ".....	.07
	Nuts for Set Screws, $\frac{3}{4}$ " Half Nut.....	.07
	Pipe for Lead Wheel Spreaders.....	.25
520 C	Rings for Hub.....	.77
	Rims (Inside), $\frac{3}{4}$ "x2"x12'.....	7.16
350 C	Spokes with Nuts.....	.40
501 C	Shaft	4.80
514 C	Spring	1.25
409	Spring Buttons.....	.50
	Set Screw for Hub, $\frac{3}{4}$ "x1 $\frac{1}{2}$ ".....	.14
	Tire, $\frac{1}{2}$ "x24"x12'-5".....	53.82

